



**TROOSTWIJK**  
INDUSTRIAL AUCTIONEERS & VALUERS SINCE 1930

**ONLINE AUCTION**

**PHARMACEUTICAL CHEMICAL AND COSMETIC  
EQUIPMENT (FR)**

**Pharmaceutical, chemical and cometical**

11 Ter Rue du Vertuquet - 59960 NEUVILLE EN FERRAIN  
(Neuville en Ferrain)

Closing date: Tuesday **12 DECEMBER** starting 15:00



**Viewing:**

By appointment

11 Ter Rue du Vertuquet - 59960 NEUVILLE EN FERRAIN (France)

*Bidding only on the internet!*

04-12-17 14.45

**[www.TroostwijkAuctions.com](http://www.TroostwijkAuctions.com)**



## Tuesday 12 December 2017 PHARMACEUTICAL CHEMICAL AND COSMETIC EQUIPMENT

### Specific terms and conditions of the online sale

Allocation of the lots	The "Commissaire Priseur" nominates the highest and last bidder and registers him the winning bidder of the lot. Information in "My Troostwijk" and an email confirm the winning bid. The "Commissaire Priseur" tells that a lot is not won if it is taken back by the vendor, because of a lack of bids to reach the reserve price.
Closing date	Tuesday 12 December 2017 starting 15:00 CET
Viewing	<b>By appointment</b> <b>Neuville en Ferrain</b> 11 Ter Rue du Vertuquet 59960 NEUVILLE EN FERRAIN, France
Markup	18.00%
VAT	20.00%
Collection	<b>from Tuesday 19 December until Friday 22 December</b> <b>By appointment</b> <b>from Wednesday 03 January until Friday 19 January</b> <b>By appointment</b> <b>Neuville en Ferrain</b> 11 Ter Rue du Vertuquet 59960 NEUVILLE EN FERRAIN, France
Viewing Instructions	Please note that this concerns an ascending auction sale, preceded by a viewing day. Placing a bid without viewing the equipment is at one's own risk. Please see articles 3 and 6 of the General Conditions.
Payment Details	Your immediate bank payment is required within 48 hours after receipt of the purchase agreement (proforma invoice). Please state your buyer number and the auction name.  For buyers located outside the European Community, the EXA document proving the exportation of lots outside the European Community must be received within six weeks following the auction closing date. Without this document the sale will be considered as a French sale.
Collection Instructions	The buyer is fully responsible for the dismantling, loading and transportation of the bought lots. Troostwijk Auctions cannot accept any responsibility unless indicated otherwise. The delivery (pick-up bought lots) will only take place on the date and time decided BY TROOSTWIJK according to their removal planning and only after the buyer receives his delivery copy.
Prolongation	The seller has agreed to load the lots free of charge on normal trucks. No help will be provided for packaging needs or container loading, though. If a bid is made in the last 5 minutes before the lot closes, the closing time of that lot will be extended with 5 minutes until no bids are made. All lots without any bid will stay open until half an hour after the last closing time bid.
Lots without bid	From all lots without a bid, the closing time is extended with 30 minutes after the last closing time for lots in that auction.
Quantity, capacity, dimensions and weight of goods	Where a lot description contains details of quantities, capacities, dimensions or weights of the goods, these data are indicative only and no rights can be derived from this information. Bidders must satisfy themselves as to the accuracy of such data. If not indicated otherwise, please consider the origin documents of the equipments to be unavailable. Although the information contained herein was obtained from resources deemed reliable, the seller and Troostwijk make no



warranty, expressed or implied as to the accuracy of the information.



Lot	Number	Description	Starting Bid €
1	1	<b>10t crane</b> KONECRANES, KONECRANES traveling crane Capacity 10t Range 13,7 m ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	2,250.00
2	1	<b>10t crane</b> VERLINDE, VERLINDE traveling crane Capacity 10t Range 13,7 m ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	1,500.00
3	1	<b>5t crane</b> KONECRANES, KONECRANES traveling crane Capacity 5t Range 13,7 m ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	900.00
4	1	<b>4t crane</b> VERLINDE, VERLINDE traveling crane Capacity 4t Range 13,7 m ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	600.00
5	1	<b>Bridge crane 3,2t</b> ADC, Bridge crane ADC Capacity 3,2t Range 8.5 m ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	600.00
6	1	<b>Mixing tank type reactor</b> CASTOR & CIE, CASTOR & CIE brand reactor mixing tank made of stainless steel Total volume 3600 liters conical bottom top dome welded, on four gussets, with 1/2 stainless steel shell on the shell and on the bottom On top of tank: nine tubes, a Ø 120 mm sight and a Ø 330 mm inspection hatch with lid Bolted tilt with Ø 120 mm sight On ferrule and on the bottom: a tube for the 1/2 shell, emptying by tubing Ø 42 mm with valve: Stirring: three blades Ø 600 mm at the bottom of the tank, on shaft Ø 60 mm and three breakwaters Control: CEN motor hp 4 hp 3 kw 1400 rpm 220/380 v plus gearbox ANSEN PATENT; stirring speed 190 rpm approx., without electrical cabinet, braided seals; internal dimensions of the tank: Ø 1500 mm x height 200 + 1900 + 200 = 2300 mm; approximate external dimensions: 1650 x 1600 mm x height 4050 mm height under gussets 2200 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	525.00
7	1	<b>Liquid ring vacuum pump</b> SULZER BURCKHARDT, PMZF 2507 C3, SULZER BURCKHARDT liquid ring vacuum pump; Type: PMZF 2507 C3; 15.5 KW - 20 hp - 1500 rpm - 380 volts ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
8	1	<b>Forklift</b> BT, CB1800T, CB1800T BT Forklift Truck, Maximum Load 1650 DaN / 0.50 M / 4.35 M, Batteries to be changed at customer's expense ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
9	1	<b>Big bag drain station</b> Stainless steel big-bag drain station installed on a steel frame Equipped with a hopper with vibrator and a draining screw On the hopper: two pipes with valves, one of which is used for the extraction of fumes and A trap door with swivel cover opening 400 x 300 mm; Feed opening: 1100 x 1100 mm, loading height 2060 mm; hopper outlet on Ø 250 mm tubing with pneumatically operated slide valve; SINFIMASA screw outlet no. 9544, tubing emptying Ø 200 mm - 170 mm pitch - 700 mm empty height; screw drive with CEMP motor hp 4 hp - 3 kw - 1430 rpm - 220/380 v plus reducer; ITALVIBRA vibrator hp 0.64 hp - 0.47 kw - 3000 rpm - 220/380 v; without control cabinet; Approximate external dimensions: 2200 x 1700 mm x height 2500 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
10	1	<b>Vertical mixing tank</b> Vertical mixing tank made of stainless steel with conical bottom, total volume 400 liters, on the shell: a pipe, on the bottom: a drain Ø 100 mm, without valve, shaking: frame driven by SEW motor gearbox 0.5 hp - 0.37 kw - 1400 / 32 rpm - 220/380 v; monobloc transmission, stirring speed 32 rpm, without electrical control cabinet; internal dimensions of the tank: Ø 800 mm x height 700 + 350 = 1050 mm; approximate external dimensions : 1700 x 1150 mm x height 2000 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00



Lot	Number	Description	Starting Bid €
12	1	<b>Liquid cooler</b> KKT-KRAUS, MLB-S7UM50, serial number IK1489-01-99, KKT-KRAUS liquid cooler type: MLB-S7UM50 No. IK1489-01-99 made of steel; Equipped with a COPELAND refrigeration unit with R134A refrigerant, maximum pressure 20 bar; On one side: an inlet and a liquid outlet connected to a circulation pump and a tank, volume 100 liters Approximate external dimensions: 800 x 630 mm x height 1100 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
13	1	<b>Liquid cooler</b> EUROKLIMAT, LPE51, Liquid cooler EUROKLIMAT type: LPE51 on steel mobile chassis; Equipped with refrigeration unit with refrigerant R407C, maximum pressure 27.6 bar, temperature -10 °; On one side: an inlet and a liquid outlet connected to a circulating pump and a tank; circulation pump DAB type JET251T 3 hp - 2.2 kw - 2800 rpm - 220/380 v; Flow rate from 0.6 to 7.2 m3 / h, pressure from 3.4 to 6 bar max; approximate external dimensions: 1500 x 850 mm x height 1800 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
14	1	<b>Central vacuum</b> DELTA NEU, NEUMATIC JK8, Suction unit DELTA NEU type NEUMATIC JK8 steel equipped with four filter cartridges Ø 150 mm approximately The unit is equipped with a dust collector with booster GARDENR it uses the principle of unclogging by compressed air and can thus operate continuously; SIEMENS motor booster 7.5 hp - 5.5 kw - 2900 rpm - 380/660 v On one side: a dusty air intake Ø 60 mm, clean air outlet on one side Ø 50 mm; On the underside : one outlet for dust collection opening 200 x 200 mm, height under drain 520 mm, on frame, with control cabinet, external dimensions approx: 1500 x 850 mm - height 1900 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
15	1	<b>75 liter copper cooker</b> Copper cooker 75 liters double jacket Height overall: 2750 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
16	1	<b>Powder doser</b> ACCURATE, MOD912, Plastic and stainless steel ACCURATE powder dispenser type MOD912 570 x 570 mm hopper feed with lid, dosing screw diameter 80 mm, DC power supply 180V - 4.5A, without chassis, control cabinet, ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
17	1	<b>Powder doser</b> ACCURATE, MOD912, Plastic and stainless steel ACCURATE powder dispenser type MOD912 570 x 570 mm hopper feed with lid, dosing screw diameter 80 mm, DC power supply 180V - 4.5A, without chassis, control cabinet, ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
18	1	<b>Powder doser</b> ACCURATE, MOD912, Plastic and stainless steel ACCURATE powder dispenser type MOD912 570 x 570 mm hopper feed with lid, dosing screw diameter 80 mm, DC power supply 180V - 4.5A, without chassis, control cabinet, ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
19	1	<b>Vertical tubular exchanger</b> SAG, serial number 9587/5, SAG vertical tubular heat exchanger n ° 9587/5 pinned Equipped with 18 stainless steel tubes Ø 16 mm x length 1150 mm, surface 1 m², stainless steel body Ø 170 mm x length 1200 mm, equipped with two Ø 28 mm flange connections 115 mm and Ø 15 mm tubing on Ø 95 mm flange With stainless steel cap with two Ø 40 mm flanges Ø 150 mm flange Approximate external dimensions: 500 x 500 mm x 1600 mm high; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
20	1	<b>Bell filter s/s</b> s/s BELL FILTER, ON FOOTS, BELL DIMENSIONS: DIA 550 MM, HEIGHT 850 MM, BOTTOM BOTTOM WITH 2 TUBULES, SWIVEL BOLT COVER ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00



Lot	Number	Description	Starting Bid €
21	1	<b>Lobe pump</b> WAUKESHA, 030 U2, serial number 1000002693446, Lobe pump WAUKESHA type 030 U2 n ° 1000002693446 made of stainless steel; Inlet and outlet pipes Ø 35 mm; Rotor equipped with two stainless steel lobes driven by; Motor reducer NORD 4 hp - 3 kw - 1425/146 rpm - 220/380 v; pump speed 146 rpm, maximum flow 0.8 m³ / h at a pressure of 1.7 bar; stainless steel base without control cabinet; approx. External dimensions: 900 x 330 mm - height 400 mm ; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
22	1	<b>Central Vacuum</b> LEYBOLD, CV150-65, serial number 1984-710386, Vacuum central LEYBOLD type CV150-65 n ° 1984-710386 made of steel Equipped with a tank dimensions 1000 x 840 mm - height 170 mm - volume 150 liters, suction diameter 14 mm; Pump drive by motor BROOK ANSEN 2 hp - 1.5 kw - 1425 rpm - 220/380 v; monobloc transmission, pumping speed 1425 rpm; with electrical control cabinet; approximate external dimensions: 1300 x 860 mm - height 920 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
23	1	<b>PCM pump</b> PCM, MR25U4, serial number 202673, PCM pump type: MR25U4 n ° 202673 in stainless steel, on the top: Ø 70 mm tubing and tubing Ø 47 mm, on the front Ø 70 mm tubing, pump drive by geared motor SEW 7.5 hp - 5.5 kw - 1400 / 213 rpm - 220/380 v; Monobloc transmission, pumping speed 213 rpm; With stainless steel base, without control cabinet; Approximate external dimensions: 2000 x 350 mm - 380 mm high. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
24	1	<b>HP Cleaners</b> HP KARCHER Gas Cleaners Type HDS 9/16-GAS ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
25	1	<b>HP Cleaners</b> HP KARCHER Gas Cleaners Type HDS 9/16-GAS ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
26	1	<b>Archimedes' screw</b> Undercarriage steel Archimedes screw; Without frame; Screw diameter: 250mm; Not thwarted: 250mm; Central draining 270x180mm; Useful length 2x1800mm; Trough width: 360mm; Length: 3550mm; Overall Dim: 4760x510x560mm; BAUER gearmotor - 1.1kw - 1.5cv 230/400 volts three-phase - 41rpm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
27	1	<b>MIXING TANK</b> AIR LIQUIDE, MIXER TUBE AIR LIQUID, VERTICAL CYLINDRICAL, s/s 316 UNDER RESERVE, VOLUME: 2000 LITERS, WITHOUT LID, ON SKIRT, INTERIOR DIMENSIONS TANK: DIA 1050 MM, HEIGHT 2300 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
28	1	<b>MIXING TANK</b> MERLINC, MIXER TANK "MERLINC", CYLINDRICAL, VERTICAL, STAINLESS STEEL, MOBILE, TOTAL VOLUME: 420 LITERS, BOTTOM BOTTOM, BULK BUMPERED COVER, ON TOP OF TANK: 2 LOADS Ø 100 MM, 5 TUBULES;; ON VIROLE: 1 TUBE, DRAIN; : Ø 23 MM, AGITATOR: 8 RADIAL BLADES, WITH 4 BLADE BREAKERS, WITHOUT MOTOR, FLANGE Ø 200 MM, 4TROUS, INTERRUPT Ø 165 MM, INTERNAL DIMENSIONS TANK: Ø 800 MM, HEIGHT 900 MM, APPROXIMATE EXTERIOR DIMENSIONS : 1000 X 900 MM, HEIGHT 1800 MM; NB: ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
29	1	<b>Beam with base 3,2t</b> ADC, Beam with sommier ADC Capacity 3,2t Range 8,5m ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
30	1	<b>Beam with base 3,2t</b> ADC, Beam with sommier ADC Capacity 3,2t Range 8,5m ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00





Lot	Number Description	Starting Bid €
31	1 <b>Beam with base 3,2t</b> ADC, Beam with sommier ADC Capacity 3,2t Range 8,5m ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
32	1 <b>2t hoist</b> VERLINDE, 2t VERLINDE hoist ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
34	1 <b>2t hoist</b> DEMAG, Hoist 2t DEMAG ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
35	1 <b>Pigtail pump</b> SIHI, 1B SSB SAA, SIHI type 1B SSB SAA pigtail pump made of stainless steel, Suction Ø 32 mm on flange Ø 140 mm, discharge Ø 38 mm on flange Ø 150 mm, pump drive by CEN motor hp 1.5 cv - 1.1 kw - 1360 rpm - 220/380 v plus LEROY SOMER gearbox, transmission by coupling, pump speed approx 660 rpm, on base, without control cabinet, approximate external dimensions: 1220 x 340 mm - height 360 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
36	1 <b>lobe pump</b> HILGE, HYGIR A 400, HILGE lobe pump type HYGIR A 400 in 316 stainless steel subject to availability, maximum flow 15 m³ / h at a pressure of 50 mCE, supply and outlet on tubing Ø 100 mm, without control unit or chassis, approximate external dimensions: 650 x 450 mm - height 350 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
37	1 <b>Agitator</b> LIGHTNIN, LP75, LIGHTNIN stirrer made of LP75 stainless steel, shaft diameter 20 mm Long 1400 mm, tools: 2 double tri-pale and 2 single tri-light, gear motor BROOKHANSEN 0.75 kw - 1 hp - 1400 rpm; Voltage 220/380 volts; monobloc transmission - Speed of agitation 300 rpm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
38	1 <b>Agitator</b> LIGHTNIN, LP75, LIGHTNIN stirrer made of LP75 stainless steel, shaft diameter 20 mm Long 1400 mm, tools: 2 double tri-pale and 2 single tri-light, gear motor BROOKHANSEN 0.75 kw - 1 hp - 1400 rpm; Voltage 220/380 volts; monobloc transmission - Speed of agitation 300 rpm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
39	1 <b>Agitator</b> LIGHTNIN, LP75, LIGHTNIN stirrer made of LP75 stainless steel, shaft diameter 20 mm Long 1400 mm, tools: 2 double tri-pale and 2 single tri-light, gear motor BROOKHANSEN 0.75 kw - 1 hp - 1400 rpm; Voltage 220/380 volts; monobloc transmission - Speed of agitation 300 rpm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
40	1 <b>Agitator</b> LIGHTNIN, LP75, LIGHTNIN stirrer made of LP75 stainless steel, shaft diameter 20 mm Long 1400 mm, tools: 2 double tri-pale and 2 single tri-light, gear motor BROOKHANSEN 0.75 kw - 1 hp - 1400 rpm; Voltage 220/380 volts; monobloc transmission - Speed of agitation 300 rpm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
41	1 <b>Hydraulic unit</b> HIP, HIP hydraulic unit, with HAWKER motor, 15 hp, 1460 rpm, 220/380 v, oil tank Capacity: 30 liters, Approximate external dimensions: 1100 x 700 mm, Height: 1050 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00



Lot	Number	Description	Starting Bid €
42	1	<b>GRANULATOR MILL</b> TORNADO, TORNADO GRANULATOR GRINDER, s/s, VERTICAL ROTOR DIA 250 MM, HEIGHT 100 MM, OPENING HOPPER SUPPLY 150 X 110 MM, CLIPSE COVER, CONTROL: motor CEN 5.50 HP, HP, 2810 TR / MN, 220.380 V + PULLEYS AND BELT ;TRAPEZOIDALE WITHOUT ELECTRICAL CABINET, ON beam, MOBILE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
43	1	<b>Hoist 1t</b> DEMAG, Hoist 1t DEMAG ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
44	1	<b>2t hoist</b> DEMAG, Hoist 2t DEMAG ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
45	1	<b>Panel saw</b> Panel saw ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
46	1	<b>Pump with lobes</b> ALFALAVAL, SRU278/L5, ALFA LAVAL type SRV278 / L5 lobe pump in stainless steel, 1.5 kw motor - 2 hp - 220/380 volts - 1395 rpm, 40 mm diameter inlet and outlet connections, double jacket, without control cabinet ; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	50.00
47	1	<b>Centrifugal pump</b> GUINARD, CPKC25/160, serial number 151076848, GUINARD centrifugal pump type: CPKC25 / 160, stainless steel No. 151076848, flow rate: 4.8 m³ / h, at 38 mce, suction diameter 38 mm, discharge 27 mm, on base, without control, approximate external dimensions: 1000 x 400 mm, height: 430 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
48	1	<b>Parallelepipedic hopper</b> Stainless steel parallelepipedic hopper, volume 200 liters, feed opening 1120 x 600 mm outlet Ø 300 mm with air operated valve, on one side: inspection hatch Ø 350 with pivoting lid equipped with two cleaning nozzles; ; 1450 x 700 mm - height 1180 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
49	1	<b>Plate heat exchanger</b> ACM, serial number 9064, ACM plate heat exchanger type S8IG16-11-TL n ° 9064 with stainless steel plate Equipped with 11 plates dimensions 720 x 130 mm, surface 1.9 m² With two circuits fed by two pipes Ø 26 mm on flange Ø 115 mm and two pipes 26/34 males, operating pressure 1 bar 120 °, test pressure 1.5 bar, stainless steel frame, coolant medium, approximate external dimensions: 460 x 210 mm - height 930 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
50	1	<b>motor</b> LEROY SOMER, LS225MR_T, motor LEROY SOMER type LS225MR_T; Power 60 hp - 45 kw - 1452 rpm - 380/660 v; Nb ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
51	1	<b>Centrifugal pump</b> GMP, B3XR_AT/ST, New GMP centrifugal pump, type: B3XR-AT / ST steel, suction and discharge diameter 85 mm, motor driven pump SMEM 7.5 hp - 5.5 kw - 2900 rpm - 380/660 v; from 3 to 8 m³ / h, pressure from 5 to 24 mCE; On base, without electrical control cabinet; Approximate external dimensions: 800 x 360 mm x height 470 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00





Lot	Number Description	Starting Bid €
52	<b>1 taping machine</b> 3M_MATIC, serial number 1600, 3M-MATIC grinding machine type: 77A No. 1600 made of steel Equipped with two conveyor belts PVC 75 mm wide x length 800 mm and two reel stands, one of which can be manually adjusted by worm gear; COEL 0.18 hp - 0.12 kw - 1340 rpm - 220/380 v; Transmission by pulleys and toothed belt on a common drive shaft; Conveyor linear speed: approx. 17 m / min; with adjustable manual guides, max. packages 480 mm x maximum height 500 mm; On chassis, without control cabinet; Approximate external dimensions: 1800 x 720 mm x height 1680 mm; Nb ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
53	<b>1 PLATE AIR JET SHREDDER</b> GUSEO, PLATE AIR JET SHREDDER; NB ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
54	<b>1 Stainless stirrer</b> Stirrer made of stainless steel with stainless steel lid to be installed on a tank, curved lid Ø 540 mm equipped with three tubes and a sight Ø 80 mm, stainless steel shaft Ø 20 mm - length 600 mm, tools: four blades Ø 350 mm plus three times a blade in stepped blade drive by geared motor FLENDER hp 0.5 hp - 0.37 kw - 1380/46 rpm - 220/380 v; monobloc transmission, stirring speed: 46 rpm; without control cabinet, height under cover 480 mm Approximate external dimensions: 550 x 550 mm - height 1000 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
55	<b>1 Gear pump</b> LEWA, 41S6P22N1AO, LEWA gear pump type 41S6P22N1AO stainless steel; Inlet and outlet ports Ø 8 mm; ATAV motor pump drive hp 0.24 hp - 0.18 kw - 925 rpm - 220/380 v; Monoblock transmission, pumping speed 925 rpm, without control cabinet, approximate external dimensions: 440 x 140 mm - height 200 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
56	<b>1 Metering pump</b> LEWA, EEC 0012 S-11, serial number 422805-010-001, LEWA EEC 0012 S-11 no. 422805-010-001 metering pump made of stainless steel, 8 mm inlet and outlet tubing, max flow 12 l / h, motor pump drive ATAV hp 0.24 cv - 0.18 kw - 1410 rpm - 220/380 v; Pump equipped with a manual adjustment for the flow; Without control cabinet; Approximate external dimensions: 250 x 140 mm - height 450 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
57	<b>1 Metering pump</b> LEWA, EK16, serial number 127953, LEWA type EK16 metering pump no 127953 made of stainless steel, 5 mm inlet and outlet manifold, stroke 15 mm, motor driven pump ATAV hp 0.5 cv - 0.37 kw - 2760 rpm - 220/380 v; equipped with a manual adjustment for the flow; Without control cabinet; Approximate external dimensions: 400 x 250 mm - height 480 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
58	<b>1 Metering pump</b> LEWA, EKM1V, serial number 449146-010-002, LEWA type EKM1V metering pump n ° 449146-010-002 made of stainless steel, inlet and outlet pipe 4 mm, stroke 15 mm, rate 165 l / min, motor pump drive ATAV hp 0.5 cv - 0.37 kw - 1390 tr / min - 220/380 v; Pump equipped with a manual adjustment for the flow rate; Without control cabinet; Approximate external dimensions: 400 x 250 mm - height 470 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
59	<b>1 Vertical storage tank</b> Stainless steel vertical storage tank, volume 750 liters, convex bottom, welded lid, skirt with holes for forklift forks, on the top: tubing, and inspection hatch with tilting lid, opening 420 x 315 mm; the ferrule: a tubing, on the bottom: drain pipe Ø 32 mm without valve, side outlet, internal dimensions of the tank: Ø 900 mm - heights 1150 + 80 = 1230 mm, approximate external dimensions: 1150 x 910 mm - height 1710 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number Description	Starting Bid €
60	<b>1 Vertical storage tank</b> Stainless steel vertical storage tank, volume 750 liters, convex bottom, welded lid, skirt with holes for forklift forks, on the top: tubing, and inspection hatch with tilting lid, opening 535 x 410 mm; the ferrule: a tubing, on the bottom: drain pipe Ø 32 mm without valve, side outlet, internal dimensions of the tank: Ø 900 mm - heights 1150 + 80 = 1230 mm, approximate external dimensions: 1150 x 910 mm - height 1710 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
61	<b>1 gearmotor</b> LEROY SOMER, CB2502,9B3, LEROY SOMER gearmotor type: CB2502.9B3 B3 mounting, shaft Ø 60 mm - length 120 mm, height 200 mm, with CEN motor hp power 7.5 hp - 5.5 kw - 1420/55 rpm - 220/380 v; External dimensions approximate values: 950 x 350 mm - height 400 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
62	<b>1 gearmotor</b> LEROY SOMER, CB2502,9B3, LEROY SOMER gearmotor type: CB2502.9B3 B3 mounting, shaft Ø 60 mm - length 120 mm, height 200 mm, with CEN motor hp power 7.5 hp - 5.5 kw - 1420/55 rpm - 220/380 v; External dimensions approximate values: 950 x 350 mm - height 400 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
63	<b>1 Lot of security barriers</b> Lot of security barriers ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
64	<b>1 booster</b> BUSCH, SB020D2H0UHXX, BUSCH booster type SB020D2H0UHXX, 3 kw - 4 hp - 3000 rpm - 220/380 volts, 340-410 mbar; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
65	<b>1 booster</b> BUSCH, SB020D2H0UHXX, BUSCH booster type SB020D2H0UHXX, 3 kw - 4 hp - 3000 rpm - 220/380 volts, 340-410 mbar; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
66	<b>1 Aluminum chopper</b> CUTTER, Aluminum chopper 450mm dia, without cabinet, ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
67	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
68	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
69	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
70	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number Description	Starting Bid €
71	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
72	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
73	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
74	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
75	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
76	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
77	<b>1 Liquid ring vacuum pump</b> SIHI, LPHE45008, SIHI type liquid ring vacuum pump type: LPHE 45008 made of steel, suction and discharge diameter 40 mm on flange Ø 150 mm, without actuator, average flow: 70 m³ / h for a pressure of 40 ml / bar; approximate: 550 x 330 mm x height 330 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
78	<b>1 VERTICAL CYLINDRICAL TANK</b> VERTICAL CYLINDRICAL VESSEL, s/s, 650 LITERS, BOTTOM BOTTOM, UPPER DOME SODED, ON FOOTS, ON TOP OF TANK: 1 HOLE OF MAN WITH RAJOUT; DRAIN DIA 30 MM; DIMENSIONS: DIA 800 MM, HEIGHT 1500 MM; * ** WITH SKETCH *** ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
79	<b>1 Storage tank with retention</b> ALLIBERT, Storage tank with retention ALLIBERT 1000 liters in HDPE, a manhole on the top of diameter 500mm, double skin of retention, Diameter of the tank: 1000mm Total approximate dimensions: diam: 1200mm x height 1900mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
80	<b>1 Storage tank with retention</b> ALLIBERT, Storage tank with retention ALLIBERT 1000 liters in HDPE, a manhole on the top of diameter 500mm, double skin of retention, Diameter of the tank: 1000mm Total approximate dimensions: diam: 1200mm x height 1900mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
81	<b>1 TRI-CLOVER-ROTARY LOBE PUMP</b> TRI- CLOVER-ROTARY, TRI-CLOVER-ROTARY LOBE PUMP, TYPE: PPRE 60, STAINLESS STEEL, CONTROL: LS 5.50 HP MOTOR-REDUCER, 1430/183 TR / MN, 220.380 V WITHOUT ELECTRICAL CABINET; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number	Description	Starting Bid €
82	2	<b>Metering pump</b> GRUNDFOS, GRUNDFOS DMH 440-10 metering pump, flow rate: 440 lit / h, pressure: 10 bar, 1.5kw / 2hp motor - 220v / 380v - 1420 rpm, polypro body ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
83	1	<b>VERTICAL CYLINDRICAL TANK</b> VERTICAL CYLINDRICAL VESSEL, s/s, 850 LITERS, INCLINED BOTTOM, FLAT DISASSEMBLY, SKIRT, DIA 40 MM, DIMENSIONS: DIA 950 MM, HEIGHT 1250 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
84	1	<b>VERTICAL CYLINDRICAL TANK</b> VERTICAL CYLINDRICAL VESSEL, s/s, 850 LITERS, INCLINED BOTTOM, FLAT DISASSEMBLY, SKIRT, DIA 40 MM, DIMENSIONS: DIA 950 MM, HEIGHT 1250 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
85	1	<b>300 liters tank</b> Tank 300 liters stainless steel on wheels, tank dimensions: Ø 750 - L = 700; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
86	1	<b>Inverter</b> Inverter LANPRO type 5-11, 5000 VA - 230 volts; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
87	1	<b>DUST</b> NEU, DUST COLLECTOR NEU TYPE CYCLAIR 3000. PRESSURE: 500 PASCALS, WITH HOPPER STEEL RECEIVING A CONDUIT DIAMETER 200 MM. ELECTRICAL CABINET; Nb ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
88	1	<b>Lifting table</b> HYMO, Lifting table HYMO type CXX 4-8 Equipped with a steel plate 800 x 600 mm Lifting by central and hydraulic cylinder, force 400 kg, stroke 850 mm Control of the power station by BEVI motor 0.75 hp 0.55 kw 2800 rpm min 220/380 v; without control cabinet; Approximate external dimensions: 800 x 600 mm x height 200 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
89	1	<b>Centrifugal pump</b> KSB, ETANORM-G-040-150-G5, Centrifugal pump KSB type ETANORM-G-040-150-G5 made of steel, suction Ø 65 mm on flange Ø 180 mm, discharge Ø 40 mm on flange Ø 150 mm, motor-driven KSB 7.5 hp - 5.5 kw - 2925 rpm - 380/660 v; Maximum flow rate 50 m³ / h, pressure 28 mCE; On base without control cabinet; Approximate external dimensions: 900 x 300 mm - 410 mm high. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
90	1	<b>Centrifugal pump</b> KSB, ETANORM-G-032-125, Centrifugal pump KSB type ETANORM-G-032-160 made of steel, Suction Ø 50 mm on flange Ø 165 mm, discharge Ø 30 mm on flange Ø 140 mm, drive by motor KSB 5.5 hp - 4 kw - 2815 rpm - 220 / 380 v; Maximum flow 16 m³ / h, pressure 25 mCE; On base, without control cabinet; Approximate external dimensions: 900 x 300 mm - height 400 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
91	1	<b>Metering pump</b> GRUNDFOS, GRUNDFOS DMH 194-10 dosing pump, flow rate: 194 lit / h, pressure: 10 bar, 0.78kw / 1hp motor - 230v / 400v - 1395 rpm, polypro body ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
92	1	<b>Vertical parallelepiped bin</b> Vertical parallelepipedic tank with flat bottom made of stainless steel, total volume 110 liters on mobile stainless steel frame, on the top: a fitted lid fitted with a handle, on the ferrule: two tubes On the bottom: a drain Ø 24 mm with valve Lateral exit Internal dimensions of the tank: 700 x 500 mm - height 340 mm Approximate external dimensions: 900 x 540 mm - height 680 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00



Lot	Number Description	Starting Bid €
93	<b>1 Conical hopper</b> VAC-U-MAX, VAC-U-MAX conical hopper for stainless steel powder, total volume 20 liters, on the top: bolted cover with tubing, on the conical part: tubing, drain on tubing Ø 150 mm with closing flap equipped with a pneumatic cylinder, internal dimensions of hopper: Ø 300 and 150 mm - height 620 mm, approximate external dimensions: 350 x 330 mm - height 800 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
94	<b>1 Vertical hopper</b> Vertical stainless steel hopper on a mobile frame, total volume 400 liters open conical bottom, on the bottom, a drain Ø 200 mm with butterfly valve Internal dimensions of the tank: Ø 880 mm height 480 + 440 = 920 mm Approximate external dimensions: Ø 980 mm height 1250 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
95	<b>1 booster</b> FUJI Electric Motor, FUJI Electric Motor booster, 5.5 hp - 220/380 volts; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
96	<b>1 CONTAINER ASTRO PARALLÉLÉPIPEDIC</b> ASTRO, ASTRO CONTAINER PARALLEL PIPEDIC, VERTICAL PLASTIC, VOLUME: 2200 LITERS, TAPERED BOTTOM, UPPER: 1 TRAPPER WITHOUT COVER Ø 390 MM, 3 PIECES, CENTRAL DRAIN Ø 50 MM, WITHOUT VALVE, ON CHASSIS WITH STEEL CAGE, INDOOR DIMENSIONS OF THE CONTAINER: 1100 X 1100 MM, HEIGHT 2150 MM, APPROXIMATE EXTERIOR DIMENSIONS: 1170 X 1170 MM, HEIGHT: 2400 MM. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
97	<b>1 CYLINDRICAL-TRONCONIC TANK</b> CYLINDRICAL-TRONCONIC TANK ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
98	<b>1 CYLINDRICAL-TRONCONIC TANK</b> CYLINDRICAL-TRONCONIC TANK ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
99	<b>1 Storage tank</b> Storage tank, vertical cylindrical plastic, volume 1500 liters, bottom curved welded lid, placed on skirt; On the top of tank: three pipes, on ferrule tubing, central drain Ø 55 mm with valve; Interior dimensions of the tank: Ø 1050 mm x height 200 + 1500 + 200 = 1900 mm Approximate external dimensions: 1100 x 1050 mm x height 2350 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
100	<b>1 smoothing filter</b> ZSCHOKKE WARTMANN, smoothing filter Zschokke Wartmann No. 5307 stainless steel 316l ; mobile base equipped with a half-shell 304 stainless steel with filter ø 900 mm; area of 0.63 m² ; on the bottom: a drain ø 50 mm flange ø 165 mm ; vertical cylindrical tank with half-shell in 304; total volume 650 liters ; on top: three neck; two eyes ø 80 mm and two cleaning ramps ; drain by manual swivel hatch ø 300 mm ; agitation propeller-type motor driven leroy somer hp 5.5 hp - 4 kilowatts - 1455 rev / min - 220/380 v ; transmission by plus reducing trapezoidal pulleys; Stirring speed 12 rev / min. ; filter equipped with a hydraulic power for up / down agitation and up / down the bottom. ; drive from the central motor siemens 1 cv - 0.75 kW - 1500 rev / min - 380 v. ; on three legs; without electrical control cabinet. ; internal dimensions of the tank: ø 980 mm - height 780 mm ; approximate exterior dimensions: 1600 x 1600 mm - 2500 mm height; agitation raised height 2900 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	1,500.00





Lot	Number Description	Starting Bid €
101	<b>1 filter press</b> CHOQUENET, filter press CHOQUENET No. 8871 on steel frame with support removal stainless driven by hydraulic motor ; equipped 81-chamber plates like 800 x 800 mm polypropylene; area of 88 sqm ; thick support about 35 mm; volume 1.35 m³; effective length between 5700 mm frames ; samac filter equipped with a hydraulic unit for tightening and plate shifting trays ; drive from the central motor abb hp 5.5 - 4 kilowatts - 1420 rev / min - 220/380 v ; with electrical control cabinet ; approximate exterior dimensions: 7600 x 1650 mm x height 1920 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	1,500.00
102	<b>1 mixer extruder</b> GUITTARD, ME60, mixer extruder guittard kind ME60 No. 3064 with steel jacket on the tank and on the sides ; Total volume: 700 liters - capacity: 450/550 liters ; hinged lid with against-weight system with 2 eyes ø 150 mm and a feed hopper ; Tools: 2 z arm cem 30 driven by 2 engines and 25 HP - 22 and 18.5 kilowatts - 1460 and 970 rev / min - 220/380 v ; transmission by pulleys and belts, arm forward speed 26 rev / min, rear arm 19.5 rev / min ; extruder motor driven alsthom 30 hp - 22 kilowatts 1500 rev / min - 380 v piv more with transmission and gearbox ; extrusion speed 53 rev / min, drain opening 105 mm ; etanchéité by braids boxes ; Chassis without electrical control cabinet ; internal dimensions of the tank: 1130 x 900 mm - height 750 and 800 mm ; approximate exterior dimensions: 5300 x 1700 mm - height 2200 mm, height 3100 mm raised lid ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	1,500.00
103	<b>1 mixer turbo-sphere</b> MORITZ, TSI 500, mixer turbo-sphere Moritz; type: type tsi 500, KF 126; No. 549 287; jf 006; 316l stainless steel ; Total volume: 590 liters ; spherique tank; dual stainless steel casing; ; on top of tank: 1 manhole dia 600 mm with rocking cover bolts ; 2 taps ; on ferrule: 2 probes ; drain trap by swiveling diameter 200 mm spout ; agitations: 3 blade tank bottom curved motor-driven alsthom 81 hp; 440 v ; 1820 r / min; + Pulleys and trapezoidal belts; ; 5 - 165 rpm; ; 1 disperser diving with 4 x 3 blade dia 180mm ~ motor drive ; 2 speeds abb motors 11 hp and 17.50 hp; 720 r / min and 1445 r / min; ; 1 disperser lateral motor drive 15 hp; 1500 rev / min; without turbine ; Inner tank size: 1,050 mm dia ; on bati ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	1,500.00
105	<b>1 vacuum mixer</b> GRENIER CHARVET, PL600, vacuum mixer attic charvet type PL600 No. 12255 stainless steel 304l ; comes with 2 stainless steel tanks with rounded bottom of total volume 4500 liters, 1 double stainless steel casing - drain ø 100 mm ; luffing cylinder head mixer - stroke 2000 mm - delivered with hydraulic power motor driven abb hp 3 - 2.2 kW - 1425 rev / min - 220/380 v ; on top: 1 cap with 6 tubes; 1 look ø 170 mm and 1 inspection door with bolt-on cover; opening 520 x 400 mm ; slow stirring: scraping framework driven by gearmotor cen hp 4 hp - 3 kilowatts - from 1400 to 1415 rev / min - 220/380 v - sprockets and chain transmission - speed of the scraping framework: 7 tr / min ; rapid agitation: 1 and 1 deflocculating turbine vortex turbine engine driven hp 60 hp - 45 kilowatts - 1500 rev / min - 380 v - belt and pulley transmission variator; then return on pulleys and V-belts - variable speed turbines electrically gearmotor ; with control console ; without electrical power cabinet ; internal dimensions of the tank: ø 1790 mm x height 1600 + 300 = 1900 mm ; approximate exterior dimensions: 3700 x 2000 mm x height 4100 mm; height 6100 mm head up ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	1,050.00





Lot	Number Description	Starting Bid €
106	<b>1 mixer turbo-sphere</b> MORITZ, TSI 1000, mixer turbo-sphere Moritz; Type: tsi 1000; No. 2076 e; Stainless z2cn18 / 10; ; total volume 1250 liters; ; spherical tank; Double envelope ; on top of tank: 1 manhole dia 750 mm with hinged lid with bolts ; 1 220 mm dia look with lamp; 2 piping and stitching 1; ; on ferrule: 1 manifold ; 1 probe ; agitation: 3 raclantes curved blades tank bottom ; control: 2 speed motor 20 and 60 hp; 1500 and 500 r / min; 380 v; with speed control ; 15 to 90 rev / min or 5 to 30 r / min; ; drain diameter 200 mm + hopper hatch; bailer on hydraulic control group ; motor 0.50 hp; 1500 rev / min; ; without electrical cabinet ; inner dimension tank: 1350 mm dia ; on bati ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	900.00
107	<b>1 straightener-dryer filter under vacuum</b> GUEDU, 750, straightener-dryer filter under vacuum GUEDU; Type: 750; stainless steel; ; cylindrique bell; vertical; with double envelope; Total volume: 535 liters; ; on top: a look ø 150 mm; lighting; seven pipes; ; ferrule on three tubures; a drain ø 85 mm; ; agitation: both arms in "s"; installed on up and down by cylinders and hydrraulique group; race: 400 mm; ; without control; 5.5 hp motor; predictable; ; movable floor; equipped with a perforated plate and filter cloth; ø 930 mm; Surface: 0.69 m²; with jacket; ; the connection between the bell and the bottom is by hydraulic cylinders; plus spikes; ; without electrical control cabinet; ; approximate exterior dimensions: 1800 x 1600 mm; height: 3300 mm; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	750.00
108	<b>1 mixing tank</b> LABBE, mixing tank skua No. 38360a, cylindrical, vertical, stainless steel, ; total: 4,200 liters, with double insulated stainless steel shell, ; rounded bottom, cover welded on 4 stainless steel feet, ; on top of tank: 9 necked 1 oval trapdoor 460 x 380 mm, fitted with a lid with ø 150 mm, tilting bolt, 3 cleaning nozzles, 1 eye ø 150 mm, ; on ring: 5-necked, 1 probe, ; background: 2 tubes, 1 probe, a central drain ø 56 mm, ; without agitation, ; with control group "sew" a dual training has variable speeds ; 15/10 hp, 220/380 v, ; without electrical control cabinet, ; internal dimensions of the tank: ø 1700 mm, overall height 2150 mm, ; approximate exterior dimensions: 2200 x 2000 mm, height 4000 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	750.00
109	<b>1 mixer</b> AMK, mixer amk No. 11944 steel; with double envelope; total: 1,000 liters ; on top: three pipes and a hinged lid with against-equipped weight ; a look ø 300 mm and a cleaning ramp ; on each side of the mixer: a suction duct ; tools: two motor driven arm z Loher two speeds 40 and 55 hp 30 and 42 kilowatts 785 and 1485 rev / min v 380 ; pulley transmission gear and V-belts ; emptying by tilting the tank with hydraulic cylinder and central ; drive from the central engine by 10 hp 7.5 kw Loher 1440 rev / min 220/380 v ; Chassis; without electrical control cabinet ; internal dimensions of the tank: 1110 x 1000 mm x height 900 mm and 1100 ; approximate exterior dimensions: 3900 x 2500 mm x height 2250 mm; cover statement 2750 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	750.00
110	<b>1 mixer</b> VIBRO_MAC, HYDROMIX SS 1800/75, vibro-type mixer mac Hydromix ss.1800 / 75 with 1 stainless steel tank total volume of 1350 liters (2nd feasible tank) ; head up and down by hydraulic cylinder stroke 1050 mm - delivered with hydraulic power driven motor 3 hp 2.2 kw 1420 rev / min 220/380 v ; 1 stainless steel cover with 1 trapdoor; opening 540 x 270 mm ; agitation: paster 3 pale butterfly type ø 1250 mm Shaft ø 100 mm x length 900 mm - driven by hydraulic axial piston motor types mr-1800 / n - delivered with hydraulic power motor driven ea 75 hp 55 kilowatts 1470 rev / min 380/660 v ; mobile tank equipped with a jacket and a steel drain ø 75 mm ; with control console ; without electrical control cabinet ; internal dimensions of the tank: ø 1300 mm x height 1020 mm ; approximate exterior dimensions: 2370 x 1400 mm x height: 2800 mm; head up 3850 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	750.00



Lot	Number Description	Starting Bid €
111	<b>1 horizontal storage tank 9500 liter stainless steel</b> horizontal storage tank 9500 liter stainless steel 316 subject ; two dished ends, on two steel cradles ; on top: eight manifolds and an inspection hatch ø 590 mm with lid bolted ; on the shell: tubing on each end: a drain valve with ø 50 mm ; internal dimensions of the tank: ø 1900 mm - Length 300 + 3300 + 300 = 3900 mm ; approximate exterior dimensions: 4100 x 2100 mm - 2500 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	600.00
113	<b>1 rotary mixer</b> VIDAX, n°6, rotary mixer vidax No. 6 steel single port; 1550 liters useful volume ; horizontal cylindrical tank with two dished ends with six buckets bolted ; mixer equipped with a worm screw and an injection nozzle ; the screws used for feeding and draining ; supply pipe ø 150 mm; drain ø 220 mm ; Discharge outlet height 950 mm ; screw drive by vem motor 3 cv - 2.2 kw - 1410 rev / min - 220/380 v ; pulley transmission gear and V-belts ; speed of rotation of the screw 88 rev / min ; mixer drive with geared motor 1400 rev / min - 220/380 v ; transmission sprockets; speed: 8 tr / min ; Chassis; without electrical control cabinet ; internal dimensions of the tank: ø 1600 mm - length 200 mm + 1600 + 200 = 2000 mm ; approximate exterior dimensions: 4400 x 2150 mm - height 2000 mm ; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	600.00
114	<b>1 mixer arms</b> GUITTARD, M 58, mixer arms "z" guittard; Type: 58 m; No. 2494; steel; ; total: 1000 liters; ; 2 arms "z" steel ; Double steel jacketed tank with hinged lid 2 against-weight; 2 looks ; 140 mm dia and protection grid ; emptying by tilting of the tank ; command cem engine 75 hp; 1470 r / min; hp; 380 v + reducer TEXROPE-speed hansen ; 123 r / min; + Transmission; velocities of arms 20 and 15 rev / min, ; without electrical control cabinet ; Tank internal dimensions; length 1250 mm; 1115 mm width; height 610/850 mm ; External dimensions: ~ 3000 x 2100 mm, height 2200 mm, 3300 mm cover notes ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	600.00
115	<b>1 mixer</b> SEVIN, sevin mixer with stainless steel jacket, total volume 600 liters ; on top: a sliding cover, opening mm 1000 x 900 ; emptying by tilting the tank with hydraulic cylinder and driven by central ; vem 1.5 hp motor - 1.1 kW - 1400 rev / min - 220/380 v ; tools: two motor driven arm z leroy somer 25 hp - 18.5 kW - 1450 rev / min - 380/660 v ; transmission by pulleys and V-belts more referrals gears ; Chassis without electrical control cabinet ; internal dimensions of the tank: 1000 x 900 mm x height 600 and 760 mm ; approximate exterior dimensions: 2600 x 1800 mm x 1700 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	600.00
116	<b>1 mixer with vibro-mac</b> VIBRO-MAC, HYDROMIX, mixer with vibro-mac Hydromix type empty; without tank ; head up and down by hydraulic cylinder - 950 mm stroke - delivered with hydraulic power driven motor 2 hp 1.5 kw 1380 rev / min 220/380 v ; 1 stainless steel lid equipped with: 1 lighting; 1 look ø 120 mm; 1 and 1 cleaning nozzle opening inspection hatch 400 x 200 mm with bolted cover equipped with one eye ø 120 mm ; agitation: paster 3 pale butterfly ø 900 mm shaft ø 88 mm x length 800 mm driven by hydraulic motor - delivered with hydraulic power motor driven 60 hp 45 kilowatts 1470 rev / min 380/660 v ; with cover retaining cylinders ; with control console ; without electrical control cabinet ; approximate exterior dimensions: 1900 x 1100 mm x height: 2550 mm; head up to 3500 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	600.00



Lot	Number Description	Starting Bid €
117	<b>1 mixer with vibro-mac</b> VIBRO-MAC, HYDROMIX, mixer with vibro-mac Hydromix type empty; without tank ; head up and down by hydraulic cylinder - 950 mm stroke - delivered with hydraulic power driven motor 2 hp 1.5 kw 1380 rev / min 220/380 v ; 1 stainless steel lid equipped with: 1 lighting; 1 look ø 120 mm; 1 and 1 cleaning nozzle opening inspection hatch 400 x 200 mm with bolted cover equipped with one eye ø 120 mm ; agitation: paster 3 pale butterfly ø 900 mm shaft ø 88 mm x length 800 mm driven by hydraulic motor - delivered with hydraulic power motor driven 60 hp 45 kilowatts 1470 rev / min 380/660 v ; with cover retaining cylinders ; with control console ; without electrical control cabinet ; approximate exterior dimensions: 1900 x 1100 mm x height: 2550 mm; head up to 3500 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	600.00
118	<b>1 mixing tank reactor type</b> CASTOR & CIE, mixing tank reactor type beaver brand stainless & cie ; total volume 3600 liters conical welded upper dome bottom, four gussets ; half shell with stainless steel on the shell and on the bottom ; on top of tank: new manifolds, a look ø 120 mm and an inspection hatch ø 330 mm with lid ; tilting bolt fitted with a look ø 120 mm ; on sleeve and on the bottom: a tube for half shell, tubing by draining ø 42 mm with valve ; agitation: three blades ø 600 mm tank bottom on shaft ø 60 mm and three breakwater ; command cen hp engine 4 hp three kilowatts 1400 rev / min 220/380 v more reducing patent ansen ; monobloc transmission, agitation speed 190 r / min ; without electrical control panel, sealing with braids ; internal dimensions of the tank: ø 1500 mm x height 200 + 1900 + 200 = 2300 mm ; approximate exterior dimensions: 1650 x 1600 mm x height 4050 mm 2200 mm height gussets ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	525.00
119	<b>1 mixing tank-type reactor</b> DE DIETRICH, mixing tank-type reactor Dietrich No. 1331 stainless steel with stainless steel inner coil ; total volume ; 5527 liters rounded bottom upper dome bolted on four gussets ; on top of bowl seven pipes a look ø 95 mm and an inspection hatch with cover ø 390 mm ; on the bottom: a drain pipe ø 52 mm without valve ; agitation anchor motor driven cen hp 5.5 hp four kilowatts 1400 rev / min 220/380 v ; more transmission gear pulleys and belts, stirring speed 45 rev / min ; without electrical control panel, sealing with braids ; internal dimensions of the tank: ø 1800 mm x height 600 + 1600 + 400 = 2600 mm ; approximate exterior dimensions: 1950 x 1900 mm x height 4300 mm 1900 mm height gussets ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	525.00
120	<b>1 fluidized bed dryer schenck 8 sev 1139 stainless steel</b> SCHENCK, fluidized bed dryer schenck 8 sev 1139 stainless steel ; on top: a bolted cabinet equipped with three tubes ø 240 mm ; on one side: a pipe for air supply 240mm ; was inside: a grid dimensions : 4000 x 250 mm; 1 m² surface area ; on the bottom: a pipe and a product output opening 240 x 110 mm ; transmission of motion by two vibrators rchenck hp 2.3 - 1.7 kw - 1400 rev / min - 220/380 v ; dryer equipped with a self-driven fan aeg motor 5.5 hp - 4 kilowatts - 2870 rev / min - 380/660 v ; transmission by pulleys and v-belts; Fan speed: 2400 rev / min ; on steel frame; without electrical control panel ; approximate exterior dimensions of the dryer: 4500 x 900 mm x 1850 mm height ; approximate exterior dimensions of the fan: 2000 x 1500 mm x 1350 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	450.00
121	<b>1 Fryma ball mill</b> FRYMA, COBALL MILL MSZ 50, Fryma ball mill; Type: Coball-mill msz 50; m No. 012006; stainless steel; ; frustoconical tank 9.60 liters; vertical; Double envelope; up and down on bailer ; cover bolts ; command: 60hp engine Loher 380.660v + + Belt Timing pulleys and coupler ; without electrical cabinet ; on bati ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	450.00



Lot	Number Description	Starting Bid €
122	<b>1 vertical ball mill</b> FRYMA, MSZ18, vertical ball mill Fryma type msz No. 18 f235989 stainless steel ; conical tanks with double-walled stainless steel; capacity 1.1 liters ; on top; a bolted cover ; feeding hopper equipped conical with a jacket; opening 380 mm ; output on gear pump krachttype bto bz oac51 driven motovarateur ; mill drive motor Leumann 9 hp hp 6.8 kw 1440 rev / min 380/660 v ; transmission belt and pulley; grinding speed 1200 rev / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 1000 x 870 mm - 1350 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	450.00
123	<b>1 horizontal mixer</b> GRELBEX, horizontal mixer steel Grelbex; total: 3,000 liters ; on top: two tubes ø 390 mm flange ø 565 mm and ø 200 mm pipe flange 340 mm ; on the following: a pneumatically operated trap door opening 330 x 260 mm ; output on channel; opening 520 x 400 mm ; Front: two overhead access doors; opening 600 x 450 mm ; on the back of the mixer: two slots for mulchers ; tools with tree ten plowshares motor driven brook Crompton ; 50 Cv- power 37 kilowatts - 1410 rev / min - 380 v transmission by pulleys and trapezoidal courroies ; plus reducing brook hansen 1470/233 rev / min; and transmission gears and chain ; etanchéité tree blown by seals ; on without electrical control cabinet frame ; Interior dimensions: ø 1240 mm x 2700 mm length ; approximate exterior dimensions: 3700 x 1420 mm x 1800 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	450.00
124	<b>1 vertical tank 1462 liters</b> DE DIETRICH, vertical tank of Dietrich kind AE1000 No. 54515, in 3008 enamel, total volume 1462 liters ; rounded bottom, top dome nut, embedded, with double shell steel shell and substance ; on top of bowl seven pipes and a trap door without cover, opening: 450 x 350 mm on the bottom: a central drain ø 100 mm, without valve; internal dimensions of the tank: ø 1150 mm - height: 350 + 1000 + 150 = 1500 mm ; approximate exterior dimensions: 1800 x 1800 mm - 2200 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00
126	<b>1 vertical mixing tank-type reactor</b> SCEI, vertical mixing tank-type reactor SCEI No. stainless ic1204 ; rounded bottom, top dome nut, total volume 313 liters ; reactor equipped with a stainless steel half shell on the shell and on the bottom ; on top of bowl seven pipes, two eyes ø 70 mm and an inspection hatch with cover ø 145 mm ; on the bottom four pipes and a drain valve with ø 40 mm ; agitation setting motor driven cen hp 5.5 hp - 4 kilowatts - 1500 rev / min - 220/380 v ; transmission belt and pulley variator more Compabloc gear ratio 1 / 17.91 ; variable mixing speed manually ; four pockets, without electrical control cabinet, mechanical seal ; internal dimensions of the tank: ø 700 mm x height 150 + 650 + 100 = 900 mm ; approximate exterior dimensions: 1000 x 1000 mm x 3000 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00
127	<b>1 cylindrical tank-type reactor, vertical</b> VERTICAL, cylindrical tank-type reactor, vertical stainless steel ; 1500 liters, upper dome demontable, conical bottom, feet, 1/2 shell, ; on top of one tank inspection hatch 400 x 250 mm ; agitation: 4 blades ; drain dia 85mm ; without electrical cabinet ; dimensions tank: dia.1200 mm, height 1300 + 600 = 1900 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00
128	<b>1 tank-type reactor vertical, stainless steel</b> LABBE, VERTICAL, tank-type reactor skua, No. 08873, vertical, stainless steel, ; total: 2232 liters, jacket, on 4 feet ; on top of tank: 1 trapdoor dia 400 mm with cover bolts ; 6 tubes ; on bottom 1 nozzle ; central drain dia 65 mm ; upper dome soda ; agitation robin 2 x 3 blade dia 700 mm ~ + breakwaters, ; control: engine 15 hp, 1400 rev / min, hp, 220 380 + v + trapezoidal pulleys and belts ; speed reducer ; without electrical cabinet ; Tank internal dimensions: 1380 mm dia ~, height 420 + 950 + 350 = 1720 mm ; + Hydraulic group feodor Burgmann Type: 3050 Spa / ao2, 100 liters ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00





Lot	Number Description	Starting Bid €
129	<b>1 vibro-mac drain press</b> VIBRO_MAC, CU 1000 L, vibro-mac drain press type: cu 1000 l tank with a stainless steel ; clamp with central and hydraulic cylinder; strokeabout 1000 mm ; drive from the central motor cen hp 7.5 hp 5.5 kx 1420 rev / min 220/380 v ; approximate exterior dimensions of the tank: 1400 x 1370 mm x height 1200 mm; volume 1350 liters ; approximate exterior dimensions: 2400 x 1200 mm x height: 4400 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00
130	<b>1 Drain tank press without</b> SCHWERDEL, Schwerdtel drain tank press without ; tightening by central and hydraulic actuator; strokeabout 1000 mm ; drive from the central motor vem 10 hp 7.5 kw 1450 rev / min 220/380 v ; with hydraulic control; plate diameter 950 mm ; approximate exterior dimensions: 2000 x 1000 mm x height: 4000 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00
131	<b>1 filter monoplate stainless steel with double jacket</b> ACOMETI, filter monoplate acometi No. 8911 stainless steel with double jacket ; equipped with a vertical tank with bolted cover; total volume 515 liters ; filter ø 855 mm equipped with a screen with holes ø 8 mm; Surface: 0.5 m <sup>2</sup> ; on the cover: a four-necked look ø 80 mm and two inspection openings with lids ; bolted ø 260 mm; on a hatch a look ø 80 mm; on the other trap: a cleaning pad ; on the bottom: a drain ø 55 mm flange ø 165 mm ; tank 3 bar, and void; jacket 6 bar ; internal dimensions of the tank: ø 880 mm - height 230 + 500 + 230 = 960 mm ; approximate exterior dimensions 1150 x 1150 mm - 1600 mm height; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00
132	<b>1 melter equipment agitated rump</b> RUMP EQUIPEMENTS, melter equipment agitated rump No. 1332 copper heating with gas ; cylindrical tank, half-spheric bottom with bolted cover, total volume 1000 liters ; on top: five pipes and a trap door in tilting half-moon opening mm 1000 x 320 ; on the shell: a heating ramp with three burners ; on the bottom: a drain ø 56 mm with air valve ; agitation: stainless steel anchor with two scrapers copper bolted ; Training the agitation by gearmotor sew 3 hp - 2 kilowatts - from 1400 to 1414 rev / min - 220/380 v ; monobloc transmission, agitation speed 14 rev / min ; on stainless steel frame, with electrical control cabinet ; internal dimensions of the tank: ø 1200 mm - height 1,050 mm ; approximate exterior dimensions: 2200 x 1900 mm - 2500 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00
133	<b>1 mixer</b> PAPENMEIER, KMSO, Papenmeier mixer; Type: kmso; No. 1616; stainless steel ; Total volume: 800 liters ; vertical cylindrical tank; steel-cased; background bomb; cover bolted ; on top of tank: 1 345 mm dia pipe; 1 180 mm dia look with lamp; 1 pipe ; emptying lateral dia 220 mm tubing bailer and 345 mm dia ; agitation: 2 blade TOOTHED dia 1000 mm ; control: 2 speed motor garbe 20 hp and 25 hp; 1415 r / min et2955 r / min; 220 v + pulleys and trapezoidal belts + speed reducer 55 and 110 r / min ; without electric cabinet ; dimensions inland tank: 1090 mm dia; height 650 mm; bati on; ; weight: 2250 kg; thickness: virole4.80 mm; bottom 3.80 mm; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00
134	<b>1 mixer stainless steel</b> KARL SCHNELL, mixer stainless karl schnell No. 864 stainless steel with double shell on the shell and ; part on the tank bottom and the extruder screw ; cylindrical conical bottom tank; total: 1,000 liters ; on top: three neck plus two swing covers; opening 1100 x 390 mm ; drain screw extrusion of tubing ø 100 mm with side exit ; agitation scraping frame with tank bottom extrusion screw ; drive gearmotor sew the frame with 4 hp three kilowatts 2800 rev / min 220/380 v ; piece transmission; mixing speed 16 rev / min ; drive screw extrusion gearmotor sew 7.5 hp 5.5 kw 2800/113 rev / min 380/660 v ; transmission by coupling; screw speed 113 rev / min ; on a chassis; without electrical control panel ; internal dimensions of the tank: ø 1200 mm x height 800 + 400 = 1200 mm ; approximate exterior dimensions: 2100 x 1300 mm x 3200 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	300.00



Lot	Number Description	Starting Bid €
135	<p>1 <b>screen chauvinistic kind sift</b></p> <p>CHAUVIN, SIFT 28XKM2, screen chauvinistic kind sift- 28 xkm2 No. 40908 aluminum ; equipped with a sieve mesh floor with stainless steel balls and declogging ; aluminum frame on dimensions 3440 x 1020 mm, 2.8 m<sup>2</sup> area ; on top: a lid equipped with a feed pipe ø 210 mm ; the desous two refusals and a product outlet ø 150 mm ; training cen sieve motor hp 3 hp - 2.2 kw - 1400 rev / min - 220/380 v ; transmission by pulleys and belts, sifting speed 235 tr / min ; Chassis without electrical control cabinet ; approximate exterior dimensions: 3500 x 1700 mm x 1700 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)</p>	300.00
136	<p>1 <b>vertical storage tank</b></p> <p>TECNAL, vertical storage tank Tecnal 1.10.t03 No. 304 stainless steel with insulation ; conical bottom lid welded on three stainless steel legs. total volume 5000 liters ; on top: a five-necked washing ball and a look ø 100 mm ; on the shell: a pipe ø 210 mm and a location for probe ; an oval trapdoor with hinged lid opening 450 x 390 mm ; on the bottom: without a valve discharge pipe ø 300 mm ; internal dimensions of the tank: ø 1580 mm - height 250 + 2500 + 250 = 3000 mm ; approximate exterior dimensions: 1800 x 1750 mm - 3900 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)</p>	270.00
137	<p>1 <b>vertical storage tank</b></p> <p>TECNAL, vertical storage tank Tecnal 1.10.t04 No. 304 stainless steel ; conical bottom lid welded on three stainless steel legs. total volume 5000 liters ; on top: five manifolds, a washing ball and a look ø 100 mm ; on the shell: a pipe, space for a probe and ; an oval trapdoor with hinged lid opening 450 x 390 mm ; on background: a discharge pipe without valve ø 300 mm ; internal dimensions of the tank: ø 1580 mm - height 250 + 2500 + 250 = 3000 mm ; approximate exterior dimensions: 1650 x 1600 mm - 3900 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)</p>	240.00
138	<p>1 <b>tank-type reactor</b></p> <p>BSL, VERTICAL, tank-type reactor bsl, cylindrical, vertical, 316SS subject, ; total volume: 3,000 liters, background bomb, bomb cover bolts, 4 pockets, ; double-quilted jacket, thickness: 3 mm, ; on top of tank: 1 central flange, 1 trapdoor dia 400 mm with hinged lid bolts and 1 look dia 100 mm, 6-necked 1 look dia 100 mm, on shell 2 pipes ; on bottom 2 tubes a central drain dia 95mm ; agitation: 2 x 4 blades staggered, with 3 breakwater ; without electric cabinet, thick dome, shell, bottom: 10 mm, ; tank internal dimensions: dia 1390 mm, height 400 + 1550 + 360 = 2310 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)</p>	225.00
139	<p>1 <b>conveyor</b></p> <p>ORTY, Orty conveyor type iia No. 0304125a on stainless steel frame ; equipped with a perforated plastic strip, width 600 mm x length 10000 mm, driven by ; trommelmotor drum geared motor 0.75 hp - 0.55 kw - 2850/66 rev / min - 220/380 ; linear conveyor speed: 19 m / min ; without electrical control panel, adjustable working height from 600 to 850 mm ; approximate exterior dimensions: 10000 x 800 mm x height 1000 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)</p>	225.00
140	<p>1 <b>horizontal hammermill</b></p> <p>WEIDKNECHT, horizontal hammermill steel weidknecht ; rotor ø 250 mm - 600 mm length equipped with four rows of hammers 7 ; feeding hopper; opening 700 x 425 mm; rejection under grinder ; mill drive motor vem 40 hp - 30 kilowatts - 1450 rev / min 380/660 v ; transmission by pulleys and V-belts ; on the frame; without electrical control panel ; approximate exterior dimensions: 2050 x 1500 mm - 1720 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)</p>	225.00





Lot	Number Description	Starting Bid €
141	<b>1 horizontal mixer</b> LODIGE, EK 60 F, Lodige horizontal mixer types ek 60 fn ° 9703 stainless steel ; cylindrical tank; Total volume: 500 liters with double steel jacket ; on top: a rocker cover bolt; opening 2200 x 600 mm fitted with a hopper ; feed opening 550 x 330 mm ; on the bottom a discharge spout 700 x 300 mm ; tools: shaft provided with finger-shaped horn; with cooling spray and ; control: without engine and without cabinet ; chassis; internal dimensions of the mixer: ø 600 mm x 2200 mm length ; approximate exterior dimensions: 4000 x 2100 mm x 1800 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	225.00
142	<b>1 disperser</b> WILHELM-NIEMANN, BR 93-9,3, disperser "wilhelm-niemann" type: br 93-9.3; No. 861 271; with stainless steel tanks, ; steel shaft ø 70 mm; length: 850 mm ; tool: two flexible blades fixed on stainless steel support, ; command: 9 hp engine; 380 v, transmission by pulleys and belt variator; ; speed of the tool may vary from 15 to 90 rev / min; ; up and down head cylinder and the hydraulic unit; race: 1100 mm ~ ; without eclectic wardrobe control, ; tank size: ø 1400 mm; height: 1040 mm; volume 1500 liters ; approximate exterior dimensions: 2100 x 1700 mm; height: 1950 mm; head up: 3000 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	225.00
143	<b>1 shaking head with stainless steel flange mounting</b> shaking head with stainless steel flange mounting ; tools: three blades ø 950 mm Shaft ø 80 mm x length 2000 mm ; drive of the agitator motor cen hp 15 hp - 11 kilowatts - 1450 rev / min - 220/380 v ; transmission belt and pulley variator more gear manually variable speed agitation the ; flange ø 510 mm with 16 holes ø 20 mm center distance 470 mm ; without electrical control panel, mechanical seal ; approximate exterior dimensions: 1100 x 600 mm x height 3700 mm, height 2200 mm flange ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	225.00
144	<b>1 disperser vibromac</b> VIBROMAC, HYDROMIX, disperser vibromac; Type: Hydromix; ; steel shaft dia 78 mm; height 1050mm; turbine deflocculator dia stainless steel 450 mm ; up and down on hydraulic unit with 2 hp motor mez; 1410 r / min; 230.400 v ; command: hydraulic unit with 50 hp engine marelli; 1460 r / min; 380 V ; without electrical cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	225.00
145	<b>1 mixer stainless steel</b> MORITZ, Moritz mixer stainless steel; steel-cased ; volume: 200 liters with 2 x 2 blade dia 625 mm ; on top of tank: 1 rocker cover bolts dia 640 mm ; + 1 manifold ; possesses a drain by tilting lateral hatch bolts dia 115 mm ; control: Engine 2 cem 35 hp and speeds 25 hp 1430 r / min and 730 rev / min; 220 V ; without electrical cabinet ; dimensions inland tank: 550/750/630 mm dia; height 635 mm ; *** *** with sketch ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	195.00
146	<b>1 storage tank</b> SOLYCI, solyci insulated storage tank, stainless steel 316 subject, ; with indoor coil ø 40 mm, length: 3700 mm Surface: 0.45 m², ; volume 5000 liters, vertical, cylindrical with a flat bottom welded lid, asked, ; on top three pipes, ø 500 mm visit a trap with swiveling bolted lid ; on shell: a level two manifolds for the coil, two taps to probe a drain ø 56 mm, ; internal dimensions of the tank: ø 1800 mm, height 2300 mm, 4 mm thick, ; approximate exterior dimensions: 2300 x 2150 mm, height 2950 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	180.00



Lot	Number Description	Starting Bid €
147	<b>1 cylindrical mixing tank vertical</b> cylindrical mixing tank, vertical, 316SS subject, ; total volume 1000 liters, with half-shell stainless steel ; conical bottom half moon cover with a bolted part, ; on top of bowl seven pipes, a hinged lid bolted, with a pipe with valve ; on shell: four-necked ; background: two tubes, ø 46 mm drain one with pneumatic control valve, ; a central stirrer "moritz" four blades, controlled by gearmotor "abbot" 1 CVs 1440 rev / min, 220/380 v, ; single-piece transmission, stirring speed: 47 rev / min, ; an eccentric homogenizer motor driven "rotor" 5 hp, 1440 rev / min, 380/660 v, ; four feet without electrical control cabinet, ; internal dimensions of the tank: ø 1100 mm total height: 1300 mm, ; approximate exterior dimensions: 1350 x 1250 mm, height 2650 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	180.00
148	<b>1 vertical mixing tank in stainless steel</b> vertical mixing tank in stainless steel with half shell on the shell and on the bottom ; conical bottom lid bolted, total volume: 3,500 liters ; on top of the tank: twelve pipes and an inspection hatch with lid opening 400 x 250 mm ; on background: a pipe and a drain ø 60 mm flange valve ø 170 mm without ; agitation: twice two blades staggered over three breakwater ; drive blade motor abb hp 7.5 - 5.5 kw - 1445 rev / min - 220/380 v ; pulley transmission gear and V-belts sew ; interior dimensions of the tank: ø 1400 mm - height 2200 + 300 = 2500 mm ; approximate exterior dimensions: 1600 x 1600 mm - 3900 mm height ; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	180.00
149	<b>1 Petrin mixer</b> Petrin mixer; stainless steel ; Total volume: 450 liters ; cylindrical tank; vertical background bomb; rotating and mobile; surmounted by a lid ; with opening ; agitation: 2 curved blades and angled aluminum ; control: engine + pulleys and flat belt NOTCHED ; without electrical cabinet ; tipping the whole lid agitation ; dimensions inland tank: 1200 mm dia; height 300 + 270 = 570 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	180.00
151	<b>1 vacuum pump</b> RIETSCHLE, VWZ 402, Rietschle vacuum pump types: VWZ 402 steel ; suction and discharge ø 68 mm ; flow: 400 m³ / h pressure: 0.5 mb ; with cooling circuit ; control: abb hp 15 hp motor - 11 kilowatts - 1455 rev / min 220/380 V ; on frame; with holding tank; without electrical control panel ; approximate exterior dimensions: 1700 x 700 mm - height 1100 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
152	<b>1 chain of two vacuum pumps</b> ALCATEL, RHV2000_RSV600, chain of two vacuum pumps Alcatel Type: rhv2000 and rsv600, steel ; suction ø 150 mm, discharge ø 100 mm, ; speed: 2000 and 600 m³ / h, pression: up to 80 mbar, ; rhv2000 command engine "vem" 7.5 hp, 2890 rev / min, 220/380 v, ; rsv600 command engine "vem" 3 hp, 2810 rev / min, 220/380 v, ; on common chassis with filter media without electrical control cabinet, ; approximate exterior dimensions : 2100 x 900 mm, height 1700 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
153	<b>1 Hydraulic group</b> MANNESMANN REXROTH, A 4 VSG 125 HM 1/22, Hydraulic group Mannesmann Rexroth, 1997 ; Type: 4 vsg 125 hm 1/22 r Brueninghaus Hydromatik ; vq 125 cc, 1000 r / min ; order: cen engine 75 hp, 1470 rev / min, hp, 230 400 V ; without electrical cabinet, ; under cabinet capitonne ; stand ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00



Lot	Number Description	Starting Bid €
154	<b>1 tank type reactor, cylindrical, vertical</b> tank type reactor, cylindrical, vertical, stainless steel, ; total volume 3200 liters, background bomb, upper dome soda, embedded, ; 1/2 steel shell, ; on top of tank: 1 trapdoor dia 410 mm with hinged lid bolts ; and look dia 140 mm ; 5 nozzles ; 1 center flange ; of shell 1 manifold ; background: 1 tube ; 1 temperature sensor ; central drain dia 80mm ; dimensions inland tank: dia 1600 mm, height 300 + 1370 + 150 = 1820 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
155	<b>1 storage tank</b> VALOREL, valorel insulated storage tank, with inner pin, ; volume 3000 liters, vertical, cylindrical with a flat bottom welded lid, asked, ; on top: three-neck ø 500 mm visit a trap with swiveling bolted lid ; on ferrule a level two manifolds for the coil, a drain ø 56 mm, ; internal dimensions of the tank: ø 1400 mm, height 2200 mm, ; approximate exterior dimensions: 1750 x 1700 mm, height 2800 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
156	<b>1 temperature stabilizer</b> THERMOPAC, 36E, thermopac like temperature stabilizer: 36 ° Steel 96918 ; with resistors with a total output of 36 kilowatts; voltage 380 V ; input and output tubes ø 50 mm ; with independent pump Salmson type get.c161.2b driven by ; motor 3 cv - 2.2 kw - 2850 rev / min - 220/380 v ; approximate exterior dimensions: 900 x 900 mm - height 2050 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
157	<b>1 vertical cyclone conical steel</b> vertical cyclone conical steel; surface 15 m <sup>2</sup> ; volume 5000 liters ; on top: a rectangular tubing; opening 700 x 470 mm ; on top of the shell: a pipe ø 600 mm flange ø 705 mm ; cyclone with a conical bottom swivel mounted on pneumatic vibrator plus cylinders type bm130 wz / 3 ; driving the vibrator motor 0.24 hp - 0.18 kw - 3000 rev / min - 220/380 v ; dimensions of the conical bottom ø 760 mm and 70 mm x height 650 mm ; chassis with dampers; without electrical control panel ; inside dimensions of Cylon: ø 1600 mm x height 1200 mm on the cylindrical part, ; ø 1600 mm on the top of the cone and ø 760 mm on the bottom x height 2650 mm ; approximate exterior dimensions: 2050 x 1850 mm x height 6000 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
158	<b>1 horizontal tubular exchanger</b> CIAT, horizontal tubular ciat exchanger No. 82 16930 hairpin; Chassis ; steel body ø 350 mm length 2600 mm with the top and bottom tubing ø 150 mm ; flange ø 285 mm and two nozzles 20/27 mm ; with a cap provided with two stainless steel tubes ø 110 mm flange ø 220 mm ; consisting of 204 copper tubes ø 15 mm in length 2600 mm surface of 25 m <sup>2</sup> ; approximate exterior dimensions: 3100 x 460 mm height 1500 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
159	<b>1 leaf crusher</b> ADLER, steel alder leaf crusher equipped with a rotor ø 500 mm - 600 mm long with two rows of four bolted knife ; length of each blade 300 mm; mill equipped with a perforated grid with holes ø 10 mm ; rotor drive motor FIMM hp 20 hp - 15 kilowatts - 1430 rev / min - 380/660 v ; transmission by pulleys and V-belts; grinding speed 560 rev / min ; feed hopper hinged grinding chamber; hopper opening 635 x 270 mm ; on top of the hopper: a manifold for the suction of fumes and two cleaning nozzles ; rejection in mill; opening 570 x 530 mm Discharge outlet height 880 mm ; chassis; without electrical control panel ; approximate exterior dimensions: 1650 x 1100 - 2200 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00



Lot	Number Description	Starting Bid €
160	<b>1 crusher rotor stator online three floors</b> crusher rotor stator online three floors; steel, ; horizontal model; steel rotor stator; ; feeding tubes ø 35 mm; Output ø 30 mm; ; control: abb motor; hp; 60 hp; 2960 rev / min; 380/660 v, ; grinding speed: 2960 rev / min, ; without electrical control cabinet, ; approximate exterior dimensions: 750 x 500 mm; length 1400 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
161	<b>1 bell-type filter</b> CALMIC, FS 8528, bell-type filter Calmic fs 8528; No. 71763; Polished stainless ; equipped eight plates ø 450 mm; Surface: 1.5 m²; manual tightening ; hinged lid; bolt; with a pipe ; bowl ø 520 mm x height 480 mm; Volume: 100 liters ; on the bottom: two tubes ; on mobile chassis ; approximate exterior dimensions: 1000 x 1000 mm x height: 1700 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
162	<b>1 cylindrical mixing tank</b> cylindrical melangeuse tank, vertical, stainless steel 316 (subject) insulated, ; total volume 1800 liters, conical bottom, bomb lid soda, 3 feet ; on top of tank: 1 pear spray, ; 4 taps ; on ferrule: 1 trapdoor oval 440 x 310 mm with hinged cover bolts, ; 4 taps ; agitation: 3 blade dia 450 mm at the bottom of shell: ; command: motovariator sew 0.50 hp, 1400 to 1480 rev / min, 220 380 v ; background: 1 sensor ; 1 stitching ; central drain dia 35 mm ; dimensions inland tank: dia 1045 mm, height 130 + 2070 + 130 = 2330 mm ; without electric cabinet; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
163	<b>1 mixing tank stainless steel</b> mixing tank stainless steel ; cylindrical tank, vertical, curved bottom, total volume: 500 liters, with double insulated envelope ; on top of the tank: four tubes, a 240mm inspection hatch with hinged lid bolted ; on ring: three slots gussets, six total power resistors: 6 kilowatts ; background: a drain ø 28 mm with valve ; slow stirring: anchor controlled gear motor eberhard 1.5 hp, 930 / 21.5 rev / min, 220/380 v ; monobloc transmission speed of agitation: 21.5 rev / min ; rapid agitation defloculator controlled motor acec 1.3 hp, 685 rev / min, 220/380 v monobloc transmission, agitation speed: 685 r / min ; without electrical control cabinet ; etanchéité by braids ; interior dimensions the tank: ø 800 mm x 1150 mm total height ; approximate exterior dimensions: 1300 x 1200 mm x 2250 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
164	<b>1 vertical mixing tank</b> HONORE, vertical mixing tank honors No. 92090, stainless steel mobile frame. Total volume: 230 liters, rounded bottom, cover up and down actuator and hydraulic power, ; on top: two tubes, a look ø 205 mm, with cover, ; on the bottom: a drain pipe ø 52 mm, side exit, ; agitation defloculator eccentric ø 200 mm shaft ø 48 mm, length 850 mm, ; control: engine and hydraulic pump "volvo" hp, with central "sevmhy" ; Central control: engine "abbot" hp, 7.5 hp, 1445 rev / min, 220/380 v, ; Variable agitation speed 320-1480 rev / min, ; with hydraulic control console, ; internal dimensions of the tank: ø 600 mm, height: 700 + 140 + 140 mm, ; approximate exterior dimensions: 2400 x 1200 mm, height 2500 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
165	<b>1 vertical mixing tank 2360 liters</b> vertical mixing tank in stainless steel, total volume 2360 liters ; domed bottom lid bolted and inner welded four gussets ; on top of tank: 10 pipes an inspection hatch ø 350 mm with lid bolted ; on the bottom: a drain ø 36 mm without valve ; agitation eccentric rayneri centripetal ø 95 mm Type: t95n controlled: ; cem hp 1.5 hp motor 1415 rev / min 220/380 v monobloc transmission ; stirring speed: 1415 rev / min, without electrical control panel ; internal dimensions of the tank: ø 1300 mm, height: 200 + 1500 + 200 = 1900 mm ; approximate exterior dimensions: 1650 x 1650 mm, height 2600 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00



Lot	Number Description	Starting Bid €
166	<b>1 vertical mixing tank 2360 liters</b> METALNOR, vertical mixing tank metalnor stainless total volume: 2360 liters ; bolted cover curved bottom welded inside, four pockets ; on top of tank: 7 tubes an inspection hatch ø 350 mm with lid bolted ; on the bottom: a drain ø 36 mm without valve ; eccentric agitation moritz homogenizer ø 200 mm, controlled by ; motor cem hp 5.5 hp 1430 rev / min 220/380 v, single-piece transmission ; stirring speed: 1430 rev / min, without electrical control panel ; internal dimensions of the tank ø 1300 mm height 200 + 1500 + 200 = 1900 mm ; approximate exterior dimensions: 1650 x 1650 mm height 2600 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
167	<b>1 mixing tank stainless steel</b> mixing tank stainless steel ; convex bottom, bolted cover. total volume 1200 liters ; on top of tank: six manifolds and a half moon swinging trapdoor opening 1000 x 350 mm ; on the bottom: a drain pipe ø 80 mm to 200 mm flange, valve without ; agitation: ø deflocculator 380 mm with 65 mm dia shaft driven ; engine cem 40 hp - 30 kilowatts - 1460 rev / min - 380/660 v ; monobloc transmission, mixing speed 1460 rev / min ; on three gussets, without electrical control panel ; internal dimensions of the tank ø 1090 mm x height 1250 + 100 = 1350 mm ; approximate exterior dimensions: 1350 x 1300 mm x 2500 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
168	<b>1 vertical mixing tank volume 3600 liters</b> vertical mixing tank in stainless steel, total volume 3600 liters ; rounded bottom, welded cover with half-shell steel on the lower part of the shell and on the bottom ; to the top of tank: five pipes and a half-moon trapdoor opening 1500 x 760 mm ; on the bottom: a drain ø 52 mm without valve side outlet ; eccentric agitation: typhoon No. 7,712,438 three blades ø 200 mm on three floors plus ; a deflocculator ø 200 mm on the bottom, with shaft ø 50 mm ; drive of the shaft engine 30 hp - 22 kilowatts - 1465 rev / min - 380/660 v ; monobloc transmission, mixing speed 1465 rev / min ; on three steel legs, without electrical control panel ; internal dimensions of the tank: ø 1500 mm - height 2100 + 150 = 2250 mm ; approximate exterior dimensions: 1800 x 1650 mm - 4250 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
169	<b>1 vacuum mixer week</b> SEM, HELIGLOBE GM 50, vacuum mixer week; Type: heliglobe 50 gm; No. 13875; stainless steel; ; total volume: 90 liter ; spherical vessel; steel-cased ; hinged lid dia 350mm ; agitation: 3 blade dia 490 mm ; drain dia 100 Manual on chute ; control: variable speed motor sew 7.50 hp; 1440 r / min; 220,380 v ; ; without electrical cabinet ; interior dimension tank: 560 mm dia ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
170	<b>1 mixer week</b> SEM, GP 20, mixer week; Type: 20 gp; model; héliglobe; spherical; vertical; stainless steel, ; total volume: 45 liters; with double steel jacket, ; on top cover 1 Swivel bolted; equipped with 5 tubes; 2 handles; 1 flange ø 140 mm ; drain ø 80 mm; by manual side door and chute ; on ferrule: 1 pipe with valve ø 30 mm ; ; agitation: 3 blade tank bottom, command engine hp 7.5 hp; 920 rev / min; 220/380 v, ; pulleys and belt variator; on frame; without electrical control panel ; ; internal dimension of the tank: ø 380 mm, ; approximate exterior dimensions: 1200 x 700 mm; height: 1120 mm ; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00





Lot	Number Description	Starting Bid €
171	<b>1 vertical mixer</b> MORITZ, vertical mixer Moritz No. 850181 stainless steel ; conical tanks with flat bottom; total volume: 200 liters ; on top: a clipped lid equipped with three nozzles and a handle ; on the bottom of the shell: a drain ø 110 mm with manual valve then ; output on tubing ø 70 mm; Discharge outlet height 510 mm ; unrest: twice two tank bottom blades driven by ; motor cem 12.5 hp - 9.2 kw - 1440 rev / min - 220/380 v ; transmission belt pulley and variator plus reducing ; variable speed manual ; Chassis; without electrical control cabinet; sealing by housing braids ; internal dimensions of the tank: ø 750 and 550 mm - height 550 + 100 = 650 mm ; approximate exterior dimensions: 1400 x 1350 mm - Height 1650 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
172	<b>1 horizontal ribbon blender</b> horizontal ribbon blender equipped with a stainless steel tank and a steel tool ; semicylindrical bottom; total volume: 1300 liters ; on front: on each side; a hinged lid with gas lift and the center; a lid ; bolted equipped with a tubing ø 215 mm and with a hopper lid; opening 580 x 400 mm ; on the left cover: a swinging trapdoor; opening 480 x 430 mm ; on the right cover: a tilting hopper; opening 400 x 400 mm ; on the bottom: drain with a pneumatic flap; opening 150 x 150 mm; output of ; tubing ø 150 mm; Discharge outlet height 450 mm ; tool: Simple discontinuous ribbon ø 730 mm x length 2450 mm driven ; brook crompton engine 25 hp 18.5 kw 1460 rev / min 380 v kennedy plus reducing ; transmission by coupling; mixing speed 36 rev / min ; on chassis; without electrical control panel ; internal dimensions of the tank: 2450 x 755 mm x height 835 mm ; approximate exterior dimensions: 3400 x 1650 mm x height 2000 mm; height 2400 mm raised lid ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
173	<b>1 speed mixer</b> DIOSNA, RK200, speed mixer Diosna type rk 200 No. 203032 stainless steel casing with dual ; vertical cylindrical tank; Total volume: 300 liters ; on top of tank: a hinged lid equipped with a trapdoor; opening 200 x 160 mm ; lateral drain pneumatically operated; opening 140 x 135 mm ; tools: three blades driven by bauer engine 10 hp 7.5 kw 1440 rev / min 220/380 v ; transmission by pulleys and V-belts; mixing speed 386 rev / min ; on chassis; without electrical control panel ; internal dimensions of the tank: ø 900 mm x height 440 + 100 = 540 mm ; approximate exterior dimensions: 2000 x 1100 mm x 1850 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
174	<b>1 sieve sift kind</b> CHAUVIN, SIFT28SK2, chauvinist sieve sift kind sk-28 No. 40501 ; equipped with two screening stages with mesh and stainless base ; on wooden frame 3500 x 1020 mm, 2.8 m <sup>2</sup> area per floor ; on top: a power supply ø 170 mm longer a central tube ; the desous two refusal ø 145 mm and a product outlet 250 x 145 mm ; control: leroy somer motor hp 3 - 2.2 kW - 1420 rev / min - 220/380 v ; transmission by pulleys and v-belts, sifting speed 220 tr / min ; on chassis without electrical control panel ; approximate exterior dimensions: 3600 x 1700 mm - 1850 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
175	<b>1 disperser</b> MOLTENI, molteni disperser; without tank; steel; ; steel shaft ø 60 mm; height 950 mm, ; tool steel deflocculator ø 250 mm ; controlled: engine "enrico bezzi" 25 hp; 1455 rev / min; 220/380 v, ; pulleys and belt variator has hydraulic setting, ; head up and down by cylinder and hydraulic unit; controlled: ; engine "enrico bezzi" 1 hp; 1380 rev / min; 220/380 v, ; provided with a cap ø 980 mm; with a pipe ø 170 mm and a hinged lid, ; on base; without electrical control panel, ; approximate exterior dimensions: 2100 x 1100 mm; height: 1900 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00





Lot	Number Description	Starting Bid €
176	<b>1 disperser</b> VOLLRATH, EWFX 30, disperser Vollrath kind: ewfx 30 without tank and without scraper ; steel shaft ø 40 mm on the top and 32 mm on the bottom; total length 1050 mm ; head up and down mechanically driven auger ; control head by gearmotor Loher hp 1.5 - 1.1 kw - 1410/192 rev / min - 220/380 v ; transmission gears and chain; height agitation: 300 mm ; tools: turbine ø 390 mm stainless steel motor driven Loher hp 40 hp - 30 kilowatts - 1475 rev / min - 220/380 v ; transmission by pulleys and V-belts; mixing speed 460 rev / min ; with two interchangeable shafts and adjustable in height stepped turbine ; disperser equipped with a fixing system for scraper with manual adjustment of the orientation ; chassis; without electrical control panel ; approximate exterior dimensions: 1900 x 1300 mm x 2300 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	150.00
177	<b>1 electric kettle in stainless steel 1600 liters</b> electric kettle in stainless steel, power 18 kilowatts volume 1600 liters ; vertical cylindrical tank domed base, without cover, with jacket ; on the shell: a neck and two resistors vulcanic 9 kilowatts each 220/380 v ; on the bottom: a discharge pipe ø 36 mm valve with ; three legs without electrical control panel ; internal dimensions of the tank: ø 1200 x height 1400 + 200 = 1600 mm ; approximate exterior dimensions: 1700 x 1600 mm x 2700 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
178	<b>1 cylindrical tank-type reactor vertical</b> VERTICAL, cylindrical tank-type reactor, vertical, stainless steel, ; total volume 150 liters, demountable bottom lid bolted on frame ; 1/2 stainless steel shell ; on top of tank: 1 trapdoor dia 105 mm with cover bolts and look dia 85 mm ; 4-neck ; on shell manifolds 3 ; on bottom 2 tubes ; dia 27mm manual central drain ; stirring anchor ; command without motor ; without electrical cabinet ; tank internal dimensions: 495 mm dia, height 740 + 130 = 870 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
179	<b>1 steel mill</b> FORPLEX, FL2, FORPLEX type fl2 steel mill; without feed hopper ; outlet of the product as the mill opening 470 x 175 mm ; tools: rotor ø 290 mm equipped with ten hammers against rotor in the door ; of the mill drive motor Leroy somer 12 hp - 9 kilowatts - 2935 rev / min - 220/380 v ; transmission by pulleys and v-belts; grinding speed: 4000 rev / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 1500 x 850 mm x height 700 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
180	<b>1 steel mill</b> FORPLEX, FL2, FORPLEX type fl2 steel mill; without feed hopper ; outlet of the product as the mill opening 470 x 175 mm ; tools: rotor ø 290 mm equipped with ten hammers against rotor in the door ; of the mill drive motor Leroy somer 12 hp - 9 kilowatts - 2935 rev / min - 220/380 v ; transmission by pulleys and v-belts; grinding speed: 4000 rev / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 1500 x 850 mm x height 700 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
181	<b>1 steel mill</b> FORPLEX, FL2, FORPLEX type fl2 steel mill; without feed hopper ; outlet of the product as the mill opening 470 x 175 mm ; tools: rotor ø 290 mm equipped with ten hammers against rotor in the door ; of the mill drive motor Leroy somer 12 hp - 9 kilowatts - 2935 rev / min - 220/380 v ; transmission by pulleys and v-belts; grinding speed: 4000 rev / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 1500 x 850 mm x height 700 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00



Lot	Number	Description	Starting Bid €
182	1	<b>mill blades</b> mill blades; steel ; rotor ø 380 mm; length: 560 mm; equipped with 3 blades bolted; a grid, ; feed hopper with: opening 370 x 370 mm + tubing ø130 mm ; output in sole; opening 560 x 560 mm, ; with on one side of the mill; 1 trapdoor, ; without motor and chassis ; without electrical control cabinet, ; approximate exterior dimensions: 1300 x 1000 mm; height: 1600 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
183	1	<b>mill-type blades</b> MECCANOPLASTICA, FR 16 40 DP, mill-type blades Meccanoplastica en 16 40 dp steel ; rotor ø 160 mm length x 320 mm; provided with three rows of two bolted knife ; entraîné motor elektromotors 5.5 hp 4 kilowatts 1445 rev / min 220/380 v ; transmission by pulleys and V-belts; grinding speed 500 r / min ; with perforated grille holes ø 6 mm ; feed hopper hinged grinding chamber; opening 160 mm dia ; rejection under mill into a tray and then pipe ø 80 mm ; mobile chassis; without electrical control panel ; approximate exterior dimensions: 900 x 900 x 1400 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
184	1	<b>ball mill attritor</b> WIENER, ATTRITOR 1 S, wiener-type ball mill attritor sn ° 1 CM76 3812 stainless steel ; vertical cylindrical tank and tilt; 5 liters capacity with jacketed steel ; tool tree with five rows of steel fingers ; control the shaft gearmotor hoher 1 hp 0.75 kw 1395/50/250 rev / min 220/380 v ; pulley transmission and timing belt; variable grinding speed of 50 to 250 rev / min ; on a chassis; without electrical control panel ; internal dimensions of the tank: ø 210 mm x height 210 mm ; approximate exterior dimensions: 900 x 700 mm x 1450 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
185	1	<b>vertical ball mill</b> ROUSSELLE, 8, vertical ball mill rousnelle Type 8 No. 10053 stainless steel ; cylindrical vessel with double steel jacket; 8 liters capacity ; on top: a clipped lid equipped with two tubes ; tool: a milling disk and a pasting disc ; motor drive without Rouard plate; monobloc transmission ; Chassis; without electrical control panel ; inside dimensions of the room: ø 170 mm x 340 mm length ; approximate exterior dimensions: 730 x 340 mm x height 1000 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
186	1	<b>vertical ball mill</b> ROUSSELLE, 8 L, vertical ball mill rousnelle type 8l stainless ; equipped cylindrical tank with a jacket steel; total volume of 8 liters ; on the top; a clipped cover with two tubes ; tools: a grinding disc and a mashing disk driven by ; motor cen hp hp 3 - 2.2 kW - 1400 rev / min - 220/380 v ; monobloc transmission; grinding speed 1400 rev / min ; on chassis; without electrical control panel ; internal dimensions of the tank: ø 170 mm - height 340 mm ; approximate exterior dimensions: 700 x 330mm - 1000mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
187	1	<b>schenk filter</b> SCHENK, SR 5 KL, schenk filter; Type: sr 5 kl; stainless steel, ; 10 dia filter discs 805 mm; Surface: 4.70 m2 (confirmed) ; vertical cylindrical tank; Double steel shell, ; bomb ground; cover bolts with 6 tubes; 3 feet ; on ferrule: 1 look with lamp; 2 pipes; 1 look, ; drain dia 250mm ; command cen motor 7.50 hp; hp; 1420 r / min; 220 380 V ; without electrical cabinet ; internal dimensions: 890 mm dia; height 215 + 350 + 215 = 780 mm ; plate: tank volume 350 liters; temperature 164 ° C; pressure 6 / vak ; jacket 35 liters; temperature 164 ° C; pr 6 atu ; **** apparatus under rule authorization n **** 2/1 ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00



Lot	Number Description	Starting Bid €
188	<b>1 tank melangeuse</b> FIB, tank melangeuse fib, cylindrical, vertical, stainless steel, ; total volume 1860 liters, bomb bottom, flat cover bolts, insulated with ; tracing electric, 3 gussets ; on top of tank: 1 trapdoor dia 300 mm with rocking cover bolts, ; 4-neck ; on ferrule: 3 sensors ; on the bottom: 1 tube ; Central drain dia 64mm ; agitation ECCENTRIC Ekato Type: em o60, 3 dia marine blades 300mm ~ ; command: motovariator sew 3 hp, 52 311 rev / min, 220 380 v ; without electrical cabinet ; dimensions inland tank: dia 1200 mm, height 1460 + 250 = 1710 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
189	<b>1 horizontal rotary blender</b> horizontal rotary blender stainless ; cubic kettle equipped with a gaze ø 350 mm; total volume 1000 liters ; on the bottom: a drain valve with ø 105 mm ; drive the tank through cenenesa engine 5.5 hp - 4 kilowatts - 1420 rev / min - 220/380 v ; transmission belt pulleys and plus speed reducer ; chassis; without electrical control panel ; internal dimensions of the tank: 1000 x 1000 mm x 1000 mm height ; approximate exterior dimensions 2750 x 1800 mm x 2800 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
190	<b>1 screen rotex</b> ROTEX, 23, screen rotex type 23 with wooden frames and steel frame ; three screening stages, dimensions: 508 x 2057 mm, surface area per floor: 1.04 m² ; on top: a wooden lid with two tubes ø 105 and 195 mm ; on the underside three refusal ø 95 mm and a refusal 130mm; sieve with motor 1cv -1400rpm; transmission by pulleys and v-belts more reducing, the number of strokes per minute: 256 ; without electrical control panel ; approximate exterior dimensions: 3000 x 900 mm x height 750 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
191	<b>1 pump lobes</b> FRISTAM, FLF100S, Fristam pump lobes type flf100s stainless steel ; inlet and outlet manifolds ø 60 mm ; rotor has two lobes stainless driven ; north gearmotor hp 7.5 - 5.5 kw - 1450/258 rev / min - 380/660 v ; transmission by coupling; pumping speed 258 rev / min; Max speed 15 m³ / h ; on stainless steel base; without electrical control panel ; approximate exterior dimensions: 110 x 350 mm - height 430 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
192	<b>1 Liquid ring vacuum pump</b> HIBON, ALPHA04, Liquid ring vacuum pump hibon types: alpha 04 No. 4,700,209 steel ; suction and discharge diameter 70 mm; flange ø 185 mm ; pump drive motor Leroy Somer 10 cv - 7.5 kw - 1450 rev / min - 220/380 v ; transmission by coupling; max speed 120 m³ / h ; without electrical control panel ; approximate exterior dimensions: 1200 x 500 mm x height 1,050 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
193	<b>1 tank</b> MERLINC & FRERES, tank MERLINC & brothers, cylindrical, vertical, 304l stainless steel, insulated ; 1500 liters, background bomb, upper dome soda, 4 gussets ; on top of bowl 1 oval trapdoor 450 x 410 mm with protective grille and rocker cover bolt, ; 4 necked 1 look dia 135 with lamp ; on ferrule: 2 taps ; central drain ; dimensions inland tank: dia 950 mm, height 2210 mm ; approximate External dimensions: 1300 mm dia, height 2450mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
194	<b>1 cumberland mill knives</b> CUMBERLAND, LEESONA 284, cumberland mill knives; Leesona; Type: 284 ; rotor length 300 mm diameter 300 mm rotor blades Evide 3 ; + 1/2 cylindrical grid ; feed hopper by tilting SOUNDPROOF; opening 310 x 265 mm ; drain tray by tray ; control: motor 7.50 hp; 1440 r / min; 380 v + trapezoidal belts and pulleys ; without electric cabinet; mobile ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00



Lot	Number Description	Starting Bid €
195	<b>1 cutting mill</b> CMB, VLS, cutting mill cmb type vls No. 4579 steel ; rotor blades bolted with four ø 140 mm length 150 mm; with grid ; power by tipping hopper opening 800 x 800 mm feed screw driven by ; gearmotor sew 1 hp 0.75 kw 1380 rev / min 220/380 v ; rejection under crusher opening 220 x 160 mm ; control of the mill: vem motor 5.5 hp 4 kw 1430 rev / min 220/380 v ; transmission by pulleys and v-belts; grinding speed 700 rev / min ; on mobile chassis; with electrical control panel ; approximate exterior dimensions: 1500 x 1000 mm height 1200 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
196	<b>1 cutting mill</b> CMB, MS22, cmb mill MS22 like steel blades ; rotor ø 180 mm x length 200 mm; provided with three rows of blades bolted ; motor driven siemens 5.5 hp 4 kilowatts 1440 rev / min 220/380 v ; transmission by pulleys and V-belts; grinding speed 700 rev / min ; with perforated grille holes ø 6 mm ; feed hopper hinged grinding chamber; opening ø 195 mm ; rejection under grinder then return fan; ø 80 mm output ; control fan: 0.12 kw motor 0.16 hp 2750 rev / min 220/380 v; Flow 300 m³ / hour ; on the chassis; without electrical control panel ; approximate exterior dimensions: 1000 x 800 x 1650mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
197	<b>1 cutting mill</b> CMB, MS22, cmb mill MS22 like steel blades ; rotor ø 180 mm x length 200 mm; provided with three rows of blades bolted ; motor driven siemens 5.5 hp 4 kilowatts 1440 rev / min 220/380 v ; transmission by pulleys and V-belts; grinding speed 700 rev / min ; with perforated grille holes ø 6 mm ; feed hopper hinged grinding chamber; opening ø 195 mm ; rejection under grinder then return fan; ø 80 mm output ; control fan: 0.12 kw motor 0.16 hp 2750 rev / min 220/380 v; Flow 300 m³ / hour ; on the chassis; without electrical control panel ; approximate exterior dimensions: 1000 x 800 x 1650mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
198	<b>1 cutting mill</b> CMB, MS22, cutting mill cmb type MS22 No. 4105 steel ; rotor ø 180 mm x length 200 mm; provided with three rows of blades bolted ; motor driven siemens 5.5 hp 4 kilowatts 1440 rev / min 220/380 v ; transmission by pulleys and V-belts; grinding speed 700 rev / min ; with perforated grille holes ø 6 mm ; feed hopper hinged grinding chamber; opening ø 195 mm ; rejection under mill into a tray and then pipe ø 90 mm ; mobile chassis; without electrical control panel ; approximate exterior dimensions: 1000 x 800 x 1650mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
199	<b>1 ball mill</b> MOLTENI, MS 10, ball mill molteni type ms 10 No. 8-17 steel ; vertical cylindrical tank with double steel jacket volume 10 liters ; tool shaft with discs driven by: hansen hp motor 7.5 hp 5.5 kw 2900 rev / min 380/660 v ; transmission by pulleys and V-belts; grinding speed 1650 rev / min ; on chassis; without electrical control panel ; internal dimensions of the tank: ø 145 mm height 500 mm; approximate exterior dimensions: 1000 x 800 mm height 1550 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
200	<b>1 ball mill</b> MOLTENI, MS 10, ball mill type molteni 10 ms No. 18-5 steel ; vertical cylindrical tank mobile with double steel jacket; volume 10 liters ; tool shaft with discs driven hp motor plate without ; the transmission being by pulleys and V-belts ; on chassis ; with electrical control panel ; internal dimensions of the tank: ø 150 mm height 560 mm ; approximate exterior dimensions: 1100 x 850 mm height 1550 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00



Lot	Number	Description	Starting Bid €
201	1	<b>colloid mill</b> colloid mill; stainless steel; ; feed hopper tapered; opening dia. 300 mm ; output socket on 110/115 x 100 mm ; control: bbc engine; 2 speeds and 2.70 hp 3.70 hp; 2845 r / min and 1430 r / min; 380 v + pulleys and flat belt ; without electrical cabinet ; rack ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
202	1	<b>filter</b> HERFILCO, SCF 900-12 C, herfilco filter; Type: 900-12 scf c horizontal; stainless steel, ; 7 trays 750 mm dia with 2 stainless steel canvases; Surface: 5.50 m2; 4 feet ; cylindrical vessel; background bomb; pivoting cover bolts, ; dia 165 mm butterfly drain, ; spraying ramp ; control: speed reducer ls r 1 / 85.2 + transmission roller chain ; without electrical cabinet ; manometer max 8 b; ; tank dimensions: 895 mm dia; length 1000 + 170 = 1170 mm ; plate: Operating pressure max 3.90 b ; pressure hyd ordeale 5.85 b ; maximum temperature 80 ° C service ; volume inside 840 liters ; **** **** with customer drawings ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
203	1	<b>vertical mixing tank</b> TOMAS MORSON, vertical mixing tank Tomas Morson stainless steel with double steel jacket on the shell and on the bottom ; rounded bottom, cover welded enchassé, total volume 600 liters ; to the top of tank: three neck, two looks ø 150 mm and two hatches visit bolted ø 200 mm ; on the bottom: a drain pipe ø 50 mm, without valve ; agitation part driven by leroy somer motor hp 10 hp - 7.5 kw - 1430 rev / min 220/380 v more reducing ; piece transmission, mixing speed 40 rev / min ; without electrical control panel ; internal dimensions of the tank: ø 1000 mm - height 125 700 + 125 = 950 mm ; approximate exterior dimensions: 1400 x 1400 mm - 2500 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
204	1	<b>vacuum mixer</b> RAYNERI, DYNTURBO, vacuum mixer rayneri type dyn turbo stainless steel tank equipped with a double stainless steel casing ; head up and down manually equipped with a cover with four pipes and a look ø 62 mm ; agitation paster butterfly 180mm Shaft ø 18 mm ; drive by motovariator ATAV hp 1 hp 1430 rev / min 220/380 v ; variable mixing speed manually 50-290 rev / min ; on chassis; without electrical control panel ; inside dimensions of the mixer: 180mm x height 125 mm; total volume 3 liters ; approximate exterior dimensions: 600 x 600 mm x height: 900 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
205	1	<b>mixer</b> SPANGENBERG, FLUIDOMAT CS 150, spangeerg mixer; fluidomat kind: cs 150; stainless steel, ; volume: 150 liters; cylindrical vessel; vertical; steel-cased ; hydraulic lift lid with agitation, ; lid with 140 mm dia and feed pipe, ; agitations: 4 blades + 2 bottom blades tank and wiper arms ; without valve. ; Control: Siemens motor 2-speed 42 hp and 51 hp; 1485 r / min and 2970 r / min; 220 v + pulleys ; and belts trapezoidal ; engine 5 hp; 1450 r / min; 220,380 v + pulleys and toothed belt ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
206	1	<b>planetary mixer</b> MOLTENI, I 130, planetary mixer "molteni"; Type: 130; No. 8-7; steel; ; total volume: 130 liters ; cylindrical tank; vertical; flat bottom; mobile; ; conical lid with feed hopper; opening 350 x 160 mm ; ; protection grid and put lid ; head up and down; on hydraulic bailer and group ; agitations: 1 blade provided 4 pallets + 2 wiper arms ; control: 2-speed motor; 7.5 / 6 hp; 1440/950 rev / min; 220 v, ; transmission pulleys and V-belts; ; on canvas; without electrical control panel, ; internal dimensions of the tanks: ø 540 mm; height 540 mm, ; approximate exterior dimensions: 1600 x 700 mm; height: 1300 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00





Lot	Number Description	Starting Bid €
207	<b>1 lock</b> ACETT, DRA9805, lock ACETT kind dra012009805 steel ; inlet and outlet 400 x 300 mm flange 600 x 500 mm, height 520 mm ; rotor ø 350 mm - 440 mm length, equipped with ten cavities ; of the rotor drive gear motor Leroy Somer 1.5 hp hP - 1.1 kW - 1425 / 23.79 rev / min - 220/380 v ; monobloc transmission speed of lock: 23.79 r / min ; without electrical control panel ; approximate exterior dimensions: 1200 x 550 mm - height 520 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
208	<b>1 screen</b> SIFT7, screen like "chauvinist" type: sift 7-wood ; equipped two-story mesh sieve with 500 and 200 microns ; on wooden frame 2000 x 500 mm with floor area 0.7 m <sup>2</sup> ; on top: a cover with a manifold supply ø 95 mm ; on desous three product outlets ø 85 mm ; drive sieve motor brow Boveri 1 hp 0.75 kw 1380 rev / min 220/380 v ; transmission by pulleys and v-belts ; on chassis without electrical control panel ; dimensions approximate external: 2100 x 1100 mm x 1400 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	105.00
209	<b>1 vacuum pump</b> BARTHEL, VP450,300,G,30, vacuum pump barthel liquid ring types: vp450.300.g.30 No. 971603 steel ; supply and outlet manifolds ø 50 mm; flange ø 165 mm ; pump drive motor cen hp 10 hp - 7.5 kw - 1430 rev / min - 220/380 v ; monobloc transmission; pumping speed 1430 rev / min ; on base; without electrical control panel ; approximate exterior dimensions: 1550 x 600 mm x height 620 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
210	<b>1 hydraulic group</b> BRUENINGHAUS, hydraulic Brueninghaus group GUEDU pressure 280 bar mixer ; equipped with a motor driven pump Brueninghaus abbot 30 hp - 22 kilowatts - 1470 rev / min - 380/660 v ; capacity of the oil tank 200 liters, with electrical control panel ; dimensions approximate external: 1200 x 1000 mm x 1050 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
211	<b>1 electric kettle in stainless steel</b> electric kettle in stainless steel with double jacket on the bottom ; cylindrical tank, conical bottom lid bolted, total volume 35 liters ; on top: five tubes on the shell: a pipe, a look ø 100 mm and ; a bolted inspection hatch, fitted two eyes ø 100 mm ; on the bottom: two electric heaters vulcanic 2 and 4 kilowatts - 220/380 v plus ; a grundfos circulation pump ; on mobile chassis, electrical control panel ; internal dimensions of the tank: ø 300 mm x height 450 + 130 = 580 mm ; approximate exterior dimensions: 650 x 550 mm x height 1750mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
212	<b>1 tank-type reactor</b> SVCM, VERTICAL, tank-type reactor SVCM, cylindrical, vertical, stainless steel: NSMC, ; total volume 150 liters, background bomb demontable upper dome, on 4 feet, ; stainless steel double envelope ; on top of tank: 1 tube, 1 look dia 60 mm, 1 lamp ; on sleeve 4 pipes ; on bottom 2 tubing ; command: 0.33 hP motor, 1390 rev / min, 220 380 v, + speed reducer sadi + pulleys and trapezoidal belts ; without electrical cabinet ; dimensions inland tank dia 590 mm, height 130 + 510 + 130 = 770 mm ; with filter plate, ; shaking up and down, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00





Lot	Number Description	Starting Bid €
213	<b>1 centrifugal fan</b> SOLYVENT VENTEC, LM75M3, centrifugal fan Solyvent ventec type lm75m3 3 79 445 steel ; equipped with a rotor ø 800 mm with 12 blades ; suction flange ø 380 mm ø 610 mm; refoulement 480 x 360 mm flange 650 x 465 mm ; rotor drive motor cem 50 hp - 37 kilowatts - 1470 rev / min - 380/660 v ; transmission by pulleys and V-belts; Fan speed 1800 rev / min ; flow :: 23400 m <sup>3</sup> / h for a yield of 74% ; on steel frame; without electrical control panel ; approximate exterior dimensions: 2550 x 1300 mm - Height 1650 mm; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
214	<b>1 elevator conveyor</b> BATELECT, type ROTO, elevator conveyor batelect kind roto No. 04841 stainless steel ; with plastic tape, length 3500 mm width 520 mm ; feed hopper opening 600 x 530 mm ; height 2200 mm drain ; command: gearmotor sew 0.34 hp 1300 / 7.3 r / min 220/380 v ; with electrical control panel and frequency converter, mobile stainless steel frame ; approximate exterior dimensions: 3000 x 1000 mm height 2300 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
215	<b>1 Archimedes screw</b> Archimedes screw in tube diameter 250 mm x 2780 mm total length of stainless steel ; equipped with a screw length of 240 x 2200 mm with 230 mm not ; on top: a hopper located on the middle of the screw opening 600 x 600 mm ; from each end with a look of bars; opening 200 x 150 mm ; on the bottom: at each end; a drain valve ø 200 mm with ; screw drive by gear motor ebernard 4 hp - 3 kilowatts - 1400-1442 TRmin - 500 v ; transmission gears and chain; screw speed 25 rev / min ; on a chassis; without electrical control panel ; approximate exterior dimensions: 1500 x 850 mm x 3300 mm length ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
216	<b>1 mill</b> FORPLEX, F2, FORPLEX mill type f2; a hammer; steel ; rotor dia 300 mm; with against-rotor on door and gate ; feed hopper pyramidal opening 1100 x 600 mm ; Drain in sole; 470 x 140 mm ; control: without engine ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
217	<b>1 laboratory mill</b> PALLMANN, REFL 18, laboratory mill PALLMANN; Type: refl 18, ; cast iron rotor dia 170 mm 6 tools ; feed hopper 75 x 45 mm ; output by tapered hopper dia 150 mm ; control: 2 speed motor bauknecht 3 hp and 4 hp; 1410 r / min and 2820 r / min; 380 v + pulleys and toothed belts ; without electrical cabinet ; on movable frame ; + spare parts. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
218	<b>1 mixing tank</b> melangeuse tank, cylindrical, vertical, stainless steel, ; total volume: 3,000 liters, conical bottom, open pockets on ; dia central drain 60 mm ; of ferrule: 1 probe ; agitation: 3 blades 500 mm dia mixel ; command: ls motoreducteur 0.75 hp 1500/181 r / min 220 380 v ; without electrical cabinet ; dimensions inland tank: dia 1470 mm, height 1740 + 150 = 1890 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
219	<b>1 mixing tank</b> cylindrical, vertical melangeuse tank, stainless steel, ; total volume 2400 liters, conical bottom cover by 2 half moons, about 3 feet ; on top of tank: 1 ramp spray ; agitation ECCENTRIC dia 140mm ~ ; command engine vem 2 cv, 1400 r / min 220 380 v ; without electrical closet ; inside coiled tank bottom ; dia central drain 105 mm ; on the bottom: 2 tubes ; 1 stitching ; tank internal dimensions: dia 1410 mm, height 1500 + 110 = 1610 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00



Lot	Number Description	Starting Bid €
220	<b>1 horizontal mixer</b> stainless steel horizontal mixer equipped with a cylindrical vessel; Total volume: 300 liters ; on the front: two overhead access doors; opening 1030 x 200 mm ; on a side of a drain 400 x 190 mm valve without ; tools shaft with rows of adjustable blades tilt ; transmission by pulleys and V-belts; mixing speed 280 rev / min ; on chassis; without electrical control panel ; inside dimensions of the mixer: ø 400 mm - 2550 mm length ; approximate exterior dimensions: 2900 x 1100 mm - height 800 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	90.00
221	<b>1 peristaltic pump</b> RAGAZZINI, MS2, peristaltic pump Ragazzini type ms2 aluminum ; inlet and outlet manifolds ø 55 mm; flange ø 150 mm ; Order: geared bonfiglioli 3 hp - 2.2 kw - 1410 to 1430 rev / min - 220/380 v ; mean flow 4.6 m³ / h at 8 bar ; on the frame; without electrical control panel ; approximate exterior dimensions: 850 x 800 mm x height 800 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
222	<b>1 peristaltic pump</b> RAGAZZINI, MS2, peristaltic pump Ragazzini type ms2 aluminum ; inlet and outlet manifolds ø 55 mm; flange ø 150 mm ; Order: geared bonfiglioli 3 hp - 2.2 kw - 1410 to 1430 rev / min - 220/380 v ; mean flow 4.6 m³ / h at 8 bar ; on the frame; without electrical control panel ; approximate exterior dimensions: 850 x 800 mm x height 800 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
223	<b>1 Liquid ring vacuum pump</b> SIHI, LPHA 5620, Liquid ring vacuum pump SIHI Type: lpha 5620; No. 2364721 steel ; suction and discharge diameter 48 mm flange ø 165 mm ; flow 390 m³ / h at 80 mbar ; Control: 20 hp motor cem 15 kilowatts 1440 rev / min; 220/380 v ; Stand; without electrical control panel ; approximate exterior dimensions: 1700 mm x 650 mm x height 750 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
224	<b>1 vertical storage tank</b> DE DIETRICH, vertical storage tank of Dietrich kind ms105 No. 28005 in 3009 enamel, total volume 516 liters ; rounded bottom, top dome nut, three pockets ; on top of tank: eight nozzles on the bottom: a central drain ø 50 mm with valve ; dimensions interior of the tank: ø 800 mm - height: 100 + 950 + 100 = 1150 mm ; approximate exterior dimensions: 960 x 960 mm - 1600 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
225	<b>1 strapping semi-automatic</b> SIGNODE, SPIRIT E 2000 V, Signode strapping semi-automatic type: spirit e v 2000, No. 100652, 1997, Mobile 400 v ; space inside 850 x 835 mm ; with wire feeder rollers ; footswitch ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
226	<b>1 shrink tunnel</b> SAVOYE, shrink tunnel SAVOYE ; tunnel opening 500 x 400 mm, length 1200 mm, ; with conveyor belt has steel mesh, length 2680 mm, width 495 mm, ; puissance Installed: 18 kilowatts, ventilated motor drouard 0.50 hp, ; probe temperature ; temperature adjustable : 0 ° ca 300 ° c ; control conveyor: motovariator 0.50 hp, 220 380 v, from 1400 to 1410 r / min 50 r / min, ; transmission gears and chain roller ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
227	<b>1 shrink tunnel</b> OUEST CONDITIONNEMENT, M 450, shrink tunnel OUEST CONDITIONNEMENT type: m 450, mobile, ; opening 510 x 190 mm, length 960 mm ; carpet links, length 2100 mm with bar spacers ; heating power of 10 kilowatts ; variable belt speed ; of the heating distribution fan motor 0.50 cv, 2765 rev / min, 220 380 v ; cooling fan ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00



Lot	Number Description	Starting Bid €
228	<b>1 steel vacuum unit bags</b> steel vacuum unit bags; consisting of 6 filter elements 1400 x 450 mm; Surface 7.56 m <sup>2</sup> ; with motor-driven fan Walber 2 hp 1.5 kw 2855 rev / min 220/380 v ; pneumatic unclogging housing with France dusting industrial ; air outlet on the top; opening 310 x 160 mm ; inner dimensions of the hopper: 880 x 840 mm ; without electrical control panel ; approximate exterior dimensions: 1300 x 1000 mm x 3400 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
229	<b>1 elevator conveyor</b> elevator conveyor with curved exit, mobile stainless steel frame ; with plastic chain, width 500 mm x length 5000 mm, height 1900 mm drain ; drive gearmotor sew cv 0.75 - 0.55 kW - from 1360 to 1336 rev / min - 220/380 v ; monobloc transmission, linear conveyor speed 18 m / min ; without electrical control panel ; approximate exterior dimensions: 4600 mm x 2100 mm x height 2210 ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
230	<b>1 conveyor on stainless steel frame</b> conveyor on stainless steel frame, no feet ; equipped with plastic tape, width 400 mm - 5050 mm length ; strip driving by gearmotor bonfiglioli 2 cv - 1.5 kw - 1390 to 1373 rev / min - 220/380 v ; monobloc transmission speed linear conveyor 27 m / min ; without electrical control panel ; approximate exterior dimensions: 750 x 470 mm - 5200 mm length ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
231	<b>1 conveyor</b> JOSEPH CRUANAS, joseph conveyor Cruanas No. 622 on a steel support ; with plastic flat strip provided with cleats, 6000 mm length x width 730 mm ; control: Leroy Somer geared motor 0.33 cv 1500 / 9.6 r / min 220/380 v ; transmission gears and chain speed linear conveyor: 3.2 m / min ; on chassis without electrical control panel ; approximate exterior dimensions: 6100 x 1100 mm 900 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
232	<b>1 hammermill</b> FAO, TITAN2000, hammermill fao type titan No. 2000 031 284 steel ; feeding hopper with regulator; 130 liters volume ; output of tubing ø 90 mm ; rotor ø 340 mm with 16 hammers with perforated grid ø 2 mm ; mill drive motor Elektrim 7.5 hp 5.5 kw 2930 rev / min 380/660 v ; monobloc transmission; grinding speed 2930 rev / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 1430 x 1100 x height 830 mm ; inner dimensions of the hopper: 800 x 800 x height 350 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
233	<b>1 mill</b> FORPLEX, F1, FORPLEX mill; Type: f 1; steel; a bladed ; rotor dia 250mm ; hopper steel supply tapered dia 290mm with door on Montee ecluse ; control by gear motor snt 0.24 hp; 1500 rev / min; 220,380 v ; ; output dia 350mm ; command: ls engine 10 hp; 2875 r / min; 220 380 v , ; on bati with electric box ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
234	<b>1 mill blades</b> LANCELIN, L 8, lancelin mill blades; Type: l 8; No. 761 517; steel ; rotor diameter 200 mm, length 195 mm, without grid ; power by tilting hopper with hinged lid; opening 200 x 270 mm; ; output manifold on 270 mm dia; ; command: ls motor 7.50 hp; 1450 r / min; 220,380 v + trapezoidal belts and pulleys ; without electrical cabinet ; on movable frame ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
235	<b>1 frame of wringer</b> GUINARD, C 20 HLBS, frame of guinard wringer type: c 20 HLBS, 18/8 mo, 383, ; cylindrical, vertical, ; cover bolts with 2 pipes ; drain valve with butterfly dia 250mm ; command cen motor 3.30 hp, 2820 rev / min, v 220 380 ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00



Lot	Number	Description	Starting Bid €
236	1	<b>filter</b> GAUTHIER, Gauthier filter; No. 5220; stainless steel; ; 20 820 mm dia filter plates; Surface: 7 m2; ; cylindrical tank; vertical; dia 940 mm; height 850 mm; 550 liters ; tilting lid on against-weight; Bolts; ; drain dia 40 to 80 mm ; on stretcher ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
237	1	<b>vertical cylindrical mixing tank</b> vertical cylindrical mixing vessel, stainless, open, ; total volume 600 liters, rounded bottom, embedded, ; on shell: a pipe, a level ; of background: a drain ø 38 mm, ; agitation rayneri board tank, tool typhoon ; command : bbc 1 hp motor, 910 rev / min, 220/380 v, ; without electrical control cabinet, ; internal dimensions of the tank: ø 800 mm, height 1300 mm, ; approximate exterior dimensions 1150 x 900 mm, height 1900 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
238	1	<b>mixer</b> CAULLE, VISARCON, Caulle mixer; Type: visarcon; stainless steel; 1997 ; with tapered screw ; chamber horizontal trough-shaped ; total volume: 280 liters ; on top: tilting door 600 x 400 mm with protective grille ; on the bottom: drain 360 x 360 mm with bailer guillotine door ; control: without motor ; without cabinet electric ; tank internal dimensions: 610 x 530 mm; length 1400 mm ; with anti-deriveur ; prices without control group ; **** with customer map **** ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
239	1	<b>rotary valve</b> KONGSKILDE, rotary valve kongskilde steel ; inlet opening 320 x 220 mm pipe ø 245 mm ; output filtered grid; opening 580 x 290 mm pipe ø 300 mm ; on the bottom: an output of heavy opening 750 x 500 mm ; rotor ø 600 mm length x 740 mm; equipped with cells with plastic scrapers bolted ; rotor drive motor vem 2 cv - 1.5 kw - 1390 rev / min - 220/380 v plus ; gear Tramec type tf112b report 1/80 monobloc transmission; speed of 17 rev / min ; without electrical control panel ; approximate exterior dimensions 1560 x 1050 mm x height 880 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	75.00
240	1	<b>screen</b> ROTEX, 23, screen rotex type 23 with wooden frames and steel frame ; three screening stages, dimensions: 508 x 2057 mm, surface area per floor: 1.04 m² ; on top: a wooden lid with two tubes ø 105 and 195 mm ; on the underside three refusal ø 95 mm and a refusal 130mm; transmission by pulleys and v-belts more reducing, the number of strokes per minute: 256 ; without electrical control panel ; approximate exterior dimensions: 3000 x 900 mm x height 750 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	120.00
241	1	<b>motor</b> ABB, M2QA225M2A, new abbot kind legged m2qa225m2a engine ; power 60 hp - 45 kilowatts - 2970 rev / min - 380/660 v ; shaft ø 55 mm x 110 mm length, shaft height 225 mm ; approximate exterior dimensions: 820 x 430 mm - height 570 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
242	1	<b>multistage pump</b> SIHI, CEHA3101, SIHI multistage pump type: CEHA 3101 stainless steel ; suction and discharge flange ø 30 mm ø 140 mm ; motor drive cen hp hp 2 - 1.5 kw - 1380 rev / min - 220/380 v ; Stand; without electrical control panel ; approximate exterior dimensions: 750 x 330 mm - height 340 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
243	1	<b>multistage pump</b> SIHI, CEHA3101, SIHI multistage pump type: CEHA 3101 stainless steel ; suction and discharge flange ø 30 mm ø 140 mm ; motor drive cen hp hp 2 - 1.5 kw - 1380 rev / min - 220/380 v ; Stand; without electrical control panel ; approximate exterior dimensions: 750 x 330 mm - height 340 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00





Lot	Number	Description	Starting Bid €
244	1	<b>multistage pump</b> SIHI, CEHA3101, SIHI multistage pump type: CEHA 3101 stainless steel ; suction and discharge flange ø 30 mm ø 140 mm ; motor drive cen hp hp 2 - 1.5 kw - 1380 rev / min - 220/380 v ; Stand; without electrical control panel ; approximate exterior dimensions: 750 x 330 mm - height 340 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
245	1	<b>multistage pump</b> SIHI, CEHA3101, SIHI multistage pump type: CEHA 3101 stainless steel ; suction and discharge flange ø 30 mm ø 140 mm ; motor drive cen hp hp 2 - 1.5 kw - 1380 rev / min - 220/380 v ; Stand; without electrical control panel ; approximate exterior dimensions: 750 x 330 mm - height 340 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
246	1	<b>pump</b> PCM, LB 6 HR 2 VA, cfm pump sparrow-type: 6 lb 6 hr 2 will; No. 20711; stainless steel; variable rate ; feed hopper and force-feeding screw; opening 600 x 480 mm; refoulement: dn 38, ; command motovariator "sew" ip 55; 2 cv; 1400 rev / min; 220/380 v, ; variable speed pump 21-123 rev / min; ; mobile stainless steel frame; with electrical control box, ; approximate exterior dimensions: 2350 x 500 mm; height: 1200 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
247	1	<b>pump</b> PCM, MR40H6, cfm pump type: mr 40 h6 No. 253479 stainless steel ; suction and discharge diameter 100 mm ; pump drive gear motor by North 5.5 hp four kilowatts 1445/248 rev / min 220/380 v ; pumping speed 248 rev / min; flow 10 m <sup>3</sup> / h; 3 bar pressure ; on the chassis; without electrical control panel ; approximate exterior dimensions: 2200 x 450 mm x height 480 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
248	1	<b>pump</b> INOXPA, K165SF, INOXPA pump type: K165 sf stainless steel ; suction and discharge diameter 60 mm ; pump drive by motovariator vem 5.5 hp four kilowatts 1440 220/380 v ; variable pump speed; Max flow 5 m <sup>3</sup> / h ; on mobile chassis; without electrical control panel ; approximate exterior dimensions: 1650 x 500 mm x height 530 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
249	1	<b>Liquid ring vacuum pump</b> VAPYDRO, A, Liquid ring vacuum pump vapydro kind: a; steel ; suction and discharge ø 50 mm; ; control: engine 15 hp; 1445 rev / min; 380/660 v, ; on stretcher; without electrical control panel, ; approximate exterior dimensions: 1300 x 450 mm; height: 600 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
250	1	<b>liquid ring vacuum pump</b> BARTHEL, NP620/H9, liquid ring vacuum pump barthel Type: np620 / h9 No. 992016 steel ; suction and discharge diameter 80 mm flange ø 195 mm ; without frame and without engine; medium flow 550 m <sup>3</sup> / h ; approximate exterior dimensions: 1100 x 500 mm x height 700 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
251	1	<b>container parallelepipedic vertical</b> CMS, container cms, parallelepipedic, vertical, aluminum ; 2300-liter flat bottom, about 4 feet, palletised and stackable, ; the top 1 trapdoor dia 230 mm with cover ; 1 stitching ; emptying by tilting lateral hatch, opening 860 x 375 mm ; internal dimensions container: length 1220 mm, 1070 mm width, height 1830mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00





Lot	Number Description	Starting Bid €
252	<b>1 liquid container parallelepipedic</b> STOCKLIN, liquid container Stocklin, parallelepipedic, vertical, stainless steel, ; 1500 liters, flat bottom, on palletizable steel frame ; on top: 1 trapdoor dia 420 mm with hinged lid ; drain without ; dimensions inland container: length 1200mm, width 1000mm, ; 1250mm height ; approximate External dimensions: 1250 x1050 mm, height: 2000 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
253	<b>1 stainless steel tanks</b> stainless steel tanks, cylindrical, vertical, insulated, with internal coil ~ 0.28 m <sup>2</sup> , ; Volume: 600 liters, rounded bottom, cover welded on 4 feet, ; on top of tank: visit 1trappe ø 390 mm, 5-necked ; on ferrule: 1 tubing, 1 flange with stainless steel coil, level 1, 1 probe, ; central drain ø 42 mm, ; internal dimensions of the tank: ø 900 mm, height 1150 mm, ; approximate exterior dimensions: 1200 x 1300 mm, height 2300 mm.; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
254	<b>1 electric kettle</b> electric kettle in stainless steel, with double steel jacket on sleeve and on the bottom ; cylindrical tank, conical bottom, without lid, total volume 150 liters ; on the shell: a level and a probe ; on the bottom: three electric heaters vulcanic 3 x 1.5 kw - 220/380 v ; without drain valve plant ; on three feet, with electrical control panel ; internal dimensions of the tank: ø 495 mm x height 670 + 160 = 830 mm ; approximate exterior dimensions: 700 x 650 mm x 1600 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
255	<b>1 shrink tunnel</b> LARA STRIC, MS 2000, shrink tunnel lara stric type: ms 2000, No 31252, ; tunnel opening: 400 x 200, length 760 mm, ; on conveyer mesh fabric, 360 mm width, length 1100 mm, ; controlled by engine "galysol" type: sg 80, a direct current, ; transmission gears and chain, ; with output 1 cooling fan, ; controlled by engine "leroy somer" cv 1, 3000 rev / min, 220/380 v, ; mobile chassis ; with electric control cabinet, 220/380 v supply voltage, ; the rate of change and the temperature, ; approximate External dimentions: 1100 x 820 mm, height 1350 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
256	<b>1 tank-type cylindrical reactor</b> VERTICAL, tank-type cylindrical reactor, vertical stainless steel, ; total volume 8 liters bomb bottom demountable upper dome, on frame ; stainless steel double envelope ; on top of tank 4 taps ; 1 look dia 50 mm ; on ferrule 1 manifold ; manual central drain dia 21mm ; anchor agitation ; command cen motor 0.50 hp, hp, 1320 rev / min, 220 380 v + speed reducer 150 r / min + pulleys and belt trapezoidal ; dimensions inland tank: dia 210 mm, height 190 + 90 = 280 mm ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
257	<b>1 centrifugal fan polypropylene</b> SIFAT, CHVN800, centrifugal fan sifat Type: CHVN 800 No. 18631 polypropylene ; rotor ø 1360 mm with 12 blades ; aspiration ø 780 mm; Discharge 1070 x 480 mm ; flow 35000 m <sup>3</sup> / h to 2500 (pa) ; rotor motor drive siemens 60 hp - 45 kilowatts - 1445 rev / min - 380/660 v ; transmission by pulleys and V-belts; rotation speed 900 r / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 2200 x 2050 mm x 2700 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
258	<b>1 booster</b> GEBR,BECKER,WUPPERTA, SV,3,650/2, booster gebr.becker wuppertal type sv.3.650 / 2 ; equipped with 2 holes ø 125 mm; flow: 630 m <sup>3</sup> / h at a pressure of 500 m / b ; drive the blower motor GBW 25 hp - 18.5 kW - 2910 rev / min - 380/660 v ; Chassis; without electrical control panel ; approximate exterior dimensions: 850 x 800 mm - 1500 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00



Lot	Number	Description	Starting Bid €
259	1	<b>booster</b> GEBR, BECKER, WUPPERTA, SV, 3,650/2, booster gebr. becker wuppertal type sv.3.650 / 2 ; equipped with 2 holes ø 125 mm ; flow: 630 m <sup>3</sup> / h at a pressure of 500 m / b ; drive the blower motor GBW 25 hp - 18.5 kW - 2910 rev / min - 380/660 v ; Chassis; without electrical control panel ; approximate exterior dimensions: 850 x 800 mm - 1500 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
260	1	<b>elevator conveyor mobile stainless steel frame</b> elevator conveyor mobile stainless steel frame, height maxi drain under 1275 mm ; with plastic chain bandwidth of 600 mm x 1600 mm length equipped with cleats, height 50 mm ; Order: geared vem 0.33 hp 0.25 kw 700 rev / min 220/380 v ; transmission gears and chain ; feeding hopper opening 630 x 600 mm, without electrical control panel ; approximate exterior dimensions: 2300 mm x 900 mm x height 1730 ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
261	1	<b>elevator conveyor mobile stainless steel frame</b> elevator conveyor mobile stainless steel frame ; with plastic tape, width 220 mm x length 2850 mm ; fitted cleats every 60 mm x 5 mm high ; power tubes and output ø 55 mm, height 2050 mm drain ; motor drive pulley drum 0.16 hp 0.12 kw 20m / min 220/380 v ; without electrical control panel ; approximate exterior dimensions: 2400 x 600 mm x height 2200 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
262	1	<b>Archimedes' screw</b> CORNELOUP, VIS Ø 300, Archimedes screw in Corneloup trough-type screw ø 300 No. 83/2018 / L stainless steel ; width of the trough 310 mm - 2150 mm length with screw ø 300 mm - 1500 mm length and a pitch of 280 mm ; over the top: lids bolted with a ø 315 mm pipe flange ø 450 mm and two overhead access doors opening 200 x 150 mm ; on the bottom at each end; tubing ø 315 mm ø 450 mm flange ; screw drive by gear motor sew 3 hp - 2.2 kw - 1400 to 1460 rev / min - 220/380 v ; frameless and without electrical control panel ; approximate exterior dimensions: 2800 x 950 mm - height 750 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
263	1	<b>Archimedes' screw</b> SPM, Archimedes' screw; spm-tube stainless steel ; screws ø 180 mm; no: 90 mm; 2000 mm length ; ø 190 mm length 2600 mm; sealing by gaskets ; on top: a manifold at each end ø 190 mm; a central hopper ø 800 mm ; on the bottom: at each end two tubes ø 190 mm ; Order: gearmotor sew 3 cv 1400-1493 rev / min 220/380 v ; transmission sprocket and chain, screw speed: 50 rpm / min ~ ; without electrical control panel ; approximate exterior dimensions: 900 x 900 mm length 3050 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
264	1	<b>Archimedes' screw</b> Archimedes screw under tube stainless steel ; tube ø 260 mm x length 2100 mm; screw ø 250 mm x length 1900 mm with 240 mm not ; on top: a trapdoor and a pipe ø 260 mm, ; the following: an outlet with opening 250 x 250 mm ; without control; by sealing braids ; approximate exterior dimensions: 950 x 850 mm x 3400 mm longyear ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
265	1	<b>Archimedes' screw</b> CORNELOUP, Archimedes screw in tube Corneloup ref 51943 170 mm diameter x 1600 mm length stainless steel ; equipped with a screw ø 120 x 1450 mm length with no progressive from 70 to 140 mm ; on top: a feeding tube ø 320 mm an inspection hatch ø 160 mm ; on the bottom: an outlet ø 160 mm and an inspection hatch; opening 200 x 120 mm ; without drive; by sealing braids ; approximate exterior dimensions: 450 x 350 mm x 2500 mm length ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00



Lot	Number Description	Starting Bid €
266	<b>1 vertical baler</b> ORWAK, 5031, vertical baler Orwak Type 5031 No. 54482 steel ; pressure plate on cylinder and hydraulic unit with lifting the container by hydraulic cylinders to evacuate ball ; workout Central by Lafert motor 1 cv - 0.75 kW - 2780 rev / min - 230 v mono ; above a zippered protective cover; without electrical control panel ; inside dimensions of the press: 800 mm depth - 500 mm length - 500 mm width ; approximate exterior dimensions: 1100 x 800 mm - 1950 mm height - height 2700 mm press raised ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
267	<b>1 filter stainless steel</b> GAUTHIER, Gauthier filter stainless steel tanks ; ; dia 830 trays in polypropylene mounted on vertical shaft bolts; Surface: 11 m2 (plate) ; vertical cylindrical tank with hinged lid bolted on against weight- ; drain dia 70 mm ; 2 manometers: 6 b ; tank dia 940; mm height 1100 mm ; plate: surface 11 m2 ; holding capacity 330 dm3 ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
268	<b>1 filter</b> MCP, mcp filter; No 200/76; stainless steel; ; vertical cylindrical tank; dia 360 mm; Double envelope; background bomb ; lid bolted bomb; ; central drain dia 210 mm on pneumatic cylinder, ; 4 plates; dia 360 mm; Surface: 0.30 m2 ; engine cen 3 hp; hp; 1400 r / min; 220,380 v + pulleys and trapezoidal belts; ; without electric cabinet ; with pump and polyester cylindrical tank; vertical; dia 580 mm; height 850 mm ; volume 200 liters ; 3 manometers: 16 b maxi ; together on common frame ; information on litters nameplate: ; filter: ps 5b; ps 7 b ; Volume tank 50 liters; jacketed 5 liters; stamp 7 b, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
269	<b>1 vertical mixing tank 1000 liters</b> vertical mixing tank, stainless steel, total volume 1000 liters, ; domed bottom lid clipped, four pockets, ; on top of tank: 3-necked, ø 350 mm visit a hatch, with bolted cover ; on the bottom: a drain ø 24 mm, without valve, ; centripetal agitation tank edge ø 80 mm, controlled by ; engine "cen" hp, 1 hp, 1320 rev / min, 220/380 v, transmission piece, ; stirring speed: 1420 rev / min without electrical control panel, ; internal dimensions of the tank: ø 900 mm, height: 100 + 1500 = 1600 mm, ; approximate exterior dimensions: 1100 x 1100 mm, height 2300 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	60.00
270	<b>1 conveyor roller</b> TECHNOPARCK, conveyor roller galvanized steel, ; length 6000 mm, width 600 mm, ; ø 50 mm rollers, not 100 mm, ; order: gearmotor "sew" 0.5 hp, 1400-1485 rev / min, 220/380 v, ; pulleys and belts, ; without electrical control panel, ; on stretcher steel, adjustable height, ; approximate exterior dimensions: 6000 x 700 mm, height: 900 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	50.00
271	<b>1 Archimedes screw</b> BOUBIELA MORET, Archimedes screw in tube boubiela plust No. 966099 stainless steel ; tube ø 250 mm x length 1600 mm; screw length 240 mm x 1330 mm with 230 mm not ; on top: a trapdoor; ø 155 mm tubing and a power supply; opening 250 x 250 mm ; on the bottom: an outlet with opening 250 x 250 mm ; without control; by sealing braids ; approximate exterior dimensions: 500 x 450 mm length x 500 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	55.00
273	<b>1 Pump</b> PCM, CFM stainless steel pump ; control: Leroy Somer geared motor 1HP 395T / min 220 / 380v ; ø / O 60 mm; flange ø 165 mm; 4 hole spacing 125 mm ; on frame; without electrical control panel ; approximate exterior dimensions: 1400 x 230 x height: 360 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00



Lot	Number	Description	Starting Bid €
274	1	<b>Pump</b> PCM, MR25H6, cfm pump type mr-25h6 No. 235150 stainless steel ; supply and outlet pipes ø 70 mm ; pump drive by gearmotor sew 2 cv - 1.5 kw - 1410/225 rev / min - 380/660 v ; monobloc transmission; pumping speed 225 r / min ; flow pressure of 3 bar: 4 m³ / h ; on stainless steel frame; without electrical control panel ; approximate exterior dimensions: 500 x 450 mm x 2250 mm length ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
275	1	<b>Pump</b> MOUVEX, AK, MOUVEX pump type: ak steel; with double valve ; intake and discharge ø 50 mm flange ø 145 mm ; control: engine cem hp 3 hp 2.2 klw 1400 rev / min 220/380 v; plus reducing ; pumping speed 460 rev / min; flow 10.75 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 1000 x 410 mm x height 530 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
276	1	<b>Pump</b> MOUVEX, AK2, MOUVEX pump type: ak2 No. 381624 Steel; with single valve ; suction and discharge flange ø 50 mm ø 145 mm ; pump drive motor cem hp hp 1 - 0.75 klw - 910 rev / min - 220/380 v ; plus reductive coupling output ; pumping speed 255 rev / min; flow 5.7 m³ / h ; on mobile chassis; without electrical control panel ; approximate exterior dimensions: 820 x 800 mm - 650 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
277	1	<b>peristaltic pump</b> LSM, peristaltic pump lsm steel ; inlet and outlet manifolds ø 35 mm; flange ø 140 mm ; Order: geared wet cv 0.75 - 0.55 kW - 1395 rev / min - 220/380 v ; Chassis; without electrical control panel ; approximate exterior dimensions: 800 x 650 mm x height 740 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
279	1	<b>centrifugal pump</b> LEFI, NRCL 50/200, centrifugal pump lefi; Type: NRCL 50/200; stainless steel ; command: motor 0.70 hp; 1420 r / min; V 220 380 ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
280	1	<b>container vertical stainless steel</b> NORRIS, container norris, cylindrical, vertical, stainless steel, ; 700 liters, conical bottom, upper dome soda, on 4 feet, palletizable, ; Top: 3 taps ; on background: central drainage, manual ball dia 47 mm ; internal dimensions container: dia 1000 mm, height 190 + 750 + 390 = 1330 mm ; information on litters nameplate ; series 1405 ; tare 141 kgs; ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
281	1	<b>cylindrical vertical tank</b> cylindrical, vertical tank, stainless steel, ; 600-liter bottom half spherical, open ; drain by tilting 2 pins mounted on steel belt, ; internal dimensions tank: dia 1000 mm, height 450 + 500 = 950 mm ; *** reserved home *** ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
282	1	<b>vertical storage tank</b> NIKRON, vertical storage tank nikron 316 stainless steel provided with coil ; volume: 200 liters, rounded bottom, bolted cover, on stretcher, ; operating pressure: 2.5 bars and -1, ; on top thirteen tubes, ; on shell: two tubes , pump-out, ; internal dimensions of the tank: ø 500 mm, height 900 mm, ; approximate exterior dimensions: 1200 x 900 mm, height 1450 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00



Lot	Number Description	Starting Bid €
283	<b>1 tank, cylindrical, vertical</b> DE DIETRICH, Dietrich tank, cylindrical, vertical, in 3009 enamel, ; volume 52 liters, with double insulated shell, rounded bottom, ; glass cover, bolted, with 8 pipes, ; on ferrule: 2 tubes, 2 gussets ; on the bottom: a pipe, a central drain ø 42 mm valve with ; internal dimensions of the tank: ø 385 mm, height: 430 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
284	<b>1 tank-type reactor, vertical, cylindrical, stainless steel</b> VERTICAL, tank-type reactor, vertical, cylindrical, stainless steel ; . 50 liter conical bottom, lockable, on stretcher, a jacket ; on one tank inspection hatch with lighting ; tape agitation blades + ; command: motor 0.75 hp, 1500 to 1593 rev / min , 220/380 v, ; without wardrobe electric ; tank dimensions: dia 350 mm, height 500 + 150 = 650 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
285	<b>1 depoussieur</b> DELTA NEU, POLUCLEAN P 6, depoussieur delta-neu; Type: poluclean p 6; Surface: 6 m2, ; incomplete, without media or filter bags, ; with fan, ; motor control 3 hp; 3000 r / min; V 220 380 ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
286	<b>1 depoussieur</b> DELTA NEU, POLUCLEAN P 6, depoussieur delta-neu; Type: poluclean p 6; Surface: 6 m2, ; incomplete, without media or filter bags, ; with fan, ; motor control 3 hp; 3000 r / min; V 220 380 ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
287	<b>1 Plate exchanger</b> BARRIQUAND, Plate exchanger BARRIQUAND No. 17844 stainless steel ; equipped with two plates of 26 circuits; dimensions 490 x 380 mm; 9 m² area ; on one side: a solid steel cap; on the other side: a steel shell with two tubes ; stainless steel body with six manifolds ; approximate outside dimensions: 1000 x 800 mm x height 950 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
288	<b>1 Industrial manipulator</b> DALMEC, PVF, Industrial manipulator DALMEC kind: pvf; No. 224,019; ; maximum scope: 40 kgs, ; fastening: ceiling mount, ; model: lifting by hook ; command: tire; 0.65 mpa pressure ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
289	<b>1 conveyor belt metalchek</b> METALCHEK, type LOCK 30 CXE, conveyor belt metalchek type: lock 30 CXE, No. 1308, 1997, ; pvc belt, width 150 mm, length 4890 mm, smooth, flat, level, ; command motoreducteur sew 0.75 hp from 1360 to 1395 rev / min, 230.400 v + transmission ; with metal detector, height 50 mm passing ; on 10 adjustable feet in height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
290	<b>1 lot 20 trays filter press</b> lot 20 trays filter press 1000 x 1000 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
291	<b>1 lot 20 trays filter press</b> lot 20 trays filter press 1000 x 1000 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00





Lot	Number Description	Starting Bid €
292	<b>1 horizontal lock steel</b> horizontal lock steel height 420 mm ; opening inlet and outlet ø 200 mm flange ø 320 mm ; rotor ø 250 mm - 220 mm length, with eight cavities ; of the rotor drive gear motor Leroy Somer 0.5 hp - 0.37 kW - 1500 /36.2 rev / min - 220/380 v ; transmission gears and chain lock speed: 17 rev / min ; without electrical control panel ; inside cell dimensions: width 80 and 20 mm - 220 mm length - height 80 mm ; approximate exterior dimensions: 750 x 650 mm - height 420 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
293	<b>1 horizontal lock steel</b> horizontal lock steel height 420 mm ; opening inlet and outlet ø 200 mm flange ø 320 mm ; rotor ø 250 mm - 220 mm length, with eight cavities ; of the rotor drive gear motor Leroy Somer 0.5 hp - 0.37 kW - 1500 /36.2 rev / min - 220/380 v ; transmission gears and chain lock speed: 17 rev / min ; without electrical control panel ; inside cell dimensions: width 80 and 20 mm - 220 mm length - height 80 mm ; approximate exterior dimensions: 750 x 650 mm - height 420 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
294	<b>1 agitator</b> ROBIN, E 1, agitator "robin" type: e 1, stainless steel ; shaft ø 65 mm, length 1250 mm, ; agitation cutting ø 245 mm ,, ; command engine "cen" hp, 10 hp, 920 rev / min, 380 v, ; fixing flange 400 x 400 mm, height 1380 mm flange, ; without electrical control panel, ; approximate exterior dimensions: 450 x 400 mm, height 2200 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
295	<b>1 stir head flange gasket tightness by a lip</b> stir head flange gasket tightness by a lip, steel shaft ø 70 mm, length 140 mm, ; without stirring, ; command cen engine 20 hp, 1450 rev / min, 220/380 v, ; pulleys and belt variator, a hydraulic adjustment + reducer, stirring speed 20 to 123 rev / min, ; flange mounting ø 350 mm, 4 holes ø 18 mm center distance: 300 mm, without electrical control cabinet, ; approximate exterior dimensions: 1000 x 450 mm , flange height 1050 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
296	<b>1 metering</b> GERICKE, Gericke metering steel; mobile ; tube dia 150 mm; length 910 mm ; above 1 145 mm dia pipe ; below: 1 tube dia 45 mm ; order: 1 hp motor cen; hp; 1320 r / min; V 220 380 ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	45.00
297	<b>1 motor</b> LEROY SOMER, LS200LTT, leroy somer legs engine types: 200 lt ls-t ; power 40 hp 30 kilowatts 2940 rev / min 220/380 v ; shaft ø 55 mm x 110 mm length, shaft height 200 mm ; approximate exterior dimensions: 720 x 380 mm x height 460 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
298	<b>1 motor</b> SIEMENS, 200LMB3, nine legs motor siemens kind 200lmb3 ; power 40 hp - 30 kilowatts 2960 rev / min - 380/660 v ; shaft ø 55 mm x 110 mm length, shaft height 200 mm ; approximate exterior dimensions: 700 x 380 mm - height 500 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
299	<b>1 pump with cast iron and stainless steel rotor</b> PCM, RF3M, pcm type rf3m pump with cast iron and stainless steel rotor ; diameter suction and discharge 36 mm ; pump drive motor Leroy Somer 1 hp 0.75 kw 1400 rev / min 220/380 v ; pumping speed 1400 rev / min ; Chassis mobile; without electrical control panel ; approximate exterior dimensions: 1250 x 350 mm x height 550 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number	Description	Starting Bid €
301	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump types: af1; in steel; with single valve, ; inlet and outlet ø 40 mm; flange ø 120 mm ; control: engine "ACEC" hp; 1.5 hp; 1380 rev / min; 220/380 v; and reducer; ; pump speed: 530 rev / min; flow: 5 m³ / h; pressure: 40 mce, ; chassis; without electrical control panel, ; approximate exterior dimensions: 740 x 350 mm; height: 430 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
302	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump types: af1; in steel; with single valve, ; inlet and outlet ø 40 mm; flange ø 120 mm ; control: engine "ACEC" hp; 1.5 hp; 1380 rev / min; 220/380 v; and reducer; ; pump speed: 530 rev / min; flow: 5 m³ / h; pressure: 40 mce, ; chassis; without electrical control panel, ; approximate exterior dimensions: 740 x 350 mm; height: 430 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
303	1	<b>pump</b> MOUVEX, MOUVEX steel pump ; inlet and outlet ø 40 mm flange ø 120 mm ; control: engine cemp hp 2 hp 1.5 kw 1420 rev / min 220/380 v; plus gear ; pump speed: 530 r / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 860 x 350 mm height 430 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
304	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump type: af1 steel ; inlet diameter and outlet flange ø 40 mm 120 mm ; pump drive motor hp hp 1.5 - 1.1 kw - 1400 rev / min - 220/380 v ; coupling output plus reducing ; speed the pump: 530 rev / min; flow 5 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 800 x 250 mm - height 450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
305	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump type: af1 steel ; inlet diameter and outlet flange ø 40 mm 120 mm ; pump drive motor hp hp 1.5 - 1.1 kw - 1400 rev / min - 220/380 v ; coupling output plus reducing ; speed the pump: 530 rev / min; flow 5 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 800 x 250 mm - height 450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
306	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump type: af1 steel ; inlet diameter and outlet flange ø 40 mm 120 mm ; pump drive motor hp hp 1.5 - 1.1 kw - 1400 rev / min - 220/380 v ; coupling output plus reducing ; speed the pump: 530 rev / min; flow 5 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 800 x 250 mm - height 450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
307	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump type: af1 steel ; inlet diameter and outlet flange ø 40 mm 120 mm ; pump drive motor hp hp 1.5 - 1.1 kw - 1400 rev / min - 220/380 v ; coupling output plus reducing ; speed the pump: 530 rev / min; flow 5 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 800 x 250 mm - height 450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
308	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump type: af1 steel ; inlet diameter and outlet flange ø 40 mm 120 mm ; pump drive motor hp hp 1.5 - 1.1 kw - 1400 rev / min - 220/380 v ; coupling output plus reducing ; speed the pump: 530 rev / min; flow 5 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 800 x 250 mm - height 450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number	Description	Starting Bid €
309	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump type: af1 steel ; inlet diameter and outlet flange ø 40 mm 120 mm ; pump drive motor hp 1.5 - 1.1 kw - 1400 rev / min - 220/380 v ; coupling output plus reducing ; speed the pump: 530 rev / min; flow 5 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 800 x 250 mm - height 450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
310	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump type: af1 steel ; inlet diameter and outlet flange ø 40 mm 120 mm ; pump drive motor hp 1.5 - 1.1 kw - 1400 rev / min - 220/380 v ; coupling output plus reducing ; speed the pump: 530 rev / min; flow 5 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 800 x 250 mm - height 450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
311	1	<b>pump</b> MOUVEX, AF1, MOUVEX pump type: af1 steel ; inlet diameter and outlet flange ø 40 mm 120 mm ; pump drive motor hp 1.5 - 1.1 kw - 1400 rev / min - 220/380 v ; coupling output plus reducing ; speed the pump: 530 rev / min; flow 5 m³ / h ; on the chassis; without electrical control panel ; approximate exterior dimensions: 800 x 250 mm - height 450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
312	1	<b>displacement pump piston eccentric</b> MOUVEX, C4A, displacement pump piston eccentric MOUVEX kind: c4a cast ; flow: 1.2 m³ / h to 175 rev / min to a maximum pressure of 9 bar ; diameter suction and discharge 50 mm; flange ø 165 mm ; Order: geared BARTEC-varnost 2 cv - 1.5 kw - 1405/175 rev / min - 220/380 v ; transmission by coupling; pumping speed: 175 r / min ; gear motor equipped with a forced air driven ; motor BARTEC-cv varnost 0.75 - 0.55 kW - 1410 rev / min - 220/380 v ; Chassis; without electrical control panel ; approximate exterior dimensions: 950 x 400 mm x height 400 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
313	1	<b>displacement pump piston eccentric</b> MOUVEX, C4A, displacement pump piston eccentric MOUVEX kind: c4a cast ; flow: 1.2 m³ / h to 175 rev / min to a maximum pressure of 9 bar ; diameter suction and discharge 50 mm; flange ø 165 mm ; Order: geared BARTEC-varnost 2 cv - 1.5 kw - 1405/175 rev / min - 220/380 v ; transmission by coupling; pumping speed: 175 r / min ; gear motor equipped with a forced air driven ; motor BARTEC-cv varnost 0.75 - 0.55 kW - 1410 rev / min - 220/380 v ; Chassis; without electrical control panel ; approximate exterior dimensions: 950 x 400 mm x height 400 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
314	1	<b>vacuum pump</b> BAUDOT HARDOLL, 23 RC 12, vacuum pump baudot hardoll; Type: 23 rc 12; steel ; command cen engine; 15 hp; 1430 r / min; 220 380 v; hp, ; without electrical cabinet ; on stand ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
315	1	<b>vacuum pump</b> BUSCH, RC0025E501, busch vacuum pump types: rc0025e 501 steel ; suction diameter 38 mm; 20 mbar vacuum; pump with a filter ; pump motor drive elektra 1 cv - 0.75 kW - 1395 rev / min - 220/380 v ; monobloc transmission; pumping speed 1395 rev / min; Max speed 16 m³ / h ; without electrical control panel ; approximate exterior dimensions: 550 x 300 mm x height 400 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
316	1	<b>vacuum pump</b> HIBON, AL 05, vacuum pump has hibon liquid ring; Type: al 05; steel ; flow 350 m3 / ha -5 mce has 1450 rev / min; ; control: engine 20 hp; 1450 r / min; 220 380 V ; without electrical cabinet ; on stand ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number Description	Starting Bid €
317	<b>1 liquid ring vacuum pump</b> SIHI, LOHE25003, liquid ring vacuum pump SIHI Type: 25003 Lohe steel ; suction and discharge diameter 30 mm oval flange dimensions 115 x 85 mm ; Order: Leroy Somer 1.5 hp motor - 1.1 kW - 2845 rev / min - 220/380 v ; stand; without electrical control panel ; approximate exterior dimensions: 660 x 320 mm x height 280 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
318	<b>1 centrifugal pump</b> LEFI, L40/200, lefi centrifugal pump types: l40 / 200 No. 277786 stainless steel ; suction diameter 65 mm; flange ø 180 mm 40 mm discharge; flange ø 150 mm ; Order: bbc engine hp 10 hp 7.5 kw 2915 rev / min 380/660 v ; flow 20 m³ / h; mce 40 pressure ; on châssis without electrical control panel ; approximate exterior dimensions: length 1050 mm width 400 mm height 550 ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
319	<b>1 centrifugal pump</b> LEFI, NRCM50160, lefi centrifugal pump types: nrc m 50 160 in magnetically driven stainless steel ; suction flange ø 80 mm 195 mm; ø 50 mm discharge flange 165 mm ; command cen hp engine 3 hp 2.2 kw 1400 rpm / min 220/380 v ; Stand; without electrical control panel ; approximate exterior dimensions: 1000 x 400 mm x height 450 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
320	<b>1 centrifugal pump</b> LEFI, NRCM50160, lefi centrifugal pump types: nrc m 50 160 in magnetically driven stainless steel ; suction flange ø 80 mm 195 mm; ø 50 mm discharge flange 165 mm ; command cen hp engine 3 hp 2.2 kw 1400 rpm / min 220/380 v ; Stand; without electrical control panel ; approximate exterior dimensions: 1000 x 400 mm x height 450 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
321	<b>1 pump</b> RUTSCHI, CN 40-250/236, Rutschi pump; Type: cn 40-250 / 236; stainless steel ; exhaust ø 40 mm flange ø 150 mm ; discharge flange ø 30 mm 140 mm ; flow: 2 m3 / ha 90 mce 3000 rev / min; 6.80 hp ; command: bbc 10 hp engine; hp; 2930 r / min; 220 380 v, ; without electrical cabinet ; on stand ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
322	<b>1 centrifugal pump</b> SALMSON, 50/200, Salmson centrifugal pump; Type: 50/200; stainless steel ; control: 3 hp motor cen; hp; 1400 r / min; 220 380 V ; without electrical cabinet ; on stand ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
323	<b>1 Hydraulic group</b> TROCHOID, Hydraulic group trochoid ; motor "leroy somer" 0.5 hp, 1500 rev / min, 220/380 v, ; capacity of oil tank: 80 liters ; approximate exterior dimensions: 800 x 550 mm, height: 700 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
324	<b>1 water bath 70L</b> bath rectangular, vertical, stainless steel, ; volume 70 liters, posed, with indoor coil, ; flat bottom, put lid ; on ferrule: 5-necked, 1 sensor, 2 resistors "vulcanic" of 4.5 and 2 kw 220/380 v, ; the background: 1 drain ø 16 mm, 1 manifold with pump "SIREM" 220 v, 2700 rev / min, 75 l / min, ; internal dimensions of the tank: 400 x 380 mm, height 490 mm, ; approximate exterior dimensions: 650 x 550 mm, height 650 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number Description	Starting Bid €
325	<b>1 vertical storage tank in stainless steel</b> vertical storage tank in stainless steel on stainless steel frame ; curved bottom with raised lid, volume 350 liters ; to the top of the tank: five nozzles ; on the bottom: a drain pipe ø 50 mm without valve ; internal dimensions of the tank: ø 690 mm x height 900 + 100 = 1000 mm ; approximate exterior dimensions: 850 x 750 mm x height 1,550 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
326	<b>1 vertical storage tank in stainless steel</b> vertical storage tank in stainless steel on stainless steel frame ; curved bottom with raised lid, volume 350 liters ; to the top of the tank: five nozzles ; on the bottom: a drain pipe ø 50 mm without valve ; internal dimensions of the tank: ø 690 mm x height 900 + 100 = 1000 mm ; approximate exterior dimensions: 850 x 750 mm x height 1,550 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
327	<b>1 vertical storage tank in stainless steel</b> vertical storage tank in stainless steel on stainless steel frame ; curved bottom with raised lid, volume 350 liters ; to the top of the tank: five nozzles ; on the bottom: a drain pipe ø 50 mm without valve ; internal dimensions of the tank: ø 690 mm x height 900 + 100 = 1000 mm ; approximate exterior dimensions: 850 x 750 mm x height 1,550 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
328	<b>1 vertical storage tank in stainless steel</b> vertical storage tank in stainless steel on stainless steel frame ; curved bottom with raised lid, volume 350 liters ; to the top of the tank: five nozzles ; on the bottom: a drain pipe ø 50 mm without valve ; internal dimensions of the tank: ø 690 mm x height 900 + 100 = 1000 mm ; approximate exterior dimensions: 850 x 750 mm x height 1,550 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
329	<b>1 vertical storage tank in stainless steel</b> vertical storage tank in stainless steel, insulated ; total volume 200 liters, rounded bottom, cover welded on three feet ; on top: a pipe, on the shell: a level and a pipe ; on the bottom: a central drain ø 80 mm flange ø 220 mm, without valve ; internal dimensions of the tank: ø 500 mm x height 100 + 1100 + 100 = 1300 mm ; approximate exterior dimensions: 590 x 580 mm x height 2,100 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
330	<b>1 vertical storage stainless steel tank</b> VATRON, VATRON vertical storage stainless steel tank on skirt ; curved cover welded bottom, total volume 600 liters ; on top: a pipe, on the shell: a pipe and a drain 26mm valveless ; internal dimensions of the tank: ø 800 mm - heights 50 + 1220 = 1270 mm ; approximate exterior dimensions: 830 x 810 mm - 1400 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
332	<b>1 motovariator</b> SEW, DF 46 DV 160 M 4, motorcycle drive sew 15hp ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
333	<b>1 centrifugal fan</b> FERRARI, ART711, centrifugal fan ferrari Type: art711 steel ; rotor ø 700 mm; composed of ten fins ; suction outlet ø 450 mm 450 x 315 mm ; without control transmission by pulleys and V-belts ; on the frame; without electrical control panel ; approximate exterior dimensions: 1600 x 1400 mm height 1450 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00





Lot	Number Description	Starting Bid €
334	<b>1 centrifugal-type fan</b> GROUPE DESCAMPS, GMB_14_2_LGO, descamps centrifugal-type fan group: gmb_14_2_lgo No. 9,000,065 steel ; rotor ø 560 mm; equipped with eight blades ; aspiration ø 260 mm; refoulement 320 x 220 mm pipe ø 450 mm ; Order: leroy somer 20 hp motor 15 kilowatts 2925 rev / min 380/660 v ; transmission by pulleys and V-belts; speed of 2900 rev / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 1600 x 850 mm x height 1420 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
335	<b>1 centrifugal-type fan</b> GROUPE DESCAMPS, GMB_16_2_RDO, descamps centrifugal-type fan group: gmb_16_2_rdo No. 9,000,069 steel ; rotor ø 640 mm; equipped with eight blades ; aspiration ø 300 mm; refoulement 370 x 250 mm pipe ø 600 mm ; Order: leroy somer engine 25 hp 18.5 kw 2935 rev / min 380/660 v ; transmission by pulleys and V-belts; speed of 2935 rev / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 1600 x 950 mm x height 1630 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
336	<b>1 thermostatic bath, stainless steel, mobile</b> thermostatic bath, stainless steel, mobile ; parallelepipedic tank, 250 liters, ; heating hairpin with adjustable temperature from 0 ° ca 120 ° C ; with circulation pump, ; drain dia 25mm ; dimensions inland tank: length 1005 mm, width 505 mm, height 505 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
337	<b>1 booster</b> ELMO RIETSCHLE, G2BH18101HC31, elmo booster to Rietschle side channel types: g- 2BH1 810 1HC 31 steel ; suction and discharge ø 54 mm; flow 530 m³ / h to 460 mbar ; command siemens engine 15 hp - 11 kilowatts - 2920 rev / min - 380/660 V ; without electrical control panel ; approximate exterior dimensions: 800 x 700 mm; height: 1100 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
338	<b>1 roller conveyor</b> MANNESMANN, type RAZ 39/1, roller conveyor mannesmann tidal kind 39/1 No. 724329 on steel frame ; length 2800 mm width 1000 mm ; consists of 16 steel rollers ø 90 mm with 175 mm ; driven by gearmotor Demac 0.75 hp 0.55 kw 1350 rev / min 220/380 v ; transmission sprocket and chain, linear conveyor speed 2 m / min ~ ; without electrical control panel ; approximate exterior dimensions: length 2800 width 1200 mm height 550 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
339	<b>1 roller conveyor</b> conveyor steel frame roller ; length 1440 mm - width 900 mm, with feet ; equipped ten rolls ø 80 mm with 150 mm - 900 mm length driven by ; gearmotor sew 0.33 hp 0.25 kw 42 rev / min 220/380 v ; transmission gears and chain, linear conveyor speed 12 m / min ; without electrical control panel ; approximate exterior dimensions: 1500 x 1200 mm - height 380 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
340	<b>1 roller conveyor</b> roller conveyor with steel frame ; length 1440 mm - width 900 mm, without legs ; equipped ten rolls ø 80 mm with 150 mm - 900 mm length driven by ; gearmotor sew 0.33 hp 0.25 kw 42 rev / min 220/380 v ; transmission gears and chain, linear conveyor speed 12 m / min ; without electrical control panel ; approximate exterior dimensions: 1500 x 1200 mm - 150 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number Description	Starting Bid €
341	<b>1 roller conveyor</b> roller conveyor with steel frame ; length 1440 mm - width 900 mm, without legs ; equipped ten rolls ø 80 mm with 150 mm - 900 mm length driven by ; gearmotor sew 0.33 hp 0.25 kw 42 rev / min 220/380 v ; transmission gears and chain, linear conveyor speed 12 m / min ; without electrical control panel ; approximate exterior dimensions: 1500 x 1200 mm - 150 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
342	<b>1 roller conveyor</b> roller conveyor with steel frame ; length 1440 mm - width 900 mm, without legs ; equipped ten rolls ø 80 mm with 150 mm - 900 mm length driven by ; gearmotor sew 0.33 hp 0.25 kw 42 rev / min 220/380 v ; transmission gears and chain, linear conveyor speed 12 m / min ; without electrical control panel ; approximate exterior dimensions: 1500 x 1200 mm - 150 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
343	<b>1 roller conveyor</b> roller conveyor with steel frame ; length 1440 mm - width 900 mm, without legs ; equipped ten rolls ø 80 mm with 150 mm - 900 mm length driven by ; gearmotor sew 0.33 hp 0.25 kw 42 rev / min 220/380 v ; transmission gears and chain, linear conveyor speed 12 m / min ; without electrical control panel ; approximate exterior dimensions: 1500 x 1200 mm - 150 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
344	<b>1 filter</b> SIMONETON, MD 4, simoneton filter; Type: md 4; ; 4 mesh pockets cylindrical stainless steel 90 mm dia; height 720 mm; Surface: 0.80 m2 ; vertical cylindrical steel tank; dual stainless steel casing; ; internal dimensions tank: 380 mm dia; height 890 mm; Volume: 100 liters ; bomb cover bolts; ; drain dia 30 mm ; with centrifugal pump Salmson; ; control: 4 hp engine cen; hp; 2830 r / min; 220 380 V ; without electrical cabinet ; on stretcher ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
345	<b>1 stainless steel bell filter</b> stainless steel bell filter; on foot ; bell dimensions: 550 mm dia; height 700 mm ; background bomb with 2 nozzles ; lid swivel bolts ; 15 trays dia stainless steel 440 mm or 4.40 m2 ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
346	<b>1 Mobil filter</b> filtered; mobile; insulation; ; 26 plastic filter plates 320 mm dia; Surface: 2 m2, ; draining 27 mm dia ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
347	<b>1 parallelepipedic tank</b> parallelepipedic tank, vertical, stainless steel, ; total volume 600 liters, flat bottom, open on gussets ; on the bottom: drain 225 x 170 mm, ; corners chamfered ; dimensions inland tank: length 925 mm, width 910 mm, height 840 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
348	<b>1 vertical mixing tank</b> vertical mixing tank with tank EPDM and rotor stator in stainless steel, total volume 4 liters ; on top: a stainless steel bolted cover features three tubing ; tool: rotor stator motor driven Unelec 2.25 hp - 1.65 kW - 2850 rev / min - 220/380 v ; monobloc transmission, grinding speed 2850 rev / min ; on chassis without electrical control panel ; internal dimensions of the tank: ø 160 mm - height 160 mm ; approximate exterior dimensions: 520 x 520 mm - height 850 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00



Lot	Number Description	Starting Bid €
349	<b>1 head of agitation</b> PMS, MS 17996, head of pms agitation type: 17996 ms, a flange 1996 ; command: motoreducteur sew 40 hp from 1470 to 1437 rev / min, 400 690 V ; without electrical cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
350	<b>3 filter cartridge paper</b> MILLIPORE, Millipore filter cartridge has 65 mm dia paper; height 230 mm; cylindrical ; surface area: 0.10 m2 ; tank dimensions 98 mm dia; height 300 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	27.00
351	<b>1 centrifugal pump</b> ENSIVAL, CNK32-12, ensival centrifugal pump types: cnk 32-12; stainless steel ; flow 1 m3 / ha 30 mce has 2950 rev / min ; order: 5.50 hp motor (subject); 2855 r / min; hp; 220 380 V ; without electrical cabinet ; on stand ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
352	<b>1 pump</b> VOTATOR, 1 C 312 L, votator pump; Type: 1 c 312 l; stainless steel; mobile, ; manometer 10 b max; ; control: sterling engine 2 hp; 1500 rev / min; 190,380 v + inverter 93 r / min to 860 r / min ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
353	<b>1 pump</b> BARBERA, pump immergee barbera; vertical ; body polypropylene ; command: ls motor 2.45 hp; 2840 r / min; V 220 380 ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
354	<b>1 pump</b> WOLHFARTH, RAPID R 40/8, wolhfarth pump; Type: rapid r 40/8; 2000; stainless steel body, ; suction and discharge 34 mm dia; without flexible rotor ; control: 1 hp engine; 680 r / min; 220 380 v; including 1 in hp pump; ; without electrical cabinet ; on mobile trolley ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
355	<b>1 cylindrical, vertical tank, stainless steel</b> cylindrical, vertical tank, stainless steel, insulated, ; 300-liter, flat-bottomed cover pose, ; resting on a table 4 feet ; dia central drain 22 mm ; on ferrule 2 tubing ; dimensions inland tank: dia 585 mm height 1100 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
356	<b>1 cylindrical, vertical tank, stainless steel</b> cylindrical, vertical tank, stainless steel, insulated, ; 300-liter, flat-bottomed cover pose, ; resting on a table 4 feet ; dia central drain 22 mm ; on ferrule 2 tubing ; dimensions inland tank: dia 585 mm height 1100 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
357	<b>1 refrigerant</b> refrigerant; parallelepipedic stainless steel tank 160 liters; mobile, ; with 12 media containers mounted on cage with motion control and forth ; by motoreducteur ls + DC electronic speed variator, ; with transparent plastic cover ; with circulation pump and compressor ; dimensions inland tank: length 1100 mm; width 500 mm; height 300 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
358	<b>1 refrigerant</b> FACIS, facis refrigerant; mobile, ; stainless steel interior; steel exterior; ; 1 front door; opening 600 x 1160 mm; depth 500 mm; volume 340 liters ; 4 compartments with doors ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00



Lot	Number	Description	Starting Bid €
359	1	<b>centrifugal fan</b> DELTA NEU, HYPERCOBRA, centrifugal fan delta neu Type: hypercobra steel ; rotor ø 300 mm with 12 blades ; aspiration ø 280 mm ; discharge ø 280 mm ; rotor drive motor ATAV hp hp 1 - 0.75 kW - 2830 rev / min - 220/380 v ; STOVE UNIT transmission; speed of 2830 rev / min; average flow 1500 m³ / h ; without electrical control panel ; approximate exterior dimensions: 620 x 580 mm - height 600 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
360	1	<b>centrifugal fan</b> LE CALOPULSEUR, the centrifugal fan calopulseur No. 17605 steel ; rotor ø 640 mm with 38 blades ; aspiration ø 510 mm ; refoulement 780 x 380 mm ; rotor drive motor 4 hp - 3 kilowatts - 1430 rev / min - 220/380 v ; transmission by pulleys and V-belts; speed of 480 rev / min ; on chassis; without electrical control panel ; approximate exterior dimensions: 1700 x 1150 mm - 1250 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
361	1	<b>conveyor belt</b> SOMEFI, conveyor belt SOMEFI kind TMSI, No. 21830, ; flat plastic strip, width: 300 mm, length 5000 mm, with tension roller 1, ; command: gearmotor "sew" type: 32 dt 63 n4, 0.24 hp, 220 / 380 v, from 1320 to 1331 rev / min, ; pinions and chain roller, ; linear speed: 8 m / min ; on steel frame, without legs, ; without electrical control cabinet, ; approximate exterior dimensions: 5000 x 400 mm, height: 260 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
362	1	<b>conveyor belt</b> SOMEFI, conveyor belt SOMEFI kind TMSI, No. 21830, ; flat plastic strip, width: 300 mm, length 5000 mm, with tension roller 1, ; command: gearmotor "sew" type: 32 dt 63 n4, 0.24 hp, 220 / 380 v, from 1320 to 1331 rev / min, ; pinions and chain roller, ; linear speed: 8 m / min ; on steel frame, without legs, ; without electrical control cabinet, ; approximate exterior dimensions: 5000 x 400 mm, height: 260 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
363	1	<b>conveyor belt</b> SOMEFI, conveyor belt SOMEFI kind TMSI, No. 21830, ; flat plastic strip, width: 300 mm, length 5000 mm, with tension roller 1, ; command: gearmotor "sew" type: 32 dt 63 n4, 0.24 hp, 220 / 380 v, from 1320 to 1331 rev / min, ; pinions and chain roller, ; linear speed: 8 m / min ; on steel frame, without legs, ; without electrical control cabinet, ; approximate exterior dimensions: 5000 x 400 mm, height: 260 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
364	1	<b>conveyor belt</b> SOMEFI, conveyor belt SOMEFI kind TMSI, No. 21830, ; flat plastic strip, width: 300 mm, length 5000 mm, with tension roller 1, ; command: gearmotor "sew" type: 32 dt 63 n4, 0.24 hp, 220 / 380 v, from 1320 to 1331 rev / min, ; pinions and chain roller, ; linear speed: 8 m / min ; on steel frame, without legs, ; without electrical control cabinet, ; approximate exterior dimensions: 5000 x 400 mm, height: 260 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
365	1	<b>conveyor belt</b> SOMEFI, conveyor belt SOMEFI kind TMSI, No. 21830, ; flat plastic strip, width: 300 mm, length 5000 mm, with tension roller 1, ; command: gearmotor "sew" type: 32 dt 63 n4, 0.24 hp, 220 / 380 v, from 1320 to 1331 rev / min, ; pinions and chain roller, ; linear speed: 8 m / min ; on steel frame, without legs, ; without electrical control cabinet, ; approximate exterior dimensions: 5000 x 400 mm, height: 260 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
366	1	<b>conveyor belt</b> SOMEFI, conveyor belt SOMEFI kind TMSI, No. 21830, ; flat plastic strip, width: 300 mm, length 5000 mm, with tension roller 1, ; command: gearmotor "sew" type: 32 dt 63 n4, 0.24 hp, 220 / 380 v, from 1320 to 1331 rev / min, ; pinions and chain roller, ; linear speed: 8 m / min ; on steel frame, without legs, ; without electrical control cabinet, ; approximate exterior dimensions: 5000 x 400 mm, height: 260 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00



Lot	Number	Description	Starting Bid €
367	1	<b>conveyor belt</b> SOMEFI, conveyor belt SOMEFI kind TMSI, No. 21830, ; flat plastic strip, width: 300 mm, length 5000 mm, with tension roller 1, ; command: gearmotor "sew" type: 32 dt 63 n4, 0.24 hp, 220 / 380 v, from 1320 to 1331 rev / min, ; pinions and chain roller, ; linear speed: 8 m / min ; on steel frame, without legs, ; without electrical control cabinet, ; approximate exterior dimensions: 5000 x 400 mm, height: 260 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
368	1	<b>conveyor belt</b> SOMEFI, conveyor belt SOMEFI kind TMSI, No. 21830, ; flat plastic strip, width: 300 mm, length 5000 mm, with tension roller 1, ; command: gearmotor "sew" type: 32 dt 63 n4, 0.24 hp, 220 / 380 v, from 1320 to 1331 rev / min, ; pinions and chain roller, ; linear speed: 8 m / min ; on steel frame, without legs, ; without electrical control cabinet, ; approximate exterior dimensions: 5000 x 400 mm, height: 260 mm, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	25.00
369	2	<b>filter cartridge paper</b> MILLIPORE, Millipore filter cartridge has 65 mm dia paper; height 230 mm; cylindrical ; surface area: 0.10 m2 ; tank dimensions 98 mm dia; height 300 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	27.00
370	1	<b>motor</b> KSB, ksb engine 15 hp, 2900 rev / min, 380/660 v, ; flange mounting ø 350 mm, 4 holes ø 300 mm center distance, ; or legs, 255/215 mm center distance, ; approximate exterior dimensions: 550 x 400 mm, height: 450 m, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
371	1	<b>flange motor</b> LEROY SOMER, flange motor Leroy Somer - 15 hp - 2920 rev / min - 220/380 v, ; shaft ø 42 mm, length: 110 mm, mounting flange ø 350 mm, ; approximate exterior dimensions: 600 x 300 mm, height: 400 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
372	1	<b>pump</b> PCM VAMVER, LBF 6R, pcm vamver pump types: lbf 6r; stainless steel ; control: 2 hp motor; 925 rev / min; 220/380 v, ; ø / O 48 mm; ; on canvas; without electrical control panel, ; approximate exterior dimensions: 1000 x 280 mm; height: 300 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
373	1	<b>peristaltic pump</b> JABSCO, peristaltic pump jabsco; Lubbe and bran; No. 21720-7005; stainless steel; ; control: motovariator sew 0.75 hp; 660 r / min; 220 380 v; hp; ; without electrical cabinet ; on mobile trolley ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
374	1	<b>dual head pumps</b> WATSON, 701FB/R, watson dual head pumps; Type: fb 701 / r / rx ; aluminum body ; input and adjustable output ; gear motor control "Marlow" 0.5 hp; 1350 rev / min; 220/380 v ; pump speed: 89 r / min ; without electrical control panel ; approximate exterior dimensions: 750 x 300 mm; height: 250 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
375	1	<b>dual head pumps</b> WATSON, 701FB/R, watson dual head pumps; Type: fb 701 / r / rx ; aluminum body ; input and adjustable output ; gear motor control "Marlow" 0.5 hp; 1350 rev / min; 220/380 v ; pump speed: 89 r / min ; without electrical control panel ; approximate exterior dimensions: 750 x 300 mm; height: 250 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00





Lot	Number Description	Starting Bid €
376	<b>1 dual head pumps</b> WATSON, 701FB/R, watson dual head pumps; Type: fb 701 / r / rx ; aluminum body ; input and adjustable output ; gear motor control "Marlow" 0.5 hp; 1350 rev / min; 220/380 v ; pump speed: 89 r / min ; without electrical control panel ; approximate exterior dimensions: 750 x 300 mm; height: 250 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
377	<b>1 dual head pumps</b> WATSON, 701FB/R, watson dual head pumps; Type: fb 701 / r / rx ; aluminum body ; input and adjustable output ; gear motor control "Marlow" 0.5 hp; 1350 rev / min; 220/380 v ; pump speed: 89 r / min ; without electrical control panel ; approximate exterior dimensions: 750 x 300 mm; height: 250 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
378	<b>1 dual head pumps</b> WATSON, 701FB/R, watson dual head pumps; Type: fb 701 / r / rx ; aluminum body ; input and adjustable output ; gear motor control "Marlow" 0.5 hp; 1350 rev / min; 220/380 v ; pump speed: 89 r / min ; without electrical control panel ; approximate exterior dimensions: 750 x 300 mm; height: 250 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
379	<b>1 dual head pumps</b> WATSON, 701FB/R, watson dual head pumps; Type: fb 701 / r / rx ; aluminum body ; input and adjustable output ; gear motor control "Marlow" 0.5 hp; 1350 rev / min; 220/380 v ; pump speed: 89 r / min ; without electrical control panel ; approximate exterior dimensions: 750 x 300 mm; height: 250 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
380	<b>1 dual head pumps</b> WATSON, 701FB/R, watson dual head pumps; Type: fb 701 / r / rx ; aluminum body ; input and adjustable output ; gear motor control "Marlow" 0.5 hp; 1350 rev / min; 220/380 v ; pump speed: 89 r / min ; without electrical control panel ; approximate exterior dimensions: 750 x 300 mm; height: 250 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
381	<b>1 vacuum pump</b> MILS, VA 60, vacuum pump mils; Type: is 60, ; maximum vacuum: 73 cmhg; ; control: without engine ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
382	<b>1 vacuum pump a liquid ring</b> BAUDOT HARDOLL, 28 RC 16, vacuum pump a liquid ring-baudot hardoll; Type: 28 rc 16; No. 280094; steel ; command: no motor, ; no electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
383	<b>1 centrifugal pump</b> WORTHINGTON, 40-125, Worthington centrifugal pump; Type: 40-125 (subject) ; command: acec 2810 engine rev / min; hp; 220 380 V ; without electrical cabinet ; on stand ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
384	<b>1 centrifugal pump</b> WORTHINGTON, ECP 32-125, woorthington centrifugal pump; Type: ecp 32-125; stainless steel ; Control: 4 hp engine acec; 2880 r / min; 220 380 v; hp, ; without electrical cabinet ; on stand ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
385	<b>1 3 screw pump</b> SCAM, ACG 70-2 N 2 F/60/50, 3 screw pump scam; Type: acg 70-2 n 2 f / 60 / 509br serial No. 124731 steel ; command: hp engine ; without electric cabinet ; slightly different from r10z31 ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00



Lot	Number Description	Starting Bid €
386	1 <b>vertical cylindrical tank, stainless steel,</b> vertical cylindrical tank, stainless steel, ; 165 liters, bomb bottom, soda bomb lid on skirt + movable frame steel ; galvanized ; on top of tank: 1 trapdoor dia 195 mm with cover bolts ; 2 looks dia 55 mm ; of ferrule 4 handles ; dimensions inland tank: dia 495 mm, height 80 + 790 + 80 = 950 mm ; approximate External dimensions: 620 x 620 mm, height 1550 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
387	2 <b>vertical cylindrical storage tank</b> vertical cylindrical storage tank, stainless steel, ; volume: 140 liters, flat bottom with bolted, without drain cover ; on the top of tank a trapdoor with ø cover 190 mm, ; internal dimensions of the tank: ø 600 mm, height 500 mm, ; approximate exterior dimensions: ø 670 mm, height: 650 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
388	2 <b>vertical cylindrical storage tank</b> vertical cylindrical storage tank, stainless steel, ; volume: 140 liters, flat bottom with bolted, without drain cover ; on the top of tank a trapdoor with ø cover 190 mm, ; internal dimensions of the tank: ø 600 mm, height 500 mm, ; approximate exterior dimensions: ø 670 mm, height: 650 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
389	2 <b>vertical cylindrical storage tank</b> vertical cylindrical storage tank, stainless steel, ; volume: 140 liters, flat bottom with bolted, without drain cover ; on the top of tank a trapdoor with ø cover 190 mm, ; internal dimensions of the tank: ø 600 mm, height 500 mm, ; approximate exterior dimensions: ø 670 mm, height: 650 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
390	2 <b>vertical cylindrical storage tank</b> vertical cylindrical storage tank, stainless steel, ; volume: 140 liters, flat bottom with bolted, without drain cover ; on the top of tank a trapdoor with ø cover 190 mm, ; internal dimensions of the tank: ø 600 mm, height 500 mm, ; approximate exterior dimensions: ø 670 mm, height: 650 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
393	1 <b>melter cylindrical vertical</b> melter, cylindrical, vertical, stainless steel, ; volume: 400 liters, flat bottom, double stainless steel casing, on foot ; dia drain. 50 mm ; dimensions: dia 700 mm, height 1050 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
394	1 <b>storage tank</b> storage tank, vertical cylindrical plastic with indoor coil ; volume 1500 liters, domed bottom welded lid, put on skirt ; on top of tank: four-necked on ferrule tubing ; central drain ø 55 mm with valve ; internal dimensions of the tank: ø 1050 mm x height 200 + 1500 + 200 = 1900 mm ; approximate exterior dimensions: 1100 x 1050 mm x 2350 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
395	1 <b>storage tank</b> storage tank, vertical cylindrical plastic with indoor coil ; volume 1500 liters, domed bottom welded lid, put on skirt ; on top of tank: four-necked on ferrule tubing ; central drain ø 55 mm with valve ; internal dimensions of the tank: ø 1050 mm x height 200 + 1500 + 200 = 1900 mm ; approximate exterior dimensions: 1100 x 1050 mm x 2350 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
397	1 <b>motovariator</b> SEW, KA 126 R 72, motorcycle drive and sew 1.2 4cv ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00



Lot	Number	Description	Starting Bid €
398	1	<b>motovariator</b> SEW, R 80 VUAEFFD, motorcycle drive and sew 1.2 4cv ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
399	1	<b>motovariator</b> BROOK ANSEN, MVB, motovariator brook ansen kind: mvb fixing b35 ; hollow shaft ø 60 mm ; with abb motor power: 7.5 HP - 5.5 kW - 930 rev / min - 220/380 v rossi more reducer ; variable speed 27-162 rev / min ; approximate exterior dimensions: 830 x 350 mm - height 750 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
400	1	<b>vibrating bowl</b> METTLER, LV11, vibrating bowl mettler kind LV11 stainless ; equipped with four vibration speeds ; bowl 180mm, exit chute opening 35 x 25 mm ; supply 220V mono ; approximate exterior dimensions: 330 x 230 mm - height 260 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
401	1	<b>centrifugal fan</b> INGENAIR, DB16, centrifugal fan ingenair Type: DB16 No. 1.2715 / 1 steel ; rotor ø 400 mm with 12 blades ; aspiration ø 280 mm; refoulement 360 x 325 mm ; rotor drive motor siemens hp 1.5 - 1.1 kw - 1415 rev / min - 220/380 v ; monobloc transmission; speed of 1415 rev / min ; without electrical control panel ; approximate exterior dimensions: 880 x 800 mm x height 850 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
402	1	<b>steel propeller fan</b> steel propeller fan ; rotor ø 700 mm equipped with twelve steel blades ; command cem 5.5 hp motor - 4 kilowatts - 1420 rev / min - 220/380 v ; monobloc transmission; speed of 1420 rev / min ; without electrical control cabinet; flange mounting ø 790 mm ; approximate exterior dimensions: ø 790 mm x height 600 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
403	1	<b>steel propeller fan</b> FMV, SO710VIL44, fmv fan coil types: s0710vil44 steel ; rotor ø 710 mm; equipped with seven plastic blades driven by ; engine speeds and two 1.1 hp 1.6 - 0.8 and 1.2 kW - 720 and 900 rev / min - 380 v ; monobloc transmission; rotation speed 720 and 900 r / min ; average flow rate: 10000 m³ at 44 pst (pa) at 720 rev / min and 12,000 m³ / h at 80 pst (pa) of 900 rev / min ; without electrical control cabinet; flange mounting ø 860 mm ; approximate exterior dimensions: 890 x 890 mm - height 250 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
404	1	<b>temperature bath stainless steel 30 liters</b> temperature bath stainless steel, volume 30 liters, ; with two electrical resistors, and an overflow drain ø 10 mm, ; approximate exterior dimensions: 1200 x 160 mm, height: 400 mm,, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
405	1	<b>temperature bath stainless steel 30 liters</b> temperature bath stainless steel, volume 30 liters, ; with two electrical resistors, and an overflow drain ø 10 mm, ; approximate exterior dimensions: 1200 x 160 mm, height: 400 mm,, ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
406	1	<b>conveyor pallets</b> conveyor pallets perforated plastic chain, length: 2300 mm, width: 60 mm, ; consisting of a row of pallets ; command: gearmotor "sew", 0.5 hp 1380 to 1366 rev / min, 220 380 v ; : sprockets and chain roller, ; without electrical cabinet ; on frame, stainless steel, with 2 + 1 fixed feet adjustable in height, ; approximate exterior dimensions: 450 x 2450 mm, height 1150 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00



Lot	Number	Description	Starting Bid €
407	1	<b>roller conveyor</b> MAPE, roller conveyor mape mobile steel frame, ; length 2000 mm, width 370 mm, ; composed of 20 plastic rollers ø 50 mm, with a pitch of 100 mm, ; driven by geared motor 0.5 hp abbot, from 1400 to 1456 rpm / min, 220/380 v, ; flat belt transmission, linear conveyor speed, 15 m / min ~ ; with electrical control cabinet, ; approximate outer dimensions 2100 x 700 mm, height 800 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
408	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
409	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
410	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
411	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
412	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
413	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
414	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
415	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
416	1	<b>roller conveyor</b> galvanized steel frame on roller conveyor ; length 2400 mm x width 900 mm, without legs ; equipped with galvanized steel rollers ø 60 mm with 79 mm ; approximate exterior dimensions: 2500 x 1010 mm x height 80 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00



Lot	Number Description	Starting Bid €
418	<b>1 filter</b> REGIEN SIMONETON, STAR, Regien-simoneton filter; Type: star; stainless steel, ; 1 525 mm dia filter plate; Surface: 0.20 m2, ; 1 cover bolts ; drain dia 13mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
419	<b>1 Filter cartridges</b> Filter cartridges ; body stainless steel 170 mm dia; length 900 mm ; 3 60 mm dia cartridges tissue; length 750 mm ; mobile frame tilts ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
420	<b>1 vacuum pump pallets</b> BECKER, VPF 10, vacuum pump has becker pallets; Type: vpf 10; ; flow rate: 10 m3 / h; Max vacuum: 90%; ; control: halm motor 0.50 hp; 1420 r / min; 220,380 v ; Stand ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
421	<b>1 metering pump</b> DKM CLEXTAL, TO/ST/17, metering pump dkm-Clextral kind: to / st / 17; ; flow rate: 80 liters / ha b 4 ; cycles: 90 strokes / min ; order: bbc motor 0.50 hp; 1360 r / min; 220 380 v, ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
422	<b>1 pump</b> VALVOLE, valvole pump; stainless steel; 1996 ; order: Lafert motor 0.75 hp; 1090 r / min; 230.400 v ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
423	<b>3 container parallelepipedic, vertical, aluminum</b> CMS, container cms, parallelepipedic, vertical, aluminum ; 146 liters, pyramidal bottom, cover laying on frame, mobile, stackable, ; drain valve by guillotine 145 x 145 mm ; internal dimensions container: 745 x 745 mm, height 200 + 180 = 380 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
429	<b>1 cylindrical vertical tank</b> cylindrical, vertical tank, stainless steel, ; 9-liter conical bottom cover bolts, ; on top of tank: 3-neck ; dia central drain 14 mm ; dimensions inland tank: dia 300 mm, height 110 + 80 = 190 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
430	<b>1 gearmotor</b> SEW, R42DT90S4, gearmotor sew types: r42dt90s4 ; shaft ø 25 mm length x 50 mm, b3 fixing ; power 1.5 HP - 1.1 kW - 1400/298 rev / min - 220/380 v ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
431	<b>1 plotting table with marble</b> plotting table with marble, ; marble dimensions: 810 x 520 mm, height: 140 mm, ; approximate exterior dimensions ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
432	<b>1 axial fan</b> axial fan; 6 blades dia 800 mm, ; order: 2 hp motor; 910 r / min; V 220 380 ; without electric cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
433	<b>1 Pall filter cartridge-type filter</b> PALL, SCS94HE71S, Pall filter cartridge-type filter scs94he71s Pall ; filtration 0.45 microns. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	20.00





Lot	Number Description	Starting Bid €
434	<b>4 head of agitation</b> EUROMELANGE, head of agitation EUROMELANGE, ; flange ; command: 1 hp gearmotor sew, from 1400 to 1461 rev / min, 220 380 V ; without electrical cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
435	<b>4 head of agitation</b> EUROMELANGE, head of agitation EUROMELANGE, ; flange ; command: 1 hp gearmotor sew, from 1400 to 1461 rev / min, 220 380 V ; without electrical cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
436	<b>4 head of agitation</b> EUROMELANGE, head of agitation EUROMELANGE, ; flange ; command: 1 hp gearmotor sew, from 1400 to 1461 rev / min, 220 380 V ; without electrical cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
437	<b>4 head of agitation</b> EUROMELANGE, head of agitation EUROMELANGE, ; flange ; command: 1 hp gearmotor sew, from 1400 to 1461 rev / min, 220 380 V ; without electrical cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
438	<b>1 stirrer</b> LIGHTNIN, LP 25, lightnin stirrer type: lp 25, No. 090090-2, ; no trees or turbine ; on mobile and adjustable boom height ; control: vem motor 0.34 hp, 1370 rev / min, 220 380 V ; without electrical cabinet ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
439	<b>1 gearmotor</b> SEW, S42DT80K_4, gearmotor sew types: s42dt80k_4 ; tree right exit ø 25 mm length x 50 mm, b3 fixing ; power cv 0.75 - 0.55 kW - 1380/129 rev / min - 220/380 v ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
440	<b>1 gearmotor</b> SEW, R32DT80K4BM, gearmotor sew types: r32dt80k4bm with brake ; shaft ø 20 mm length x 40 mm, mounting b3 ; power cv 0.75 - 0.55 kW - 1380/104 rev / min - 220/380 v ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
441	<b>1 gearmotor</b> SEW, R32DT71D2, gearmotor sew types: r32dt71d2 ; shaft ø 20 mm length x 40 mm, b3 fixing ; power 0.5 hp - 0.55 kW - 2700/336 rev / min - 220/380 v ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
442	<b>1 gearmotor</b> SEW, R27DR63L4, gearmotor sew types: r27dr63l4 ; shaft ø 25 mm length x 50 mm, b3 fixing ; power cv 0.33 - 0.25 kW - 1300/110 rev / min - 220/380 v ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
443	<b>1 gearmotor</b> SEW, R43DT80K4, gearmotor sew types: r43dt80k4 ; shaft ø 25 mm length x 50 mm, b3 fixing ; power cv 0.75 - 0.55 kW - from 1380 to 1383 rev / min - 220/380 v ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
444	<b>1 gearmotor</b> SEW, R17DT71D4/BMG, gearmotor sew types: r17dt71d4 / bmg with brake ; shaft ø 20 mm length x 40 mm, b3 fixing ; power 0.5 hp - 0.37 kW - 1380/160 rev / min - 220/380 v ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00



Lot	Number	Description	Starting Bid €
445	1	<b>gearmotor</b> FLENDER, Z30MIP4, gearmotor flender Type: z30mip4 ; shaft ø 25 mm length x 50 mm, mounting b3 ; power cv 0.75 - 0.55 kW - 1500/260 rev / min - 220/380 ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
446	1	<b>mechanical balance</b> CHRISTMANN, 30, mechanical balance Christmann Type: 30 No. 21327 with needle dial ; steel plate, dimensions 420 x 420 mm ; Maximum range of 30 kg mini graduation 2.5 kg 50 g ; approximate exterior dimensions: 420 x 420 mm x height 460 mm. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
447	1	<b>mechanical balance</b> AVERY, 08, mechanical balance avery kind: 08 No. 610816 with dial needle ; equipped with a steel plate, dimensions 460 x 460 mm ; Maximum range of 20 kg - mini 2 kg - 20 g graduation ; approximate exterior dimensions: 630 x 620 mm x height 1120 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
448	1	<b>mechanical balance</b> BALBAS, 0110,5X0,5M, mechanical balance balbas Type: 011 0.5 x 0.5 m with needle dial ; equipped with a steel plate, dimensions 600 x 500 mm ; maximum range 100 kg - mini 5 kg - 100 g graduation ; approximate exterior dimensions: 800 x 700 mm x height 1500 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
449	1	<b>mechanical balance</b> mechanical balance with dial needle ; steel plate, dimensions 420 x 420 mm ; mini reach 400 gr - max 12 kg - 20 g graduation ; approximate exterior dimensions: 580 x 480 mm - 1130 mm height. ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
450	1	<b>mechanical balance</b> mechanical balance with needle dial ; steel plate, dimensions 420 x 420 mm ; mini range: 2.5 kg - max 30 kg - Graduation: 50 g ; approximate exterior dimensions: 580 x 420 mm - 1130 mm height ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
451	1	<b>mechanical balance</b> mechanical balance with needle dial ; steel plate, dimensions 410 x 410 mm ; mini range: 1 kg - max: 20 kg - Graduation: 50 g ; approximate exterior dimensions: 550 x 430 mm - height 830 mm ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
452	1	<b>bath thermostatic</b> PAUL CHARVET, bath thermostatic paul charvet, mobile, stainless steel, ; parallelepipedic tank, horizontal, open ; dimensions inland tank: length 1000 mm, width 500 mm, height 215 mm, or 100 liters, ; without heating or cooling, ; with SIREM 162 w pump, 2700 rev / min 230 v ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
453	1	<b>filtration cartridges</b> SPUNFLOW QN, QN10PO37S, filtration cartridges spunflow sb qn10po37s filter type for domnick ; equipped with silicone gaskets, 3 micron filtration ; LOT LOADED ON TRUCK FREE OF CHARGE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	20.00
500	1	<b>Strapper</b> STRAPEX, 350400, Strapping machine STRAPEX type 350 400, 220 volts single phase ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
501	1	<b>Strapper</b> STRAPEX, 350400, Strapping machine STRAPEX type 350 400, 220 volts single phase ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00



Lot	Number	Description	Starting Bid €
502	1	<b>Vertical cylindrical hopper</b> Vertical cylindrical hopper with conical bottom in stainless steel, on mobile frame, total volume 500 liters, on the front: a hatch bolted opening 295 x 250 mm, on the bottom: a drain pipe Ø 45 mm with valve, internal dimensions of the hopper : Ø 930 mm - height 500 + 700 = 1200 mm; approximate external dimensions: 1150 x 1000 mm - height 1350 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
503	1	<b>TRANSFORMER</b> BOIGE ET VIGNAL, 35, BOOM AND VINEYARD TRANSFORMER, TYPE: ATA 400, 35 KVA, PRIMARY: 380.220 V, SECONDARY: 220.380 V ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
504	1	<b>PCM SYSTEM PUMP BODY</b> SEEPEX, year built 1997, PCM SYSTEM PUMP BODY, SEEPEX, TYPE: BN, FROM 1997 ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
505	1	<b>Stainless steel container 445 Liters</b> Stainless steel container 445 Liters; int. 940 x 730 x 640 mm; Manhole with plate Diam. 400 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
506	1	<b>Stainless steel container 445 Liters</b> Stainless steel container 445 Liters; int. 940 x 730 x 640 mm; Manhole with plate Diam. 400 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
507	20	<b>TRUNCONIC TANK</b> TRUNCONIC, VERTICAL, STACKABLE, POSED, ALUMINUM, 15 LITERS, FLAT BOTTOM, FLAT COVER CLIPSE, INTERNAL SIZE TANK: DIA 280/240 MM, HEIGHT 300 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
508	20	<b>TRUNCONIC TANK</b> TRUNCONIC, VERTICAL, STACKABLE, POSED, ALUMINUM, 15 LITERS, FLAT BOTTOM, FLAT COVER CLIPSE, INTERNAL SIZE TANK: DIA 280/240 MM, HEIGHT 300 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
509	1	<b>Lockers Lockers</b> Lockers Lockers ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
510	1	<b>VACUUM</b> MOUZON, MOUZON VACUUM, TYPE: D 2 S, CYLINDRICAL, VERTICAL, CHAMBER DIA 280 MM, HEIGHT 300 MM, CONTROL: MOTOR 1 CV, 220.380 V, WITHOUT ELECTRICAL CABINET, INCLUDING 1 WITH PLASTIC PIPE ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
511	1	<b>agitation</b> MIXEL, TRG80, Stainless steel shaft dia 72 mm, height 650 mm; Control: SEW motor 5.50 HP, 1420 rpm, 220/380 V; Without electrical cabinet ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
512	1	<b>gearmotor</b> SEW, W20DR63L2, New gearmotor SEW type W20DR63L2, shaft Ø 20 mm x length 40 mm, fixation B3, power 0.5 hp - 0.37 kw - 2650/108 rpm - 220/380 v; Approximate dimensions: 300 x 170 mm - height 150 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
513	1	<b>gearmotor</b> SEW, SH37DRS71S4BE05, New gearmotor with SEW brake type SH37DRS71S4BE05; Hollow shaft Ø 20 mm with shrink disk fixing B3; Power 0.5 hp - 0.37 kw - 1380/103 rpm - 220/380 v; Approximate dimensions: 420 x 200 mm - height 150 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
514	1	<b>Centrifugal fan</b> SEAT, SEAT plastic centrifugal fan, 0.37 kw - 0.5 hp - 1500 rpm - 220/380 v, suction and discharge Dia 190 mm, without control cabinet ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00



Lot	Number	Description	Starting Bid €
515	1	<b>booster</b> HWANG HAE, HRB300, HWANG HAE booster type HRB300 1.5 kw - 2 hp - 3000 rpm - 220/380 volts Without cabinet ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
516	1	<b>booster</b> HWANG HAE, HRB300, HWANG HAE booster type HRB300 1.5 kw - 2 hp - 3000 rpm - 220/380 volts Without cabinet ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
517	1	<b>booster</b> HWANG HAE, HRB300, HWANG HAE booster type HRB300 1.5 kw - 2 hp - 3000 rpm - 220/380 volts Without cabinet ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
518	1	<b>PCM pump</b> PCM, MR25U8, serial number 210108, PCM pump type MR25U8 n ° 210108 made of stainless steel, on the top: Ø 70 mm tubing and Ø 47 mm tubing, on the front Ø 70 mm tubing, pump drive by SEW gearbox missing motor, monobloc transmission, gear speed pumping 179 rpm, flow rate from 0.375 to 2.5 m³ / h for a maximum pressure of 8 bar, with stainless steel base, without control cabinet, approximate external dimensions: 1800 x 310 mm - height 320 mm, FOR PIECES, Nb . ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
519	1	<b>STAINLESS STEEL tank 75L</b> STAINLESS STEEL tank 75L OPEN, 1/2 SPHERICAL BOTTOM, PLACED, DIMENSIONS: DIA 495 MM, HEIGHT 300 + 200 = 500 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
520	1	<b>STAINLESS STEEL tank 75L</b> STAINLESS STEEL tank 75L OPEN, 1/2 SPHERICAL BOTTOM, PLACED, DIMENSIONS: DIA 495 MM, HEIGHT 300 + 200 = 500 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
521	1	<b>STAINLESS STEEL tank 75L</b> STAINLESS STEEL tank 75L OPEN, 1/2 SPHERICAL BOTTOM, PLACED, DIMENSIONS: DIA 495 MM, HEIGHT 300 + 200 = 500 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
522	1	<b>STAINLESS STEEL tank 75L</b> STAINLESS STEEL tank 75L OPEN, 1/2 SPHERICAL BOTTOM, PLACED, DIMENSIONS: DIA 495 MM, HEIGHT 300 + 200 = 500 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
523	4	<b>Pneumatic valve with inclined seat</b> SPIRAX-SARCO DN 25 pneumatic inclined seat valve, type PF6 ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
524	31	<b>stainless steel lid</b> stainless steel lid diam 320 mm, internal diameter: 300 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
525	1	<b>booster</b> HWANG HAE, HWANG HAE booster pump type HRB301 1.5 kw - 2 hp 3.4m³ / h ; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
526	1	<b>naked CHASSIS OF CIRCULAR SIEVES</b> RUSSELL, naked CHASSIS OF CIRCULAR SIEVES; RUSSELL FINEX MOBILE CIRCULAR SIEVE CHAMBER, MOTOR CONTROL 2 CV, 220.380 V, 1420 RPM, WITHOUT ELECTRICAL CABINET ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
529	1	<b>freezer for spare</b> freezer for spare;Type VX100;200 volts mono;Dim int : width 430 mm height 570 mm depth 450 mm; ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00



Lot	Number Description	Starting Bid €
530	<b>1 fan for cyclone</b> DELTA NEU, DIV 350, fan for cyclone DELTA NEU type DIV 350; motor SIEMENS 3 cv - 2.2 kw - 2890 tr/min - 220/380 v; Rotor Ø 420 mm 8 blades ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
531	<b>3 Pneumatic valve with inclined seat</b> SPIRAX-SARCO DN 15 pneumatic inclined seat valve, type PF6 ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
532	<b>2 Pneumatic valve with inclined seat</b> SPIRAX-SARCO DN 20 pneumatic inclined seat valve, type PF6 ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
533	<b>9 lid s/s</b> lid s/s diam 380 mm; int diameter : 355 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	10.00
534	<b>1 Laboratory tank</b> Laboratory tank made of stainless steel, vertical, cylindrical, volume: 1 liter, bottom 1/2 spherical, with ferrule on flange, internal dimensions of tank: Ø 110 mm, height 150 mm, approximate dimensions: Ø 170 mm, height : 160 mm. ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	5.00
535	<b>1 Storage tank</b> Storage tank, vertical cylindrical, made of stainless steel, Volume: 140 liters, flat bottom, welded lid, set, On the top: a inspection hatch Ø 200 mm, with bolted tilting lid, on the ferrule: drain pipe Ø 18 mm, lateral outlet, internal dimensions of the tank: Ø 470 mm, height: 830 mm, approximate external dimensions: 530 x 480 mm, height: 950 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
536	<b>1 Storage tank</b> Storage tank, vertical cylindrical, made of stainless steel, Volume: 140 liters, flat bottom, welded lid, set, On the top: a inspection hatch Ø 200 mm, with bolted tilting lid, on the ferrule: drain pipe Ø 18 mm, lateral outlet, internal dimensions of the tank: Ø 470 mm, height: 830 mm, approximate external dimensions: 530 x 480 mm, height: 950 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	15.00
537	<b>1 VERTICAL CYLINDRICAL VESSEL</b> VERTICAL CYLINDRICAL VESSEL, s/s, 700 LITERS, BOTTOM BOTTOM, UPPER DOME SOLDER, ON CHASSIS, ON TOP OF VESSEL: 2 HANDLES, 1 CLIPSE COVER, FOR 1 TANK 1 250 MM VISIT CAP WITH BOLT COVER AND 3 PIECES FOR 1 TANK 1 TRAPPER DIA 250 MM WITH BOLT COVER AND 5 PIECES AND 1 LOAD DIA 100 MM ON VIROLE: 2 CHIVES FOR TILTING OF THE TANK ON CHASSIS DIMENSIONS INTERIOR TANK: DIA 950 MM, HEIGHT 230 + 750 + 230 = 1510 MM ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	30.00
538	<b>1 Vacuum mixer</b> H.HUBBES, year built 1365, Vacuum mixer H, HUBBES n ° 1365 steel with 2 mobile tanks Ø 1000 x 950 mm volume 746 liters equipped with a double jacket; Head up and down by cylinder - stroke approx. 1100 mm - Supplied with hydraulic unit; Power unit drive with AEG motor HP 3 hp - 2.2 kw - 1400 rpm 220/380 v; On the head: a cap equipped with 4 tubings, 1 place for 1 probe, 1 lighting and 1 flip-up inspection hatch Ø 340 mm equipped with 1 view Ø 220 mm; Slow agitation: wiper frame driven by LOHER motor hp 9 hp - 6.6 kw 960 rpm 380/660 v - Transmission by pulleys and V-belts plus reduction; Rapid agitation: 2 shafts equipped with 3 deflocculators Ø 300 mm driven by hydraulic motors - Delivered with HYDROPA control unit controlled by 2 SIEMENS motors hp 50 hp - 37 kw - 1400 rpm 380/660 v; Without control cabinet; Approximate external dimensions of the mixer: 2700 x 1300 mm - height 2700 mm, head raised 3800 mm; Approximate external dimensions of the central unit: 2000 x 1600 mm - height 1500 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	1,050.00





Lot	Number Description	Starting Bid €
539	<b>1 Stirrer on a mobile frame</b> Stirrer on a mobile frame without shaft and without tools; Head up and down by steering wheel and worm, stroke 1200 mm; LEROY SOMER geared motor drive 0.5 hp - 0.37 kw - 2000 rpm - 100 v continuous; With variation box type MSV3; Approximate external dimensions: 950 x 600 mm - height 1900 mm ; lot loaded on truck free of charge (if container or packaging : additionnal fee)	50.00



**TROOSTWIJK**  
INDUSTRIAL AUCTIONEERS & VALUERS SINCE 1930

## General conditions Online Auction TroostwijkAuctions.com

### 1. Definitions

Website:	the website <a href="http://www.TroostwijkAuctions.com">www.TroostwijkAuctions.com</a> , which is maintained by Troostwijk Veilingen B.V., with its registered seat in Amsterdam;
User:	the one who has registered on the Website;
Troostwijk:	Troostwijk Veilingen B.V. and/or its subsidiary/ies or sister company/ies as reported on the Website;
Purchase Sum:	the amount of the highest – allocated – bid increased by: - mark-up above the highest bid and - the V.A.T. owed
Registration:	registration of User on the Website by means of filling in completely the registration form found on the Website;
Bid:	each amount bid by User in the auction for a lot;
Lot:	an article, or a number of articles that are auctioned together (under one number);
Auction:	the public sale of moveable goods organized by Troostwijk via the internet;
Seller:	the one who has commissioned a Lot to be auctioned;
Purchaser:	the User to whom the Lot is allocated;
User's Agreement:	the agreement between Troostwijk and the User;
Purchase Agreement:	the purchase agreement between the Purchaser and the Seller;
Delivery:	the actual delivery of the Lot to the Purchaser or to his authorized representative;
General Terms and Conditions for the the User:	the General Terms and Conditions for access to and use of Website;
General Online Auction Terms and Conditions:	these General Terms and Conditions;
Specific Online Auction Terms and Conditions:	the additional, supplementary to or in departure from the General Terms and Conditions for the User and the General Terms and Conditions of the Online Auction, valid terms and conditions, as reported on the Website for the Auction in question;
Allocation:	the declaration by the "Commissaire PriEUR" of Troostwijk that a Lot or combination of Lots has been allocated to the highest bidder upon payment of the Purchase Price.

### Article 2. Applicability

- 2.1 The General Online Auction Terms and Conditions are applicable to the relationship between Sellers or Users on the one hand and Troostwijk on the other in the participation in Auctions.
- 2.2 The applicability of General Terms and Conditions other than the present one, General Terms and Conditions for the User, the Specific Terms and Conditions of the Online Auction, is excluded.

### Article 3. The Auction

- 3.1 Troostwijk reserves the right to cancel an Auction, to terminate an Auction earlier than reported on the Website or to extend one. In case of a technical malfunction of the Website, causing it to be not completely accessible and/or inaccessible to Users, Troostwijk has the right to extend the Auction by 24 hours.
- 3.2 The User states by his Registration that he is familiar with and agrees with the special circumstances of an internet auction and with the technical imperfections that can arise. Troostwijk denies any liability for whatever damage that may arise in any way, directly or indirectly, including but not limited to the damage arising from the use of the Website, unless there has been deliberate or conscious negligence by Troostwijk. More particularly, Troostwijk accepts no liability for any damage whatsoever that arises in any way by or from:
- actions performed by the User that may have been inspired by the information placed on the Website;
  - the impossibility of using the Website (completely) and/or another malfunction in the Website or the supporting system;
  - the Lots not meeting the specifications as reported on the Website;
  - the fact that the information on the Website is incorrect, incomplete or out of date;
  - errors in the software of the Website and/or the supporting system;
  - the unlawful use of systems, including the Website of Troostwijk, by a third party;
  - actions by the Seller after the User has concluded a Purchase Agreement with the Seller.



#### **Article 4. Organization of the Auction**

- 4.1 The organization, preparation and carrying out of the Auction is to be done by Troostwijk.
- 4.2 Without having to give any reason, Troostwijk has the authority before or during the Auction:
- not to recognize a Bid as such;
  - to exclude one or several Users from the Auction;
  - to collect objects into Lots, to split Lots or to remove Lots from the auction;
  - to repair mistakes made by Troostwijk in offers and/or allocations, without the User being able to make use of these errors and/or derive any rights from them;
  - to take other measures that are, in its judgment, necessary.
- 4.3 Troostwijk has the authority to set as a condition for participation in certain Auctions and/or bids on certain Lots that a User provide a bank guarantee beforehand to the satisfaction of Troostwijk.
- 4.4 The judgment of Troostwijk concerning that which has occurred during the Auction is binding.

#### **Article 5. Bids; Purchase Agreement**

- 5.1 The User can place a Bid on the Website on one or several Lots. Every bid is unconditional, irrevocable and without reservation. Bids are placed exclusive of mark-up and V.A.T. Troostwijk is authorized to place bids on behalf of third parties.
- 5.2 If a Lot is also brought to auction together with one or several other Lots as a combination, this will be reported on the individual page of the Lot. In that case, bids can be placed first on the individual Lots of the combination and after the closing of all individual Lots, bids can be placed on the combined Lot. Individual Lots can be allocated only if the total amount of the highest sustainable bids on the individual lots is higher than the highest sustainable bid on the combination. The combination will be allocated solely if the highest sustainable bid on the combination is higher than the total amount of the highest sustainable bids on the individual lots.
- 5.3 Bids can be placed in the form of a 'static bid' or 'auto bid.' In a static bid, the User places a bid in the form of a fixed amount per Lot. In an automatic bid the User indicates the maximum price he is prepared to pay for the Lot. The auction system sees to it that, after outbidding by a third party, the minimally possible higher bid is introduced in the name of the User, as long as the maximum indicated by the User has not been reached. An automatic bid can be eliminated by the User solely by placing a static bid that is higher than the previous bid.
- 5.4 The Purchase Agreement arises through Allocation. Allocation is generally given to the User who has made the highest Bid.
- 5.5 The Purchaser receives confirmation within 48 hours after the Auction has been closed (not including Saturdays, Sundays and holidays) by email on behalf of the Seller(s) that the Purchase Agreement has been made. If the User does not receive any e-mail within the period mentioned above, this means that his Bid has not been accepted.  
The "Commissaire Priseur" of Troostwijk then has the right not to allocate.
- 5.6 The risk of the Lot(s) is transferred to the Purchaser at the moment of Allocation.
- 5.7 Troostwijk is not a party to the Purchase Agreement but merely mediates in the creation of purchase agreements. If the auction is a forced sale, this will be reported in the Specific Terms and Conditions of the Online Auction.
- 5.8 In the event that the auction occurs in the presence of a Commissaire Priseur, civil-law notary or court bailiff, he will lead the Auction and the bids placed there and the Allocations.

#### **Article 6. Guarantees, claims and indemnities**

- 6.1 In respect of the Lots and possible claims of third parties to these, Troostwijk and/or the Seller will provide no single guarantee of whatever kind. The Purchaser waives all rights except those that are his by mandatory law.
- 6.2 The Lots are sold for what they are worth in the state in which they are found on the date of Allocation with all benefits and burdens attached there to Troostwijk and/or the Seller do not give any indemnity of any kind for visible or hidden defects or any kind of guarantee in connection with completeness, numbers, functioning, usability, saleability, the existence or non-existence of rights of third parties and/or the possibility of transfer to third parties. Defects of whatever kind, disappointed expectations of the Purchaser and/or the receiving third parties do not bestow any rights at all to damages and/or discount. The Purchaser is assumed to have carefully investigated the Lot bought by him beforehand.
- 6.3 If, in respect of the lots, claims by third parties are made on the basis of the retention of ownership, the Purchaser is obligated to hold the lot(s) in question for those third parties, under the obligation to transfer it to the third parties at the first request or to come to a suitable arrangement with the third parties.
- 6.4 The Purchaser indemnifies Troostwijk and/or the Seller against every claim by a third party in connection with the Purchase Agreement.

#### **Article 7. The Purchaser's payment obligations**

- 7.1 The Purchaser has the obligation to transfer the Purchase Price to an account number to be indicated by Troostwijk within three days (not including Saturdays, Sundays and holidays) after confirmation of the Purchase Agreement. Payment should be made in Euros or in another



currency to be indicated by Troostwijk.

- 7.2 In the event of a late payment of the Purchase Price, 15% of the Purchase Price, being a forfeit amount for collection costs and/or extrajudicial costs will be charged to the Purchaser by Troostwijk, increased by the statutory commercial interest on the outstanding amount, increased by 3% on an annual basis, starting on the day on which the payment should have occurred until the day of effective payment.
- 7.3 Payments are intended first to decrease the costs, then the interest charges, then finally the Purchase Price.

#### **Article 8. Viewing days, auction days, delivery days**

- 8.1 Whoever enters the buildings and grounds on viewing days or on the day of delivery does so entirely at his own risk. The instructions of Troostwijk and/or persons called in by Troostwijk are to be followed. Troostwijk and the Seller do not accept any liability for damages arising from entering the buildings or grounds.

#### **Article 9. Delivery**

- 9.1 If and as soon as the Purchaser has met all his payment obligations, the Purchaser can pick up the Lot(s) in question during the hours and at the place specified by Troostwijk, after having showing a proper identification. This is the Delivery. The Buyer is obligated to pick up the lot(s) no later than the date specified in the Specific Terms and Conditions of the Online Auction. Troostwijk can stipulate that (a) certain Lot(s) can be picked up only after Lots have been delivered.
- 9.2 After delivery the Purchase Agreement can no longer be terminated or destroyed by the Purchaser.
- 9.3 If it appears that a Lot cannot be delivered because of claims by third parties or because of the fact that the delivery would cause unacceptable damage to the buildings or premises where the Lot is situated or for other reasons appears to be strongly objectionable, Troostwijk is authorized to terminate the Purchase Agreement. This termination occurs by e-mail and/or registered letter to the Purchaser at the address supplied by the Purchaser, after which Troostwijk and/or the Purchaser is/are no longer held to restitution of the amounts already paid by the Purchaser to Troostwijk for the purchase of the Lot(s).
- 9.4 The Purchaser whose Lot(s) hinder the picking up of other Lots is obligated to see to it immediately after reception of an e-mail or other written documents from Troostwijk that the Lot(s) are picked up. The arranging of possible storage by third parties is at the Purchaser's own charge and risk.
- 9.5 The Purchaser is obligated to dismantle or demolish his Lot(s) and to pick them up. He is completely liable for damage done to the property of others in connection therewith. He is further obligated to indemnify Troostwijk and the Seller against all claims by third parties arising from the dismantling, demolishing and/or the picking up of the Lot(s).
- 9.6 During the dismantling, demolishing and picking of the Lot(s), the Purchaser is obligated to follow the instructions of Troostwijk and/or persons called in by Troostwijk.
- 9.7 The Purchaser is obligated to see to it that he or whoever takes care on his behalf of the dismantling, demolishing or transport has the proper required permits. Troostwijk and/or the Seller cannot be held accountable for the lack of the necessary documents and/or the infringement of governmental regulations in the dismantling, demolishing and/or transport by or on behalf of the Purchaser.
- 9.8 In situations in which it is/appears necessary to dismantle buildings for (an) allocated Lot(s), this can occur only through prior consultation with and written authorization from Troostwijk and under these terms and conditions set in the granting of permission.
- 9.9 If Troostwijk stipulates such, a deposit will be made in connection with possible damage to the buildings. If such damage occurs, the deposit will be applied to the payment for repair of the damage, subject to the obligation of the Purchaser to pay compensation for more damage. If no damage results, the deposit will be restored to the Purchaser.

#### **Article 10. Restrictions concerning the sale of certain lots.**

- 10.1 Machines and production components are generally sold in conformity with technical specifications as well as with French legal safety norms or regulations. This conformity is attested to either by a seal of conformity (for a machine put into service after 15 January 1981 – (French) Decrees 80-543 and 544) or a CE seal (machines put into service after 15 January 1993 – (French) decrees 93-40) if they have not undergone significant modifications to the safety mechanisms.
- 10.2 When the item for sale does not conform to technical specifications, or to French legal safety norms or regulations, it is reminded to buyers that this item must be imperatively refurbished in regards to the above norms and/or regulations during its installation and/or use after its auction. Buyers commit to refurbish the item in conformity with their enforceable norms and/or regulations. Items are sold as spare parts.
- 10.3 Machines which are non-compliant and not dangerous are sold as unfit for production. They may be sold in the condition as seen:
- 1 – to an individual or legal entity where the material is not destined for use on French territory. It shall be the buyer's responsibility to conform to the legislation of the country where the material is to be used.
  - 2 – to an individual or legal entity having the status of retailer, salvage dealer, re-manufacturer, scrap merchant, scrap metal dealer or collector who commits beforehand to be responsible for and to ensure conformity to required standards, for possible assignment to a client-operator.
  - 3 – to any buyer as a source of spare parts and who testifies, by accepting the general and particular conditions, not to use or assign the



material for production.

- 10.4 Machines which are considered dangerous ((French) Decrees dated 5 March and 24 June 1993) and non-compliant may only be sold under categories 1 and 2 of the preceding article.
- 10.5 Buyers formally commit to respect the above criteria by accepting the general and particular conditions of sale.
- 10.6 The measures contained in articles 10.1 to 10.4 are not applicable in the case of auctions by order of the court held after the vendor has been declared legally bankrupt.

#### **Article 11. Termination**

- 11.1 If the Purchaser does not fulfill any obligation in the Purchase Agreement, including (but not limited to):
- (i) not paying the Purchase Price or not paying it completely on time;
  - (ii) not picking up the Lot(s) on time and/or
  - (iii) not providing the information required before delivery, the Purchaser is legally in default without further notice of default being required, and Troostwijk can terminate the Purchase Agreement on behalf of the Seller. In that case Troostwijk is free to allocate the Lot(s) to another party without Troostwijk and/or the Seller being liable for any damages.
- 11.2 In case of termination as intended in 11.1, the Purchaser in default must pay, in addition to the mark-up, a forfeit amount of 25 % of the Purchase Price to cover administrative, storage, insurance and transport costs, etc., subject to the right of Troostwijk and/or the Seller to demand complete compensation for damages.

#### **Article 12. Liability**

- 12.1 The liability of Troostwijk, if and insofar as the other remaining stipulations of the General Terms and Conditions of the Online Auction, the Terms and Conditions for the User and (if applicable) the Specific Terms and Conditions of the Online Auction are applied, will still be limited to the amount to which the liability insurance of Troostwijk accords Troostwijk in the instance in question, increased by the amount of excess according to the policy in question, or, if it is less, to the invoiced amount that is involved with the commission. This limitation does not apply in the event of deliberate or gross negligence by Troostwijk.
- 12.2 Troostwijk is not liable for indirect or consequential loss. Further, all liability of Troostwijk in connection with any defect in the Lot(s) or in respect of (alleged) infringement of the rights of (the intellectual property of) third parties is excluded. The Purchaser declares that he is familiar with the fact that, in respect of Lot(s), possible rights (of intellectual property) rest with third parties.
- 12.3 In consulting with third parties, Troostwijk will take the necessary caution into consideration. Troostwijk is also not liable for possible shortcomings of these third parties.

#### **Article 13. Adjustments; Effect**

- 13.1 If and insofar as any stipulation of the General Terms and Conditions of the Online Auction is null and void or is nullified, the remaining stipulations will remain undiminished in force. Troostwijk will then determine a new stipulation to replace the null/nullified stipulation, by which the intent of the null/nullified stipulation will be taken into consideration.
- 13.2 Troostwijk can, in addition to these General Online Auction Terms and Conditions, declare the Specific Online Auction Conditions to be applicable. Notification of the Specific Online Auction Terms and Conditions will be made before the Auction. If and insofar as the Specific Online Auction Terms and Conditions are in contradiction with the General Terms and Conditions of the Online Auction, the Specific Online Auction Terms and Conditions will have preference.
- 13.3 Departure from these General Terms and Conditions of the Online Auction is permitted only if it is fixed in writing by an authorized representative of Troostwijk.
- 13.4 Troostwijk reserves the right to amend these General Terms and Conditions of the Online Auction. Amendments will take effect 24 hours after these have been sent by e-mail to the User. These terms and conditions replace all previous general terms and conditions, unless explicitly stated otherwise by Troostwijk.

#### **Article 14. Applicable law**

- 14.1 Dutch law is applicable to these General Terms and Conditions of the Online Auction and the legal relationships that are associated with the Auction.
- 14.2 The Dutch text of the General Terms and Conditions of the Online Auction is the original text. In the event that the General Terms and Conditions of the Online Auction are used in several languages; the Dutch text will therefore be given preference in case of lack of clarity or contradictions.
- 14.3 The District Court Amsterdam is authorized (subject to the possibility of appeal and to laws that state otherwise) to decide in differences





arising from these terms and conditions, to the exclusion of every other instance.

### Did you know?

- we organise auctions in **25 countries**
- we have **1,6 million** page views on a top day

# *The European Online Auctioneer and Valuer*

### 1300 Auctions

Troostwijk conducts  
annually **1300** auction sales  
all over Europe

### Statistics

- Every year we deal with **50.000** bidders
- from 95 different countries
- over 500.000 registrations

### 15 Countries

Troostwijk has  
own offices  
in 15 European countries

### 85 Years

Troostwijk is conducting  
auctions since 1930 and  
has 85 years of experience